

---

Subject: [PATCH 1/7] SUNRPC: create rpcbind client in passed network namespace context

Posted by [Stanislav Kinsbursky](#) on Thu, 15 Dec 2011 16:01:06 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Rpcbnd clients are per network namespace.

Signed-off-by: Stanislav Kinsbursky <[skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)>

---

net/sunrpc/rpcb\_clnt.c | 11 ++++++-----  
1 files changed, 6 insertions(+), 5 deletions(-)

diff --git a/net/sunrpc/rpcb\_clnt.c b/net/sunrpc/rpcb\_clnt.c

index 46f5915..43eff03 100644

--- a/net/sunrpc/rpcb\_clnt.c

+++ b/net/sunrpc/rpcb\_clnt.c

@@ -344,11 +344,12 @@ out:

return result;

}

-static struct rpc\_clnt \*rpcb\_create(char \*hostname, struct sockaddr \*srvaddr,

- size\_t salen, int proto, u32 version)

+static struct rpc\_clnt \*rpcb\_create(struct net \*net, char \*hostname,

+ struct sockaddr \*srvaddr, size\_t salen,

+ int proto, u32 version)

{

struct rpc\_create\_args args = {

- .net = &init\_net,

+ .net = net,

.protocol = proto,

.address = srvaddr,

.addrsz = salen,

@@ -708,8 +709,8 @@ void rpcb\_getport\_async(struct rpc\_task \*task)

dprintk("RPC: %5u %s: trying rpcbind version %u\n",

task->tk\_pid, \_\_func\_\_, bind\_version);

- rpcb\_clnt = rpcb\_create(clnt->cl\_server, sap, salen, xprt->prot,

- bind\_version);

+ rpcb\_clnt = rpcb\_create(xprt->xprt\_net, clnt->cl\_server, sap, salen,

+ xprt->prot, bind\_version);

if (IS\_ERR(rpcb\_clnt)) {

status = PTR\_ERR(rpcb\_clnt);

dprintk("RPC: %5u %s: rpcb\_create failed, error %ld\n",