

---

Subject: [PATCH 2/7] SUNRPC: register rpcbind programs in passed network namespace context

Posted by [Stanislav Kinsbursky](#) on Thu, 15 Dec 2011 16:01:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Registering rpcbind program requires rpcbind clients, which are per network namespace context.

Signed-off-by: Stanislav Kinsbursky <[skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)>

---

```
include/linux/sunrpc/clnt.h | 5 +++--
net/sunrpc/rpcb_clnt.c      | 8 +++++---
net/sunrpc/svc.c           | 10 ++++++-----
3 files changed, 12 insertions(+), 11 deletions(-)
```

diff --git a/include/linux/sunrpc/clnt.h b/include/linux/sunrpc/clnt.h

index 53afa56..1e56469 100644

--- a/include/linux/sunrpc/clnt.h

+++ b/include/linux/sunrpc/clnt.h

@@ -138,8 +138,9 @@ void rpc\_task\_release\_client(struct rpc\_task \*);

int rpcb\_create\_local(void);

void rpcb\_put\_local(void);

-int rpcb\_register(u32, u32, int, unsigned short);

-int rpcb\_v4\_register(const u32 program, const u32 version,

+int rpcb\_register(struct net \*, u32, u32, int, unsigned short);

+int rpcb\_v4\_register(struct net \*net, const u32 program,

+ const u32 version,

const struct sockaddr \*address,

const char \*netid);

void rpcb\_getport\_async(struct rpc\_task \*);

diff --git a/net/sunrpc/rpcb\_clnt.c b/net/sunrpc/rpcb\_clnt.c

index 43eff03..ea87b0c 100644

--- a/net/sunrpc/rpcb\_clnt.c

+++ b/net/sunrpc/rpcb\_clnt.c

@@ -425,7 +425,7 @@ static int rpcb\_register\_call(struct rpc\_clnt \*clnt, struct rpc\_message \*msg)

\* IN6ADDR\_ANY (ie available for all AF\_INET and AF\_INET6

\* addresses).

\*/

-int rpcb\_register(u32 prog, u32 vers, int prot, unsigned short port)

+int rpcb\_register(struct net \*net, u32 prog, u32 vers, int prot, unsigned short port)

{

struct rpcbind\_args map = {

.r\_prog = prog,

@@ -436,7 +436,7 @@ int rpcb\_register(u32 prog, u32 vers, int prot, unsigned short port)

struct rpc\_message msg = {

```

    .rpc_argp = &map,
};
- struct sunrpc_net *sn = net_generic(&init_net, sunrpc_net_id);
+ struct sunrpc_net *sn = net_generic(net, sunrpc_net_id);

dprintk("RPC:    %sregistering (%u, %u, %d, %u) with local "
"rpcbind\n", (port ? "" : "un"),
@@ -563,7 +563,7 @@ static int rpcb_unregister_all_protocols(struct sunrpc_net *sn,
* service on any IPv4 address, but not on IPv6. The latter
* advertises the service on all IPv4 and IPv6 addresses.
*/
-int rpcb_v4_register(const u32 program, const u32 version,
+int rpcb_v4_register(struct net *net, const u32 program, const u32 version,
    const struct sockaddr *address, const char *netid)
{
    struct rpcbind_args map = {
@@ -575,7 +575,7 @@ int rpcb_v4_register(const u32 program, const u32 version,
    struct rpc_message msg = {
        .rpc_argp = &map,
    };
- struct sunrpc_net *sn = net_generic(&init_net, sunrpc_net_id);
+ struct sunrpc_net *sn = net_generic(net, sunrpc_net_id);

    if (sn->rpcb_local_clnt4 == NULL)
        return -EPROTONOSUPPORT;
diff --git a/net/sunrpc/svc.c b/net/sunrpc/svc.c
index 6e03888..e9c42ad 100644
--- a/net/sunrpc/svc.c
+++ b/net/sunrpc/svc.c
@@ -813,7 +813,7 @@ static int __svc_rpcb_register4(const u32 program, const u32 version,
    return -ENOPROTOOPT;
}

- error = rpcb_v4_register(program, version,
+ error = rpcb_v4_register(&init_net, program, version,
    (const struct sockaddr *)&sin, netid);

/*
@@ -821,7 +821,7 @@ static int __svc_rpcb_register4(const u32 program, const u32 version,
* registration request with the legacy rpcbind v2 protocol.
*/
if (error == -EPROTONOSUPPORT)
- error = rpcb_register(program, version, protocol, port);
+ error = rpcb_register(&init_net, program, version, protocol, port);

    return error;
}
@@ -860,7 +860,7 @@ static int __svc_rpcb_register6(const u32 program, const u32 version,

```

```

    return -ENOPROTOOPT;
}

- error = rpcb_v4_register(program, version,
+ error = rpcb_v4_register(&init_net, program, version,
    (const struct sockaddr *)&sin6, netid);

/*
@@ -963,14 +963,14 @@ static void __svc_unregister(const u32 program, const u32 version,
{
    int error;

- error = rpcb_v4_register(program, version, NULL, "");
+ error = rpcb_v4_register(&init_net, program, version, NULL, "");

/*
 * User space didn't support rpcbind v4, so retry this
 * request with the legacy rpcbind v2 protocol.
 */
if (error == -EPROTONOSUPPORT)
- error = rpcb_register(program, version, 0, 0);
+ error = rpcb_register(&init_net, program, version, 0, 0);

dprintk("svc: %s(%sv%u), error %d\n",
    __func__, progname, version, error);

```

---