
Subject: [PATCH v2] Allow ipv6 proxies and arp proxies be shown with iproute2
Posted by [Tony Zelenoff](#) on Fri, 27 Jan 2012 08:28:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

Add ability to return neighbour proxies list to caller if
it sent full ndmsg structure and has NTF_PROXY flag set.

Before this patch (and before iproute2 patches):

```
$ ip neigh add proxy 2001::1 dev eth0
$ ip -6 neigh show
$
```

After it and with applied iproute2 patches:

```
$ ip neigh add proxy 2001::1 dev eth0
$ ip -6 neigh show
2001::1 dev eth0 proxy
$
```

Compatibility with old versions of iproute2 is not broken,
kernel checks for incoming structure size and properly
works if old structure is came.

[v2]

- * changed comments style.
- * removed useless line with continue and curly bracket.
- * changed incoming message size check from equal to more or equal.

CC: davem@davemloft.net
CC: kuznet@ms2.inr.ac.ru
CC: netdev@vger.kernel.org
CC: xemul@parallels.com
Signed-off-by: Tony Zelenoff <antonz@parallels.com>

```
net/core/neighbour.c | 90 ++++++
1 files changed, 87 insertions(+), 3 deletions(-)
```

diff --git a/net/core/neighbour.c b/net/core/neighbour.c

index 6dbcf51..a022072 100644

--- a/net/core/neighbour.c

+++ b/net/core/neighbour.c

```
@@ -2111,6 +2111,35 @@ nla_put_failure:
    return -EMSGSIZE;
}
```

```
+static int pneigh_fill_info(struct sk_buff *skb, struct pneigh_entry *pn,
+    u32 pid, u32 seq, int type, unsigned int flags,
+    struct neigh_table *tbl)
```

```

+{
+ struct nlmsgghdr *nlh;
+ struct ndmsg *ndm;
+
+ nlh = nlmsg_put(skb, pid, seq, type, sizeof(*ndm), flags);
+ if (nlh == NULL)
+ return -EMSGSIZE;
+
+ ndm = nlmsg_data(nlh);
+ ndm->ndm_family = tbl->family;
+ ndm->ndm_pad1 = 0;
+ ndm->ndm_pad2 = 0;
+ ndm->ndm_flags = pn->flags | NTF_PROXY;
+ ndm->ndm_type = NDA_DST;
+ ndm->ndm_ifindex = pn->dev->ifindex;
+ ndm->ndm_state = NUD_NONE;
+
+ NLA_PUT(skb, NDA_DST, tbl->key_len, pn->key);
+
+ return nlmsg_end(skb, nlh);
+
+nla_put_failure:
+ nlmsg_cancel(skb, nlh);
+ return -EMSGSIZE;
+}
+
static void neigh_update_notify(struct neighbour *neigh)
{
    call_netevent_notifiers(NETEVENT_NEIGH_UPDATE, neigh);
@@ -2156,23 +2185,78 @@ out:
    return rc;
}

+static int pneigh_dump_table(struct neigh_table *tbl, struct sk_buff *skb,
+ struct netlink_callback *cb)
+{
+ struct pneigh_entry *n;
+ struct net *net = sock_net(skb->sk);
+ int rc, h, s_h = cb->args[3];
+ int idx, s_idx = idx = cb->args[4];
+
+ read_lock_bh(&tbl->lock);
+
+ for (h = 0; h <= PNEIGH_HASHMASK; h++) {
+ if (h < s_h)
+ continue;
+ if (h > s_h)
+ s_idx = 0;

```

```

+ for (n = tbl->phash_buckets[h], idx = 0; n; n = n->next) {
+   if (dev_net(n->dev) != net)
+     continue;
+   if (idx < s_idx)
+     goto next;
+   if (pneigh_fill_info(skb, n, NETLINK_CB(cb->skb).pid,
+     cb->nlh->nlnmsg_seq,
+     RTM_NEWNEIGH,
+     NLM_F_MULTI, tbl) <= 0) {
+     read_unlock_bh(&tbl->lock);
+     rc = -1;
+     goto out;
+   }
+   next:
+   idx++;
+ }
+ }
+
+ read_unlock_bh(&tbl->lock);
+ rc = skb->len;
+out:
+ cb->args[3] = h;
+ cb->args[4] = idx;
+ return rc;
+
+}
+
static int neigh_dump_info(struct sk_buff *skb, struct netlink_callback *cb)
{
    struct neigh_table *tbl;
    int t, family, s_t;
+ int proxy = 0;
+ int err = 0;

    read_lock(&neigh_tbl_lock);
    family = ((struct rtgenmsg *) nlmsg_data(cb->nlh))->rtgen_family;
+
+ /* check for full ndmsg structure presence, family member is
+  * the same for both structures
+  */
+ if (nlmsg_len(cb->nlh) >= sizeof(struct ndmsg) &&
+     ((struct ndmsg *) nlmsg_data(cb->nlh))->ndm_flags == NTF_PROXY)
+   proxy = 1;
+
    s_t = cb->args[0];

- for (tbl = neigh_tables, t = 0; tbl; tbl = tbl->next, t++) {
+ for (tbl = neigh_tables, t = 0; tbl && (err >= 0);

```

```

+   tbl = tbl->next, t++) {
+   if (t < s_t || (family && tbl->family != family))
+       continue;
+   if (t > s_t)
+       memset(&cb->args[1], 0, sizeof(cb->args) -
+           sizeof(cb->args[0]));
-   if (neigh_dump_table(tbl, skb, cb) < 0)
-       break;
+   if (proxy)
+       err = neigh_dump_table(tbl, skb, cb);
+   else
+       err = neigh_dump_table(tbl, skb, cb);
+   }
+   read_unlock(&neigh_tbl_lock);

```

--

1.7.1

Subject: Re: [PATCH v2] Allow ipv6 proxies and arp proxies be shown with iproute2
 Posted by [Thomas Graf](#) on Fri, 27 Jan 2012 10:35:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Fri, Jan 27, 2012 at 12:28:58PM +0400, Tony Zelenoff wrote:

```

> Add ability to return neighbour proxies list to caller if
> it sent full ndmsg structure and has NTF_PROXY flag set.
>
> Before this patch (and before iproute2 patches):
> $ ip neigh add proxy 2001::1 dev eth0
> $ ip -6 neigh show
> $
>
> After it and with applied iproute2 patches:
> $ ip neigh add proxy 2001::1 dev eth0
> $ ip -6 neigh show
> 2001::1 dev eth0 proxy
> $
>
> Compatibility with old versions of iproute2 is not broken,
> kernel checks for incoming structure size and properly
> works if old structure is came.
>
> [v2]
> * changed comments style.
> * removed useless line with continue and curly bracket.
> * changed incoming message size check from equal to more or
> equal.
>

```

> CC: davem@davemloft.net
> CC: kuznet@ms2.inr.ac.ru
> CC: netdev@vger.kernel.org
> CC: xemul@parallels.com
> Signed-off-by: Tony Zelenoff <antonz@parallels.com>

Acked-by: Thomas Graf <tgraf@suug.ch>

Subject: Re: [PATCH v2] Allow ipv6 proxies and arp proxies be shown with iproute2
Posted by [davem](#) on Mon, 30 Jan 2012 18:08:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Thomas Graf <tgraf@infradead.org>

Date: Fri, 27 Jan 2012 05:35:21 -0500

> On Fri, Jan 27, 2012 at 12:28:58PM +0400, Tony Zelenoff wrote:

>> Add ability to return neighbour proxies list to caller if
>> it sent full ndmsg structure and has NTF_PROXY flag set.

>>

>> Before this patch (and before iproute2 patches):

>> \$ ip neigh add proxy 2001::1 dev eth0

>> \$ ip -6 neigh show

>> \$

>>

>> After it and with applied iproute2 patches:

>> \$ ip neigh add proxy 2001::1 dev eth0

>> \$ ip -6 neigh show

>> 2001::1 dev eth0 proxy

>> \$

>>

>> Compatibility with old versions of iproute2 is not broken,

>> kernel checks for incoming structure size and properly

>> works if old structure is came.

>>

>> [v2]

>> * changed comments style.

>> * removed useless line with continue and curly bracket.

>> * changed incoming message size check from equal to more or
>> equal.

>>

>> CC: davem@davemloft.net

>> CC: kuznet@ms2.inr.ac.ru

>> CC: netdev@vger.kernel.org

>> CC: xemul@parallels.com

>> Signed-off-by: Tony Zelenoff <antonz@parallels.com>

>

> Acked-by: Thomas Graf <tgraf@suug.ch>

Applied, thanks.
