

---

Subject: Re: [PATCH 01/10] memcg: Kernel memory accounting infrastructure.

Posted by [Glauber Costa](#) on Tue, 28 Feb 2012 13:11:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On 02/27/2012 07:58 PM, Suleiman Souhlal wrote:

> Enabled with CONFIG\_CGROUP\_MEM\_RES\_CTLR\_KMEM.

>

> Adds the following files:

> - memory.kmem.independent\_kmem\_limit  
> - memory.kmem.usage\_in\_bytes  
> - memory.kmem.limit\_in\_bytes

>

> Signed-off-by: Suleiman Souhlal<suleiman@google.com>

> ---

> mm/memcontrol.c | 121

+++++

> 1 files changed, 120 insertions(+), 1 deletions(-)

>

> diff --git a/mm/memcontrol.c b/mm/memcontrol.c

> index 228d646..11e31d6 100644

> --- a/mm/memcontrol.c

> +++ b/mm/memcontrol.c

> @@ -235,6 +235,10 @@ struct mem\_cgroup {

> \*/

> struct res\_counter memsw;

> /\*

> + \* the counter to account for kernel memory usage.

> + \*/

> + struct res\_counter kmem\_bytes;

> + \*/

Not terribly important, but I find this name inconsistent. I like just kmem better.

> \* Per cgroup active and inactive list, similar to the

> \* per zone LRU lists.

> \*/

> @@ -293,6 +297,7 @@ struct mem\_cgroup {

> #ifdef CONFIG\_INET

> struct tcp\_memcontrol tcp\_mem;

> #endif

> + int independent\_kmem\_limit;

> };

bool ?

But that said, we are now approaching some 4 or 5 selectables in the memcg structure. How about we turn them into flags?

> /\* Stuffs for move charges at task migration. \*/

```

> @@ -354,6 +359,7 @@ enum charge_type {
>     #define _MEM    (0)
>     #define _MEMSWAP (1)
>     #define _OOM_TYPE (2)
>     +#define _KMEM   (3)
>     #define MEMFILE_PRIVATE(x, val) (((x)<< 16) | (val))
>     #define MEMFILE_TYPE(val) (((val)>> 16)& 0xffff)
>     #define MEMFILE_ATTR(val) ((val)& 0xffff)
> @@ -370,6 +376,8 @@ enum charge_type {
>
>     static void mem_cgroup_get(struct mem_cgroup *memcg);
>     static void mem_cgroup_put(struct mem_cgroup *memcg);
>     +static void memcg_kmem_init(struct mem_cgroup *memcg,
>     +    struct mem_cgroup *parent);
>
>     /* Writing them here to avoid exposing memcg's inner layout */
>     #ifdef CONFIG_CGROUP_MEM_RES_CTLR_KMEM
> @@ -1402,6 +1410,10 @@ done:
>         res_counter_read_u64(&memcg->memsw, RES_USAGE)>> 10,
>         res_counter_read_u64(&memcg->memsw, RES_LIMIT)>> 10,
>         res_counter_read_u64(&memcg->memsw, RES_FAILCNT));
>     + printk(KERN_INFO "kmem: usage %llu kB, limit %llu kB, failcnt %llu\n",
>     + res_counter_read_u64(&memcg->kmem_bytes, RES_USAGE)>> 10,
>     + res_counter_read_u64(&memcg->kmem_bytes, RES_LIMIT)>> 10,
>     + res_counter_read_u64(&memcg->kmem_bytes, RES_FAILCNT));
>     }
>
>     /*
> @@ -3840,6 +3852,9 @@ static u64 mem_cgroup_read(struct cgroup *cont, struct cftype *cft)
>     else
>         val = res_counter_read_u64(&memcg->memsw, name);
>         break;
>     + case _KMEM:
>     + val = res_counter_read_u64(&memcg->kmem_bytes, name);
>     + break;
>     default:
>         BUG();
>         break;
> @@ -3872,8 +3887,14 @@ static int mem_cgroup_write(struct cgroup *cont, struct cftype *cft,
>         break;
>         if (type == _MEM)
>             ret = mem_cgroup_resize_limit(memcg, val);
>     - else
>     + else if (type == _MEMSWAP)
>     + ret = mem_cgroup_resize_memsw_limit(memcg, val);
>     + else if (type == _KMEM) {
>     + if (!memcg->independent_kmem_limit)
>     + return -EINVAL;

```

```

> + ret = res_counter_set_limit(&memcg->kmem_bytes, val);
> + } else
> + return -EINVAL;
> break;
> case RES_SOFT_LIMIT:
> ret = res_counter_memparse_write_strategy(buffer,&val);
> @@ -4572,8 +4593,47 @@ static int mem_control_numa_stat_open(struct inode *unused,
struct file *file)
> #endif /* CONFIG_NUMA */
>
> #ifdef CONFIG_CGROUP_MEM_RES_CTLR_KMEM
> +static u64
> +mem_cgroup_independent_kmem_limit_read(struct cgroup *cgrp, struct cftype *cft)
> +{
> + return mem_cgroup_from_cont(cgrp)->independent_kmem_limit;
> +}
> +
> +static int mem_cgroup_independent_kmem_limit_write(struct cgroup *cgrp,
> + struct cftype *cft, u64 val)
> +{
> + mem_cgroup_from_cont(cgrp)->independent_kmem_limit = !!val;
> +
> + return 0;
> +}
> +
> +static struct cftype kmem_cgroup_files[] = {
> + {
> + .name = "kmem.independent_kmem_limit",
> + .write_u64 = mem_cgroup_independent_kmem_limit_write,
> + .read_u64 = mem_cgroup_independent_kmem_limit_read,
> + },
> + {
> + .name = "kmem.limit_in_bytes",
> + .private = MEMFILE_PRIVATE(_KMEM, RES_LIMIT),
> + .write_string = mem_cgroup_write,
> + .read_u64 = mem_cgroup_read,
> + },
> + {
> + .name = "kmem.usage_in_bytes",
> + .private = MEMFILE_PRIVATE(_KMEM, RES_USAGE),
> + .read_u64 = mem_cgroup_read,
> + },
> +};
> +
> static int register_kmem_files(struct cgroup *cont, struct cgroup_subsys *ss)
> {
> + int ret;
> +

```

```
> + ret = cgroup_add_files(cont, ss, kmem_cgroup_files,
> + ARRAY_SIZE(kmem_cgroup_files));
> + if (ret)
> + return ret;
> /*
>   * Part of this would be better living in a separate allocation
>   * function, leaving us with just the cgroup tree population work.
> @@ -4587,6 +4647,10 @@ static int register_kmem_files(struct cgroup *cont, struct
cgroup_subsys *ss)
> static void kmem_cgroup_destroy(struct cgroup_subsys *ss,
>       struct cgroup *cont)
> {
> + struct mem_cgroup *memcg;
> +
> + memcg = mem_cgroup_from_cont(cont);
> + BUG_ON(res_counter_read_u64(&memcg->kmem_bytes, RES_USAGE) != 0);
```

---