
Subject: smtp port

Posted by [youp](#) on Tue, 05 Sep 2006 19:26:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

my vps's don't contact all distant port smtp (25) :

```
-bash-3.00# telnet 69.64.46.7 25
Trying 69.64.46.7...
```

-> other adress does not work ...

```
-bash-3.00# telnet 69.64.46.7 80
Trying 69.64.46.7...
Connected to 69.64.46.7.
Escape character is '^]'.
-bash-3.00# telnet 69.64.46.7 443
Trying 69.64.46.7...
Connected to 69.64.46.7.
Escape character is '^]'.

```

-> other port work perfect , iptable is not loaded , and on harware node the command work fine
???

how to check if is it a misconfiguration ?

BR

Subject: Re: smtp port

Posted by [Vasily Tarasov](#) on Wed, 06 Sep 2006 07:18:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

Are the versions of telnet in VE and on HN the same?

Can you post here straces of telnet to 25th port from VE and from HN, please.

Thanks!

vass.

Subject: Re: smtp port

Posted by [youp](#) on Wed, 06 Sep 2006 07:38:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

on vps :

```
strace -f -e trace=file telnet 69.64.46.7 25
execve("/usr/bin/telnet", ["telnet", "69.64.46.7", "25"], [/* 17 vars */]) = 0
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
open("/lib/libutil.so.1", O_RDONLY) = 3
open("/usr/lib/libncurses.so.5", O_RDONLY) = 3
open("/lib/libc.so.6", O_RDONLY) = 3
open("/lib/libdl.so.2", O_RDONLY) = 3
Trying 69.64.46.7...
-bash-3.00# strace -f -e trace=file telnet 69.64.46.7 80
execve("/usr/bin/telnet", ["telnet", "69.64.46.7", "80"], [/* 17 vars */]) = 0
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
open("/lib/libutil.so.1", O_RDONLY) = 3
open("/usr/lib/libncurses.so.5", O_RDONLY) = 3
open("/lib/libc.so.6", O_RDONLY) = 3
open("/lib/libdl.so.2", O_RDONLY) = 3
Trying 69.64.46.7...
open("../.telnetrc", O_RDONLY) = -1 ENOENT (No such file or directory)
Connected to 69.64.46.7.
Escape character is '^]'.
^]
telnet> quit
```

ON HW :

```
strace -f -e trace=file telnet 69.64.46.7 25
execve("/usr/bin/telnet", ["telnet", "69.64.46.7", "25"], [/* 29 vars */]) = 0
open("/etc/ld.so.preload", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
open("/lib/libutil.so.1", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0755, st_size=14100, ...}) = 0
open("/usr/lib/libncurses.so.5", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0755, st_size=2743560, ...}) = 0
open("/lib/tls/libc.so.6", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0755, st_size=1579688, ...}) = 0
open("/usr/lib/libgpm.so.1", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0755, st_size=20624, ...}) = 0
open("/lib/tls/libm.so.6", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0755, st_size=213192, ...}) = 0
open("/etc/nsswitch.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=1695, ...}) = 0
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
```

```
open("/lib/libnss_files.so.2", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0755, st_size=51136, ...}) = 0
open("/etc/resolv.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=110, ...}) = 0
open("/etc/host.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=17, ...}) = 0
open("/etc/hosts", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=186, ...}) = 0
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
open("/lib/libnss_dns.so.2", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0755, st_size=18244, ...}) = 0
open("/lib/libresolv.so.2", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0755, st_size=73932, ...}) = 0
fstat64(1, {st_mode=S_IFCHR|0620, st_rdev=makedev(3, 1), ...}) = 0
Trying 69.64.46.7...
open("/root/.telnetrc", O_RDONLY) = -1 ENOENT (No such file or directory)
Connected to 69.64.46.7.
Escape character is '^]'.
220 vzorg.swsoft.net ESMTP Sendmail 8.13.1/8.13.1; Wed, 6 Sep 2006 03:36:45 -0400
```

i don't know if telnet are the same ...

Subject: Re: smtp port
Posted by [Vasily Tarasov](#) on Wed, 06 Sep 2006 07:53:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

Please, don't run strace with "-e trace=file" option.
Do "strace -f command".

To check what versions are on your machine and in VE:
"rpm -qa | grep telnet"

If it is possible for you, you can give me an access to the node
and I'll see what's wrong.

Thanks!

Subject: Re: smtp port
Posted by [youp](#) on Wed, 06 Sep 2006 08:01:12 GMT
[View Forum Message](#) <> [Reply to Message](#)

ON HW Node -> rpm -qa | grep telnet
telnet-0.17-26.2.1.legacy

telnet-server-0.17-26.2.1.legacy

ON VPS rpm -qa | grep telnet
telnet-0.17-28.FC2.1

strace on vps :

```
trace -f telnet 69.64.46.7 25
execve("/usr/bin/telnet", ["telnet", "69.64.46.7", "25"], [/* 17 vars */]execve("/usr/bin/telnet",
["telnet", "69.64.46.7", "25"], [/* 17 vars */]) = 0
) = 0
brk(0) = 0x80023000
uname({sys="Linux", node="virt103.allit.be", ...}) = 0
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=29474, ...}) = 0
old_mmap(NULL, 29474, PROT_READ, MAP_PRIVATE, 3, 0) = 0x4001c000
close(3) = 0
open("/lib/libutil.so.1", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\260\0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=13380, ...}) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1,
0) = 0x40024000
old_mmap(NULL, 12432, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0)
= 0x40025000
old_mmap(0x40027000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1000) = 0x40027000
close(3) = 0
open("/usr/lib/libncurses.so.5", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\200\343"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1030984, ...}) = 0
old_mmap(NULL, 288684, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3,
0) = 0x40029000
old_mmap(0x40067000, 32768, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3e000) = 0x40067000
old_mmap(0x4006f000, 1964, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x4006f000
close(3) = 0
open("/lib/libc.so.6", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\252N\1"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1478672, ...}) = 0
old_mmap(NULL, 1215452, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3,
0) = 0x40070000
old_mmap(0x40193000, 16384, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x122000) = 0x40193000
uname({sys="Linux", node="nsbk.allit.be", ...}) = 0
old_mmap(0x40197000, 7132, PROT_READ|PROT_WRITE,
```

```

MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x40197000
close(3) = 0
open("/lib/libdl.so.2", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\0\0\0\000"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=14504, ...}) = 0
old_mmap(NULL, 12408, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0)
= 0x40199000
old_mmap(0x4019b000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1000) = 0x4019b000
close(3) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1,
0) = 0x4019d000
set_thread_area({entry_number:-1 -> 6, base_addr:0x4019d8e0, limit:1048575, seg_32bit:1,
contents:0, read_exec_only:0, limit_in_pages:1, seg_not_present:0, useable:1}) = 0
mprotect(0x4019b000, 4096, PROT_READ) = 0
mprotect(0x40193000, 8192, PROT_READ) = 0
mprotect(0x40027000, 4096, PROT_READ) = 0
mprotect(0x4001a000, 4096, PROT_READ) = 0
munmap(0x4001c000, 29474) = 0
brk(0) = 0x80023000
brk(0x80044000) = 0x80044000
ioctl(0, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
rt_sigprocmask(SIG_BLOCK, NULL, [], 0) = 0
fstat64(1, brk(0)) = 0x80021000
{st_mode=S_IFCHR|0600, st_rdev=makedev(136, 0), ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x4001c000
write(1, "Trying 69.64.46.7...\r\n", 22Trying 69.64.46.7...
) = 22
socket(PF_INET, SOCK_STREAM, IPPROTO_TCP) = 3
setsockopt(3, SOL_IP, IP_TOS, [16], 4) = 0
connect(3, {sa_family=AF_INET, sin_port=htons(25), sin_addr=inet_addr("69.64.46.7")},
16open("/etc/ld.so.preload", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=24409, ...}) = 0
old_mmap(NULL, 24409, PROT_READ, MAP_PRIVATE, 3, 0) = 0x40013000
close(3) = 0
open("/lib/libutil.so.1", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\0\0\0\000"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=13948, ...}) = 0
old_mmap(NULL, 12432, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x40019000
old_mmap(0x4001b000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x1000) = 0x4001b000
close(3) = 0
open("/usr/lib/libncurses.so.5", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\0\0\0\000\341"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=2746679, ...}) = 0
old_mmap(NULL, 261420, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x4001d000

```

```
old_mmap(0x40054000, 36864, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x36000) = 0x40054000
close(3) = 0
open("/lib/libc.so.6", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\360O\1"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1345512, ...})
```

STRACE on HW

```
strace -f telnet 69.64.46.7 25
execve("/usr/bin/telnet", ["telnet", "69.64.46.7", "25"], [/* 29 vars */]) = 0
uname({sys="Linux", node="nsfr.allit.be", ...}) = 0
brk(0) = 0x8067000
open("/etc/ld.so.preload", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
old_mmap(NULL, 27378, PROT_READ, MAP_PRIVATE, 3, 0) = 0x40000000
close(3) = 0
open("/lib/libutil.so.1", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0@\^347G"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=14100, ...}) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1,
0) = 0x40007000
old_mmap(0x47e75000, 10996, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) =
0x47e75000
old_mmap(0x47e77000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x1000) = 0x47e77000
close(3) = 0
open("/usr/lib/libncurses.so.5", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\200\243"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=2743560, ...}) = 0
old_mmap(0x47eec000, 260172, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) =
0x47eec000
old_mmap(0x47f23000, 32768, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x37000) = 0x47f23000
old_mmap(0x47f2b000, 2124, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x47f2b000
close(3) = 0
open("/lib/tls/libc.so.6", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0`\210\317"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1579688, ...}) = 0
old_mmap(0x47ce3000, 1279340, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) =
0x47ce3000
old_mmap(0x47e16000, 12288, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x133000) = 0x47e16000
old_mmap(0x47e19000, 9580, PROT_READ|PROT_WRITE,
```

```

MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x47e19000
close(3) = 0
open("/usr/lib/libgpm.so.1", O_RDONLY) = 3
read(3, "\177ELF1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0 \372\362"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=20624, ...}) = 0
old_mmap(0x47f2e000, 23192, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x47f2e000
old_mmap(0x47f33000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3, 0x4000) = 0x47f33000
close(3) = 0
open("/lib/tls/libm.so.6", O_RDONLY) = 3
read(3, "\177ELF1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\0\25\342"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=213192, ...}) = 0
old_mmap(0x47e1e000, 138000, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x47e1e000
old_mmap(0x47e3f000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3, 0x20000) = 0x47e3f000
close(3) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x40008000
set_thread_area({entry_number:-1 -> 6, base_addr:0x40008360, limit:1048575, seg_32bit:1, contents:0, read_exec_only:0, limit_in_pages:1, seg_not_present:0, useable:1}) = 0
munmap(0x40000000, 27378) = 0
brk(0) = 0x8067000
brk(0x8088000) = 0x8088000
brk(0) = 0x8088000
ioctl(0, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
rt_sigprocmask(SIG_BLOCK, NULL, [], 0) = 0
socket(PF_FILE, SOCK_STREAM, 0) = 3
connect(3, {sa_family=AF_FILE, path="/var/run/.nscd_socket"}, 110) = -1 ENOENT (No such file or directory)
close(3) = 0
open("/etc/nsswitch.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=1695, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x40000000
read(3, "#\n# /etc/nsswitch.conf\n#\n# An ex"..., 4096) = 1695
read(3, "", 4096) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
old_mmap(NULL, 27378, PROT_READ, MAP_PRIVATE, 3, 0) = 0x40000000
close(3) = 0
open("/lib/libnss_files.so.2", O_RDONLY) = 3
read(3, "\177ELF1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\0\000\35\0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=51136, ...}) = 0
old_mmap(NULL, 41904, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x40009000
old_mmap(0x40013000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,

```

```

0xa000) = 0x40013000
close(3) = 0
munmap(0x40000000, 27378) = 0
gettimeofday({1157529596, 841996}, NULL) = 0
getpid() = 8793
open("/etc/resolv.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=110, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(3, "nameserver 213.186.45.190\nname", 4096) = 110
read(3, "", 4096) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
uname({sys="Linux", node="nsfr.allit.be", ...}) = 0
open("/etc/host.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=17, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(3, "order hosts,bind\n", 4096) = 17
read(3, "", 4096) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
open("/etc/hosts", O_RDONLY) = 3
fcntl64(3, F_GETFD) = 0
fcntl64(3, F_SETFD, FD_CLOEXEC) = 0
fstat64(3, {st_mode=S_IFREG|0644, st_size=186, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(3, "# Do not remove the following li", 4096) = 186
read(3, "", 4096) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
old_mmap(NULL, 27378, PROT_READ, MAP_PRIVATE, 3, 0) = 0x40000000
close(3) = 0
open("/lib/libnss_dns.so.2", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\260\16"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=18244, ...}) = 0
old_mmap(NULL, 12700, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x40014000
old_mmap(0x40017000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x3000) = 0x40017000
close(3) = 0
open("/lib/libresolv.so.2", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\260xpC"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=73932, ...}) = 0
old_mmap(0x43705000, 73640, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) =
0x43705000

```



```

old_mmap(0x43714000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0xe000) = 0x43714000
old_mmap(0x43715000, 8104, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x43715000
close(3) = 0
munmap(0x40000000, 27378) = 0
socket(PF_INET, SOCK_DGRAM, IPPROTO_IP) = 3
connect(3, {sa_family=AF_INET, sin_port=htons(53), sin_addr=inet_addr("213.186.45.190")}, 28)
= 0
send(3, "\204\252\1\0\0\1\0\0\0\0\0\0\0017\00246\00264\00269\7i"..., 41, 0) = 41
gettimeofday({1157529596, 856161}, NULL) = 0
poll([{fd=3, events=POLLIN, revents=POLLERR}], 1, 5000) = 1
ioctl(3, FIONREAD, [0]) = 0
recvfrom(3, 0xbfffe140, 1024, 0, 0xbfffd04, 0xbffdec4) = -1 ECONNREFUSED (Connection
refused)
close(3) = 0
socket(PF_INET, SOCK_DGRAM, IPPROTO_IP) = 3
connect(3, {sa_family=AF_INET, sin_port=htons(53), sin_addr=inet_addr("193.221.123.11")}, 28)
= 0
send(3, "\204\252\1\0\0\1\0\0\0\0\0\0\0017\00246\00264\00269\7i"..., 41, 0) = 41
gettimeofday({1157529596, 858437}, NULL) = 0
poll([{fd=3, events=POLLIN, revents=POLLIN}], 1, 3000) = 1
ioctl(3, FIONREAD, [129]) = 0
recvfrom(3, "\204\252\201\200\0\1\0\1\0\3\0\0\0017\00246\00264\0026"..., 1024, 0,
{sa_family=AF_INET, sin_port=htons(53), sin_addr=inet_addr("193.221.123.11")}, [16]) = 129
close(3) = 0
fstat64(1, {st_mode=S_IFCHR|0620, st_rdev=makedev(3, 1), ...}) = 0
ioctl(1, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
write(1, "Trying 69.64.46.7...\r\n", 22Trying 69.64.46.7...
) = 22
socket(PF_INET, SOCK_STREAM, IPPROTO_TCP) = 3
setsockopt(3, SOL_IP, IP_TOS, [16], 4) = 0
connect(3, {sa_family=AF_INET, sin_port=htons(25), sin_addr=inet_addr("69.64.46.7")}, 16) = 0
open("/root/.telnetrc", O_RDONLY) = -1 ENOENT (No such file or directory)
write(1, "Connected to 69.64.46.7.\r\n", 26Connected to 69.64.46.7.
) = 26
write(1, "Escape character is '^]'\r\n", 27Escape character is '^]'.
) = 27
rt_sigprocmask(SIG_BLOCK, NULL, [], 0) = 0
rt_sigaction(SIGINT, {0x804e1f0, [INT], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, 0) = 0
rt_sigaction(SIGQUIT, {0x804e230, [QUIT], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, 0) = 0
rt_sigaction(SIGPIPE, {0x804e1d0, [PIPE], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, 0) = 0
rt_sigaction(SIGWINCH, {0x804e2a0, [WINCH], SA_RESTORER|SA_RESTART, 0x47d0aa58},

```

```
{SIG_DFL}, = 0
rt_sigaction(SIGTSTP, {0x804e260, [TSTP], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, = 0
rt_sigaction(SIGTSTP, {0x804e260, [TSTP], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{0x804e260, [TSTP], SA_RESTORER|SA_RESTART, 0x47d0aa58}, = 0
ioctl(0, SNDCTL_TMR_STOP or TCSETSW, {B38400 opost isig icanon echo ...}) = 0
ioctl(0, FIONBIO, [1]) = 0
ioctl(1, FIONBIO, [1]) = 0
ioctl(3, FIONBIO, [1]) = 0
setsockopt(3, SOL_SOCKET, SO_OOBINLINE, [1], 4) = 0
select(4, [0 3], [], [3], {0, 0}) = 0 (Timeout)
select(4, [0 3], [], [3], NULL) = 1 (in [3])
recv(3, "220 vzorg.swsoft.net ESMTP Sendm"..., 8192, 0) = 83
select(4, [0 3], [1], [3], {0, 0}) = 1 (out [1], left {0, 0})
write(1, "220 vzorg.swsoft.net ESMTP Sendm"..., 82220 vzorg.swsoft.net ESMTP Sendmail
8.13.1/8.13.1; Wed, 6 Sep 2006 04:00:01 -0400
) = 82
select(4, [0 3], [], [3], NULL
```

Subject: Re: smtp port
Posted by [Vasily Tarasov](#) on Wed, 06 Sep 2006 08:40:53 GMT
[View Forum Message](#) <> [Reply to Message](#)

Sorry,
are you sure that strace from VE is complete?
You mentioned that telnet outputs "other adress does not work",
But in strace I can't find where it does it.
Moreover strace is ended by fstat64(), this is rather strange...

Thanks.

Subject: Re: smtp port
Posted by [youp](#) on Wed, 06 Sep 2006 09:11:05 GMT
[View Forum Message](#) <> [Reply to Message](#)

yes i think :

another one ->

ON VPS

=====

strace -f telnet 69.64.46.7 25

```
execve("/usr/bin/telnet", ["telnet", "69.64.46.7", "25"], [/* 17 vars */]) = 0
brk(0) = 0x80023000
uname({sys="Linux", node="virt103.allit.be", ...}) = 0
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=29474, ...}) = 0
old_mmap(NULL, 29474, PROT_READ, MAP_PRIVATE, 3, 0) = 0x4001c000
close(3) = 0
open("/lib/libutil.so.1", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\260\xf0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=13380, ...}) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x40024000
old_mmap(NULL, 12432, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x40025000
old_mmap(0x40027000, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1000) = 0x40027000
close(3) = 0
open("/usr/lib/libncurses.so.5", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\200\343"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1030984, ...}) = 0
old_mmap(NULL, 288684, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x40029000
old_mmap(0x40067000, 32768, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x3e000) = 0x40067000
old_mmap(0x4006f000, 1964, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x4006f000
close(3) = 0
open("/lib/libc.so.6", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\252N\1"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1478672, ...}) = 0
old_mmap(NULL, 1215452, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x40070000
old_mmap(0x40193000, 16384, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x122000) = 0x40193000
old_mmap(0x40197000, 7132, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x40197000
close(3) = 0
open("/lib/libdl.so.2", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\0\xf0\000"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=14504, ...}) = 0
old_mmap(NULL, 12408, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) = 0x40199000
old_mmap(0x4019b000, 8192, PROT_READ|PROT_WRITE,
```

```

MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x1000) = 0x4019b000
close(3) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x4019d000
set_thread_area({entry_number:-1 -> 6, base_addr:0x4019d8e0, limit:1048575, seg_32bit:1, contents:0, read_exec_only:0, limit_in_pages:1, seg_not_present:0, useable:1}) = 0
mprotect(0x4019b000, 4096, PROT_READ) = 0
mprotect(0x40193000, 8192, PROT_READ) = 0
mprotect(0x40027000, 4096, PROT_READ) = 0
mprotect(0x4001a000, 4096, PROT_READ) = 0
munmap(0x4001c000, 29474) = 0
brk(0) = 0x80023000
brk(0x80044000) = 0x80044000
ioctl(0, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
rt_sigprocmask(SIG_BLOCK, NULL, [], 0) = 0
fstat64(1, {st_mode=S_IFCHR|0600, st_rdev=makedev(136, 0), ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x4001c000
write(1, "Trying 69.64.46.7...\r\n", 22Trying 69.64.46.7...
) = 22
socket(PF_INET, SOCK_STREAM, IPPROTO_TCP) = 3
setsockopt(3, SOL_IP, IP_TOS, [16], 4) = 0
connect(3, {sa_family=AF_INET, sin_port=htons(25), sin_addr=inet_addr("69.64.46.7")}, 16

```

-> here the process wait

ON HW

=====

```
strace -f telnet 69.64.46.7 25
```

```

execve("/usr/bin/telnet", ["telnet", "69.64.46.7", "25"], [/* 29 vars */]) = 0
uname({sys="Linux", node="nsfr.allit.be", ...}) = 0
brk(0) = 0x8067000
open("/etc/ld.so.preload", O_RDONLY) = -1 ENOENT (No such file or directory)
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
old_mmap(NULL, 27378, PROT_READ, MAP_PRIVATE, 3, 0) = 0x40000000
close(3) = 0
open("/lib/libutil.so.1", O_RDONLY) = 3
read(3, "\177ELF1\1\1\0\0\0\0\0\0\0\0\0\0\03\0\3\0\1\0\0\0@\^347G"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=14100, ...}) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) = 0x40007000
old_mmap(0x47e75000, 10996, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x47e75000

```

```

old_mmap(0x47e77000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x1000) = 0x47e77000
close(3) = 0
open("/usr/lib/libncurses.so.5", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\200\243"... , 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=2743560, ...}) = 0
old_mmap(0x47eec000, 260172, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) =
0x47eec000
old_mmap(0x47f23000, 32768, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x37000) = 0x47f23000
old_mmap(0x47f2b000, 2124, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x47f2b000
close(3) = 0
open("/lib/tls/libc.so.6", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\210\317"... , 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=1579688, ...}) = 0
old_mmap(0x47ce3000, 1279340, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) =
0x47ce3000
old_mmap(0x47e16000, 12288, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x133000) = 0x47e16000
old_mmap(0x47e19000, 9580, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x47e19000
close(3) = 0
open("/usr/lib/libgpm.so.1", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\372\362"... , 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=20624, ...}) = 0
old_mmap(0x47f2e000, 23192, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x47f2e000
old_mmap(0x47f33000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x4000) = 0x47f33000
close(3) = 0
open("/lib/tls/libm.so.6", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\25\342"... , 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=213192, ...}) = 0
old_mmap(0x47e1e000, 138000, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) =
0x47e1e000
old_mmap(0x47e3f000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0x20000) = 0x47e3f000
close(3) = 0
old_mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1,
0) = 0x40008000
set_thread_area({entry_number:-1 -> 6, base_addr:0x40008360, limit:1048575, seg_32bit:1,
contents:0, read_exec_only:0, limit_in_pages:1, seg_not_present:0, useable:1}) = 0
munmap(0x40000000, 27378) = 0
brk(0) = 0x8067000
brk(0x8088000) = 0x8088000
brk(0) = 0x8088000
ioctl(0, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
rt_sigprocmask(SIG_BLOCK, NULL, [], = 0

```

```

socket(PF_FILE, SOCK_STREAM, 0) = 3
connect(3, {sa_family=AF_FILE, path="/var/run/.nscd_socket"}, 110) = -1 ENOENT (No such file
or directory)
close(3) = 0
open("/etc/nsswitch.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=1695, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(3, "#\n# /etc/nsswitch.conf\n#\n# An ex"..., 4096) = 1695
read(3, "", 4096) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
old_mmap(NULL, 27378, PROT_READ, MAP_PRIVATE, 3, 0) = 0x40000000
close(3) = 0
open("/lib/libnss_files.so.2", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0000\35\0"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=51136, ...}) = 0
old_mmap(NULL, 41904, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x40009000
old_mmap(0x40013000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3,
0xa000) = 0x40013000
close(3) = 0
munmap(0x40000000, 27378) = 0
gettimeofday({1157533790, 396941}, NULL) = 0
getpid() = 16968
open("/etc/resolv.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=110, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(3, "nameserver 213.186.45.190\nname"..., 4096) = 110
read(3, "", 4096) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
uname({sys="Linux", node="nsfr.allit.be", ...}) = 0
open("/etc/host.conf", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=17, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
read(3, "order hosts,bind\n", 4096) = 17
read(3, "", 4096) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
open("/etc/hosts", O_RDONLY) = 3
fcntl64(3, F_GETFD) = 0
fcntl64(3, F_SETFD, FD_CLOEXEC) = 0
fstat64(3, {st_mode=S_IFREG|0644, st_size=186, ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =

```

```

0x40000000
read(3, "# Do not remove the following li"..., 4096) = 186
read(3, "", 4096) = 0
close(3) = 0
munmap(0x40000000, 4096) = 0
open("/etc/ld.so.cache", O_RDONLY) = 3
fstat64(3, {st_mode=S_IFREG|0644, st_size=27378, ...}) = 0
old_mmap(NULL, 27378, PROT_READ, MAP_PRIVATE, 3, 0) = 0x40000000
close(3) = 0
open("/lib/libnss_dns.so.2", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\260\16"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=18244, ...}) = 0
old_mmap(NULL, 12700, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x40014000
old_mmap(0x40017000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3, 0x3000) = 0x40017000
close(3) = 0
open("/lib/libresolv.so.2", O_RDONLY) = 3
read(3, "\177ELF\1\1\1\0\0\0\0\0\0\0\0\3\0\3\0\1\0\0\0\260xpC"..., 512) = 512
fstat64(3, {st_mode=S_IFREG|0755, st_size=73932, ...}) = 0
old_mmap(0x43705000, 73640, PROT_READ|PROT_EXEC, MAP_PRIVATE, 3, 0) = 0x43705000
old_mmap(0x43714000, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED, 3, 0xe000) = 0x43714000
old_mmap(0x43715000, 8104, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x43715000
close(3) = 0
munmap(0x40000000, 27378) = 0
socket(PF_INET, SOCK_DGRAM, IPPROTO_IP) = 3
connect(3, {sa_family=AF_INET, sin_port=htons(53), sin_addr=inet_addr("213.186.45.190")}, 28) = 0
send(3, "\334\234\1\0\0\1\0\0\0\0\0\0\0\0017\00246\00264\00269\7i"..., 41, 0) = 41
gettimeofday({1157533790, 411863}, NULL) = 0
poll([{fd=3, events=POLLIN, revents=POLLERR}], 1, 5000) = 1
ioctl(3, FIONREAD, [0]) = 0
recvfrom(3, 0xbfffe140, 1024, 0, 0xbfffd04, 0xbffdec4) = -1 ECONNREFUSED (Connection refused)
close(3) = 0
socket(PF_INET, SOCK_DGRAM, IPPROTO_IP) = 3
connect(3, {sa_family=AF_INET, sin_port=htons(53), sin_addr=inet_addr("193.221.123.11")}, 28) = 0
send(3, "\334\234\1\0\0\1\0\0\0\0\0\0\0\0017\00246\00264\00269\7i"..., 41, 0) = 41
gettimeofday({1157533790, 414278}, NULL) = 0
poll([{fd=3, events=POLLIN, revents=POLLIN}], 1, 3000) = 1
ioctl(3, FIONREAD, [177]) = 0
recvfrom(3, "\334\234\201\200\0\1\0\1\0\3\0\3\0017\00246\00264\0026"..., 1024, 0, {sa_family=AF_INET, sin_port=htons(53), sin_addr=inet_addr("193.221.123.11")}, [16]) = 177
close(3) = 0
fstat64(1, {st_mode=S_IFCHR|0620, st_rdev=makedev(3, 1), ...}) = 0

```

```
ioctl(1, SNDCTL_TMR_TIMEBASE or TCGETS, {B38400 opost isig icanon echo ...}) = 0
mmap2(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0) =
0x40000000
write(1, "Trying 69.64.46.7...\r\n", 22Trying 69.64.46.7...
) = 22
socket(PF_INET, SOCK_STREAM, IPPROTO_TCP) = 3
setsockopt(3, SOL_IP, IP_TOS, [16], 4) = 0
connect(3, {sa_family=AF_INET, sin_port=htons(25), sin_addr=inet_addr("69.64.46.7")}, 16) = 0
open("/root/.telnetrc", O_RDONLY) = -1 ENOENT (No such file or directory)
write(1, "Connected to 69.64.46.7.\r\n", 26Connected to 69.64.46.7.
) = 26
write(1, "Escape character is '^]'\r\n", 27Escape character is '^].
) = 27
rt_sigprocmask(SIG_BLOCK, NULL, [], 0)
rt_sigaction(SIGINT, {0x804e1f0, [INT], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, 0)
rt_sigaction(SIGQUIT, {0x804e230, [QUIT], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, 0)
rt_sigaction(SIGPIPE, {0x804e1d0, [PIPE], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, 0)
rt_sigaction(SIGWINCH, {0x804e2a0, [WINCH], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, 0)
rt_sigaction(SIGTSTP, {0x804e260, [TSTP], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{SIG_DFL}, 0)
rt_sigaction(SIGTSTP, {0x804e260, [TSTP], SA_RESTORER|SA_RESTART, 0x47d0aa58},
{0x804e260, [TSTP], SA_RESTORER|SA_RESTART, 0x47d0aa58}, 0)
ioctl(0, SNDCTL_TMR_STOP or TCSETSW, {B38400 opost isig icanon echo ...}) = 0
ioctl(0, FIONBIO, [1]) = 0
ioctl(1, FIONBIO, [1]) = 0
ioctl(3, FIONBIO, [1]) = 0
setsockopt(3, SOL_SOCKET, SO_OOBINLINE, [1], 4) = 0
select(4, [0 3], [], [3], {0, 0}) = 0 (Timeout)
select(4, [0 3], [], [3], NULL) = 1 (in [3])
recv(3, "220 vzorg.swsoft.net ESMTP Sendm"..., 8192, 0) = 83
select(4, [0 3], [1], [3], {0, 0}) = 1 (out [1], left {0, 0})
write(1, "220 vzorg.swsoft.net ESMTP Sendm"..., 82220 vzorg.swsoft.net ESMTP Sendmail
8.13.1/8.13.1; Wed, 6 Sep 2006 05:09:55 -0400
) = 82
```

Subject: Re: smtp port
Posted by [youp](#) on Wed, 06 Sep 2006 09:14:03 GMT
[View Forum Message](#) <> [Reply to Message](#)

on the vps the telnet don't connect on distant port 25
