

---

Subject: [PATCH] nfsd: remove hard-coded dereferences to name-to-id and id-to-name caches

Posted by Stanislav Kinsbursky on Wed, 11 Apr 2012 11:18:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

These dereferences to global static caches are redundant. They also prevents converting these caches into per-net ones. So this patch is cleanup + precursor of patch set, which will make them per-net.

Signed-off-by: Stanislav Kinsbursky <[skinsbursky@parallels.com](mailto:skinsbursky@parallels.com)>

---

fs/nfsd/nfs4idmap.c | 50 ++++++-----

1 files changed, 24 insertions(+), 26 deletions(-)

```
diff --git a/fs/nfsd/nfs4idmap.c b/fs/nfsd/nfs4idmap.c
index 322d11c..2ff4470 100644
--- a/fs/nfsd/nfs4idmap.c
+++ b/fs/nfsd/nfs4idmap.c
@@ -183,8 +183,9 @@ warn_no_idmapd(struct cache_detail *detail, int has_died)

static int      idtoname_parse(struct cache_detail *, char *, int);
-static struct ent *idtoname_lookup(struct ent *);
-static struct ent *idtoname_update(struct ent *, struct ent *);
+static struct ent *idtoname_lookup(struct cache_detail *, struct ent *);
+static struct ent *idtoname_update(struct cache_detail *, struct ent *,
+        struct ent *);

static struct cache_detail idtoname_cache = {
    .owner = THIS_MODULE,
@@ -244,7 +245,7 @@ idtoname_parse(struct cache_detail *cd, char *buf, int buflen)
    goto out;

    error = -ENOMEM;
-    res = idtoname_lookup(&ent);
+    res = idtoname_lookup(cd, &ent);
    if (!res)
        goto out;

@@ -260,11 +261,11 @@ idtoname_parse(struct cache_detail *cd, char *buf, int buflen)
    else
        memcpy(ent.name, buf1, sizeof(ent.name));
    error = -ENOMEM;
-    res = idtoname_update(&ent, res);
+    res = idtoname_update(cd, &ent, res);
    if (res == NULL)
        goto out;
```

```

- cache_put(&res->h, &idtoname_cache);
+ cache_put(&res->h, cd);

    error = 0;
out:
@@ -275,10 +276,9 @@ out:

static struct ent *
-idtoname_lookup(struct ent *item)
+idtoname_lookup(struct cache_detail *cd, struct ent *item)
{
- struct cache_head *ch = sunrpc_cache_lookup(&idtoname_cache,
-     &item->h,
+ struct cache_head *ch = sunrpc_cache_lookup(cd, &item->h,
     idtoname_hash(item));
 if (ch)
     return container_of(ch, struct ent, h);
@@ -287,10 +287,9 @@ idtoname_lookup(struct ent *item)
}

static struct ent *
-idtoname_update(struct ent *new, struct ent *old)
+idtoname_update(struct cache_detail *cd, struct ent *new, struct ent *old)
{
- struct cache_head *ch = sunrpc_cache_update(&idtoname_cache,
-     &new->h, &old->h,
+ struct cache_head *ch = sunrpc_cache_update(cd, &new->h, &old->h,
     idtoname_hash(new));
 if (ch)
     return container_of(ch, struct ent, h);
@@ -359,8 +358,9 @@ nametoid_show(struct seq_file *m, struct cache_detail *cd, struct
cache_head *h)
    return 0;
}

-static struct ent *nametoid_lookup(struct ent *);
-static struct ent *nametoid_update(struct ent *, struct ent *);
+static struct ent *nametoid_lookup(struct cache_detail *, struct ent *);
+static struct ent *nametoid_update(struct cache_detail *, struct ent *,
+    struct ent *);
static int      nametoid_parse(struct cache_detail *, char *, int);

static struct cache_detail nametoid_cache = {
@@ -426,14 +426,14 @@ nametoid_parse(struct cache_detail *cd, char *buf, int buflen)
    set_bit(CACHE_NEGATIVE, &ent.h.flags);

```

```

error = -ENOMEM;
- res = nametoid_lookup(&ent);
+ res = nametoid_lookup(cd, &ent);
if (res == NULL)
    goto out;
- res = nametoid_update(&ent, res);
+ res = nametoid_update(cd, &ent, res);
if (res == NULL)
    goto out;

- cache_put(&res->h, &nemetoid_cache);
+ cache_put(&res->h, cd);
error = 0;
out:
    kfree(buf1);
@@ -443,10 +443,9 @@ out:

static struct ent *
-nametoid_lookup(struct ent *item)
+nametoid_lookup(struct cache_detail *cd, struct ent *item)
{
- struct cache_head *ch = sunrpc_cache_lookup(&nemetoid_cache,
-     &item->h,
+ struct cache_head *ch = sunrpc_cache_lookup(cd, &item->h,
     nemetoid_hash(item));
if (ch)
    return container_of(ch, struct ent, h);
@@ -455,10 +454,9 @@ nametoid_lookup(struct ent *item)
}

static struct ent *
-nametoid_update(struct ent *new, struct ent *old)
+nametoid_update(struct cache_detail *cd, struct ent *new, struct ent *old)
{
- struct cache_head *ch = sunrpc_cache_update(&nemetoid_cache,
-     &new->h, &old->h,
+ struct cache_head *ch = sunrpc_cache_update(cd, &new->h, &old->h,
     nemetoid_hash(new));
if (ch)
    return container_of(ch, struct ent, h);
@@ -493,12 +491,12 @@ nfsd_idmap_shutdown(void)

static int
idmap_lookup(struct svc_rqst *rqstp,
- struct ent *(*lookup_fn)(struct ent *), struct ent *key,
- struct cache_detail *detail, struct ent **item)
+ struct ent *(*lookup_fn)(struct cache_detail *, struct ent *),

```

```

+ struct ent *key, struct cache_detail *detail, struct ent **item)
{
    int ret;

- *item = lookup_fn(key);
+ *item = lookup_fn(detail, key);
if (!*item)
    return -ENOMEM;
retry:
@@ -506,7 +504,7 @@ idmap_lookup(struct svc_rqst *rqstp,
if (ret == -ETIMEDOUT) {
    struct ent *prev_item = *item;
- *item = lookup_fn(key);
+ *item = lookup_fn(detail, key);
if (*item != prev_item)
    goto retry;
cache_put(&(*item)->h, detail);

```

---



---

**Subject: Re: [PATCH] nfsd: remove hard-coded dereferences to name-to-id and id-to-name caches**

Posted by [bfields](#) on Wed, 11 Apr 2012 22:07:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Wed, Apr 11, 2012 at 03:18:58PM +0400, Stanislav Kinsbursky wrote:

> These dereferences to global static caches are redundant. They also prevents  
> converting these caches into per-net ones. So this patch is cleanup + precursor  
> of patch set, which will make them per-net.

This isn't applying to my latest tree; could you look into that and resend?

I've applied and pushed out your cleanup patches, but not yet the two cache-containerization patches.

--b.

```

>
> Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>
>
> ---
> fs/nfsd/nfs4idmap.c |  50 ++++++-----+
> 1 files changed, 24 insertions(+), 26 deletions(-)
>
> diff --git a/fs/nfsd/nfs4idmap.c b/fs/nfsd/nfs4idmap.c
> index 322d11c..2ff4470 100644
> --- a/fs/nfsd/nfs4idmap.c

```

```

> +++
> b/fs/nfsd/nfs4idmap.c
> @@ -183,8 +183,9 @@ warn_no_idmapd(struct cache_detail *detail, int has_died)
>
>
> static int      idtoname_parse(struct cache_detail *, char *, int);
> -static struct ent *idtoname_lookup(struct ent *);
> -static struct ent *idtoname_update(struct ent *, struct ent *);
> +static struct ent *idtoname_lookup(struct cache_detail *, struct ent *);
> +static struct ent *idtoname_update(struct cache_detail *, struct ent *,
> +      struct ent *);
>
> static struct cache_detail idtoname_cache = {
> .owner = THIS_MODULE,
> @@ -244,7 +245,7 @@ idtoname_parse(struct cache_detail *cd, char *buf, int buflen)
>     goto out;
>
>     error = -ENOMEM;
> - res = idtoname_lookup(&ent);
> + res = idtoname_lookup(cd, &ent);
>     if (!res)
>     goto out;
>
> @@ -260,11 +261,11 @@ idtoname_parse(struct cache_detail *cd, char *buf, int buflen)
> else
>     memcpy(ent.name, buf1, sizeof(ent.name));
>     error = -ENOMEM;
> - res = idtoname_update(&ent, res);
> + res = idtoname_update(cd, &ent, res);
>     if (res == NULL)
>     goto out;
>
> - cache_put(&res->h, &idtoname_cache);
> + cache_put(&res->h, cd);
>
>     error = 0;
> out:
> @@ -275,10 +276,9 @@ out:
>
>
> static struct ent *
> -idtoname_lookup(struct ent *item)
> +idtoname_lookup(struct cache_detail *cd, struct ent *item)
> {
> - struct cache_head *ch = sunrpc_cache_lookup(&idtoname_cache,
> -     &item->h,
> + struct cache_head *ch = sunrpc_cache_lookup(cd, &item->h,
>         idtoname_hash(item));
>     if (ch)

```

```

>   return container_of(ch, struct ent, h);
> @@ -287,10 +287,9 @@ idtoname_lookup(struct ent *item)
> }
>
> static struct ent *
> -idtoname_update(struct ent *new, struct ent *old)
> +idtoname_update(struct cache_detail *cd, struct ent *new, struct ent *old)
> {
> - struct cache_head *ch = sunrpc_cache_update(&idtoname_cache,
> -     &new->h, &old->h,
> + struct cache_head *ch = sunrpc_cache_update(cd, &new->h, &old->h,
>         idtoname_hash(new));
> if (ch)
>   return container_of(ch, struct ent, h);
> @@ -359,8 +358,9 @@ nametoid_show(struct seq_file *m, struct cache_detail *cd, struct
cache_head *h)
>   return 0;
> }
>
> -static struct ent *nametoid_lookup(struct ent *);
> -static struct ent *nametoid_update(struct ent *, struct ent *);
> +static struct ent *nametoid_lookup(struct cache_detail *, struct ent *);
> +static struct ent *nametoid_update(struct cache_detail *, struct ent *,
> +    struct ent *);
> static int      nametoid_parse(struct cache_detail *, char *, int);
>
> static struct cache_detail nametoid_cache = {
> @@ -426,14 +426,14 @@ nametoid_parse(struct cache_detail *cd, char *buf, int buflen)
>   set_bit(CACHE_NEGATIVE, &ent.h.flags);
>
> error = -ENOMEM;
> - res = nametoid_lookup(&ent);
> + res = nametoid_lookup(cd, &ent);
> if (res == NULL)
>   goto out;
> - res = nametoid_update(&ent, res);
> + res = nametoid_update(cd, &ent, res);
> if (res == NULL)
>   goto out;
>
> - cache_put(&res->h, &nemetoid_cache);
> + cache_put(&res->h, cd);
> error = 0;
> out:
> kfree(buf1);
> @@ -443,10 +443,9 @@ out:
>
>
```

```

> static struct ent *
> -nametoid_lookup(struct ent *item)
> +nametoid_lookup(struct cache_detail *cd, struct ent *item)
> {
> - struct cache_head *ch = sunrpc_cache_lookup(&nemetoid_cache,
> -     &item->h,
> + struct cache_head *ch = sunrpc_cache_lookup(cd, &item->h,
>     nemetoid_hash(item));
> if (ch)
>     return container_of(ch, struct ent, h);
> @@ -455,10 +454,9 @@ nemetoid_lookup(struct ent *item)
> }
>
> static struct ent *
> -nametoid_update(struct ent *new, struct ent *old)
> +nametoid_update(struct cache_detail *cd, struct ent *new, struct ent *old)
> {
> - struct cache_head *ch = sunrpc_cache_update(&nemetoid_cache,
> -     &new->h, &old->h,
> + struct cache_head *ch = sunrpc_cache_update(cd, &new->h, &old->h,
>     nemetoid_hash(new));
> if (ch)
>     return container_of(ch, struct ent, h);
> @@ -493,12 +491,12 @@ nfsd_idmap_shutdown(void)
>
> static int
> idmap_lookup(struct svc_rqst *rqstp,
> - struct ent *(*lookup_fn)(struct ent *), struct ent *key,
> - struct cache_detail *detail, struct ent **item)
> + struct ent *(*lookup_fn)(struct cache_detail *, struct ent *),
> + struct ent *key, struct cache_detail *detail, struct ent **item)
> {
>     int ret;
>
> - *item = lookup_fn(key);
> + *item = lookup_fn(detail, key);
>     if (!*item)
>         return -ENOMEM;
>     retry:
> @@ -506,7 +504,7 @@ idmap_lookup(struct svc_rqst *rqstp,
>
>     if (ret == -ETIMEDOUT) {
>         struct ent *prev_item = *item;
> -     *item = lookup_fn(key);
> +     *item = lookup_fn(detail, key);
>     if (*item != prev_item)
>         goto retry;
>     cache_put(&(*item)->h, detail);

```

>

---