
Subject: [PATCH] NFS: hard-code init_net for NFS callback transports
Posted by Stanislav Kinsbursky on Fri, 01 Jun 2012 09:55:47 GMT
[View Forum Message](#) <> [Reply to Message](#)

This patch set is a bug fix for Bruce's 3.5 branch.
I'll rebase this for 3.4 and resend.

In case of destroying mount namespace on child reaper exit, nsproxy is zeroed to the point already. So, dereferencing of it is invalid.

This patch hard-code "init_net" for all network namespace references for NFS callback services. This will be fixed with proper NFS callback containerization.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

fs/nfs/callback.c | 11 ++++++-----
1 files changed, 5 insertions(+), 6 deletions(-)

```
diff --git a/fs/nfs/callback.c b/fs/nfs/callback.c
index 970659d..23ff18f 100644
--- a/fs/nfs/callback.c
+++ b/fs/nfs/callback.c
@@ -17,7 +17,6 @@
#include <linux/kthread.h>
#include <linux/sunrpc/svcauth_gss.h>
#include <linux/sunrpc/bc_xprt.h>
-#include <linux/nsproxy.h>

#include <net/inet_sock.h>

@@ -107,7 +106,7 @@ nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
{
    int ret;

-    ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET,
+    ret = svc_create_xprt(serv, "tcp", &init_net, PF_INET,
        nfs_callback_set_tcpport, SVC SOCK ANONYMOUS);
    if (ret <= 0)
        goto out_err;
@@ -115,7 +114,7 @@ nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
    dprintk("NFS: Callback listener port = %u (af %u)\n",
        nfs_callback_tcpport, PF_INET);

-    ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET6,
+    ret = svc_create_xprt(serv, "tcp", &init_net, PF_INET6,
        nfs_callback_set_tcpport, SVC SOCK ANONYMOUS);
    if (ret > 0) {
        nfs_callback_tcpport6 = ret;
```

```

@@ -184,7 +183,7 @@ nfs41_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
 * fore channel connection.
 * Returns the input port (0) and sets the svc_serv bc_xprt on success
 */
- ret = svc_create_xprt(serv, "tcp-bc", xprt->xprt_net, PF_INET, 0,
+ ret = svc_create_xprt(serv, "tcp-bc", &init_net, PF_INET, 0,
    SVC SOCK_ANONYMOUS);
if (ret < 0) {
    rqstp = ERR_PTR(ret);
@@ -254,7 +253,7 @@ int nfs_callback_up(u32 minorversion, struct rpc_xprt *xprt)
char svc_name[12];
int ret = 0;
int minorversion_setup;
- struct net *net = current->nsproxy->net_ns;
+ struct net *net = &init_net;

mutex_lock(&nfs_callback_mutex);
if (cb_info->users++ || cb_info->task != NULL) {
@@ -330,7 +329,7 @@ void nfs_callback_down(int minorversion)
cb_info->users--;
if (cb_info->users == 0 && cb_info->task != NULL) {
    kthread_stop(cb_info->task);
- svc_shutdown_net(cb_info->serv, current->nsproxy->net_ns);
+ svc_shutdown_net(cb_info->serv, &init_net);
    svc_exit_thread(cb_info->rqst);
    cb_info->serv = NULL;
    cb_info->rqst = NULL;

```

Subject: Re: [PATCH] NFS: hard-code init_net for NFS callback transports
 Posted by [bfields](#) on Mon, 11 Jun 2012 12:37:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Fri, Jun 01, 2012 at 01:55:47PM +0400, Stanislav Kinsbursky wrote:

> This patch set is a bug fix for Bruce's 3.5 branch.
 > I'll rebase this for 3.4 and resend.

Apologies for neglecting this, I'm done with the bakeathon and should be back to this soon.

But, I'm a bit confused: you say you'll rebase this, but I've only seen two rebased patches for 3.4, and neither looks like a simple rebase of this one.

OK, I'll look more closely and probably I'll figure out. But in general, a little more detail in changelogs would help me process patches more quickly:

- Please make sure it's clear whether a given patch is a bug fix, a new feature, or code reshuffling that isn't intended to change behavior. If it's a bug fix, tell me whether we've had the bug forever or whether it's a recent regression. And (relevant here) if it's a recent regression, reference the ID of the commit that introduced it.
- If something is a backport, please reference in the changelog the commit ID of the backported patch, especially if it's not obviously the same.

--b.

```
>
> In case of destroying mount namespace on child reaper exit, nsproxy is zeroed
> to the point already. So, dereferencing of it is invalid.
> This patch hard-code "init_net" for all network namespace references for NFS
> callback services. This will be fixed with proper NFS callback
> containerization.
>
> Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>
> ---
> fs/nfs/callback.c | 11 ++++++-----
> 1 files changed, 5 insertions(+), 6 deletions(-)
>
> diff --git a/fs/nfs/callback.c b/fs/nfs/callback.c
> index 970659d..23ff18f 100644
> --- a/fs/nfs/callback.c
> +++ b/fs/nfs/callback.c
> @@ -17,7 +17,6 @@
> #include <linux/kthread.h>
> #include <linux/sunrpc/svcauth_gss.h>
> #include <linux/sunrpc/bc_xprt.h>
> -#include <linux/nsproxy.h>
>
> #include <net/inet_sock.h>
>
> @@ -107,7 +106,7 @@ nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
> {
>     int ret;
>
> -     ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET,
> +     ret = svc_create_xprt(serv, "tcp", &init_net, PF_INET,
>         nfs_callback_set_tcpport, SVC SOCK ANONYMOUS);
>     if (ret <= 0)
>         goto out_err;
> @@ -115,7 +114,7 @@ nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
>     dprintk("NFS: Callback listener port = %u (af %u)\n",
>
```

```

>     nfs_callback_tcpport, PF_INET);
>
> - ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET6,
> + ret = svc_create_xprt(serv, "tcp", &init_net, PF_INET6,
>     nfs_callback_set_tcpport, SVC_SOCK_ANONYMOUS);
> if (ret > 0) {
>     nfs_callback_tcpport6 = ret;
> @@ -184,7 +183,7 @@ nfs41_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
>     * fore channel connection.
>     * Returns the input port (0) and sets the svc_serv bc_xprt on success
>     */
> - ret = svc_create_xprt(serv, "tcp-bc", xprt->xprt_net, PF_INET, 0,
> + ret = svc_create_xprt(serv, "tcp-bc", &init_net, PF_INET, 0,
>     SVC_SOCK_ANONYMOUS);
> if (ret < 0) {
>     rqstp = ERR_PTR(ret);
> @@ -254,7 +253,7 @@ int nfs_callback_up(u32 minorversion, struct rpc_xprt *xprt)
>     char svc_name[12];
>     int ret = 0;
>     int minorversion_setup;
> - struct net *net = current->nsproxy->net_ns;
> + struct net *net = &init_net;
>
>     mutex_lock(&nfs_callback_mutex);
>     if (cb_info->users++ || cb_info->task != NULL) {
> @@ -330,7 +329,7 @@ void nfs_callback_down(int minorversion)
>     cb_info->users--;
>     if (cb_info->users == 0 && cb_info->task != NULL) {
>         kthread_stop(cb_info->task);
> - svc_shutdown_net(cb_info->serv, current->nsproxy->net_ns);
> + svc_shutdown_net(cb_info->serv, &init_net);
>     svc_exit_thread(cb_info->rqst);
>     cb_info->serv = NULL;
>     cb_info->rqst = NULL;
>

```

Subject: Re: [PATCH] NFS: hard-code init_net for NFS callback transports
Posted by [bfields](#) **on** Tue, 12 Jun 2012 15:53:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Mon, Jun 11, 2012 at 08:37:18AM -0400, J. Bruce Fields wrote:

> On Fri, Jun 01, 2012 at 01:55:47PM +0400, Stanislav Kinsbursky wrote:
> > This patch set is a bug fix for Bruce's 3.5 branch.
> > I'll rebase this for 3.4 and resend.
>
> Apologies for neglecting this, I'm done with the bakeathon and should be
> back to this soon.

>
> But, I'm a bit confused: you say you'll rebase this, but I've only seen
> two rebased patches for 3.4, and neither looks like a simple rebase of
> this one.

Oh, I see; the backport of "SUNRPC: new svc_bind() routine introduced"
is a combination of the patch by the same name upstream with this one.

In future for backports I'd rather keep a one-to-one correspondance
between the original patches and the backported patches. (Even if that
means 4.2 might not be as "bisectable".)

Also, get this patch into stable by just adding a "cc:
stable@vger.kernel.org" with the signed-off at the end of this patch.

I've gone ahead and fixed that up; results in the "for-3.4" and
"for-3.5" branches of

<git://linux-nfs.org/~bfields/linux-topics.git>

Let me know if anything looks wrong.

--b.

>
> OK, I'll look more closely and probably I'll figure out. But in
> general, a little more detail in changelogs would help me process
> patches more quickly:
>
> - Please make sure it's clear whether a given patch is a bug
> fix, a new feature, or code reshuffling that isn't intended to
> change behavior. If it's a bug fix, tell me whether we've had
> the bug forever or whether it's a recent regression. And
> (relevant here) if it's a recent regression, reference the ID
> of the commit that introduced it.
> - If something is a backport, please reference in the changelog
> the commit ID of the backported patch, especially if it's not
> obviously the same.
>
> --b.
>
>
>>
>> In case of destroying mount namespace on child reaper exit, nsproxy is zeroed
>> to the point already. So, dereferencing of it is invalid.
>> This patch hard-code "init_net" for all network namespace references for NFS
>> callback services. This will be fixed with proper NFS callback
>> containerization.

```

> >
> > Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>
> > ---
> > fs/nfs/callback.c | 11 ++++++-----
> > 1 files changed, 5 insertions(+), 6 deletions(-)
> >
> > diff --git a/fs/nfs/callback.c b/fs/nfs/callback.c
> > index 970659d..23ff18f 100644
> > --- a/fs/nfs/callback.c
> > +++ b/fs/nfs/callback.c
> > @@ -17,7 +17,6 @@
> > #include <linux/kthread.h>
> > #include <linux/sunrpc/svcauth_gss.h>
> > #include <linux/sunrpc/bc_xprt.h>
> > -#include <linux/nsproxy.h>
> >
> > #include <net/inet_sock.h>
> >
> > @@ -107,7 +106,7 @@ nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
> > {
> >     int ret;
> >
> > - ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET,
> > + ret = svc_create_xprt(serv, "tcp", &init_net, PF_INET,
> >     nfs_callback_set_tcport, SVC_SOCK_ANONYMOUS);
> >     if (ret <= 0)
> >         goto out_err;
> > @@ -115,7 +114,7 @@ nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
> >     dprintk("NFS: Callback listener port = %u (af %u)\n",
> >     nfs_callback_tcport, PF_INET);
> >
> > - ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET6,
> > + ret = svc_create_xprt(serv, "tcp", &init_net, PF_INET6,
> >     nfs_callback_set_tcport, SVC_SOCK_ANONYMOUS);
> >     if (ret > 0) {
> >         nfs_callback_tcport6 = ret;
> > @@ -184,7 +183,7 @@ nfs41_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
> >     * fore channel connection.
> >     * Returns the input port (0) and sets the svc_serv bc_xprt on success
> > */
> > - ret = svc_create_xprt(serv, "tcp-bc", xprt->xprt_net, PF_INET, 0,
> > + ret = svc_create_xprt(serv, "tcp-bc", &init_net, PF_INET, 0,
> >     SVC_SOCK_ANONYMOUS);
> >     if (ret < 0) {
> >         rqstp = ERR_PTR(ret);
> > @@ -254,7 +253,7 @@ int nfs_callback_up(u32 minorversion, struct rpc_xprt *xprt)
> >     char svc_name[12];
> >     int ret = 0;

```

```
> > int minorversion_setup;  
> > - struct net *net = current->nsproxy->net_ns;  
> > + struct net *net = &init_net;  
> >  
> > mutex_lock(&nfs_callback_mutex);  
> > if (cb_info->users++ || cb_info->task != NULL) {  
 > > @@ -330,7 +329,7 @@ void nfs_callback_down(int minorversion)  
> > cb_info->users--;  
> > if (cb_info->users == 0 && cb_info->task != NULL) {  
 > > kthread_stop(cb_info->task);  
> > - svc_shutdown_net(cb_info->serv, current->nsproxy->net_ns);  
> > + svc_shutdown_net(cb_info->serv, &init_net);  
> > svc_exit_thread(cb_info->rqst);  
> > cb_info->serv = NULL;  
> > cb_info->rqst = NULL;  
> >
```

Subject: Re: [PATCH] NFS: hard-code init_net for NFS callback transports

Posted by Stanislav Kinsbursky on Wed, 13 Jun 2012 08:16:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

> On Mon, Jun 11, 2012 at 08:37:18AM -0400, J. Bruce Fields wrote:
>> On Fri, Jun 01, 2012 at 01:55:47PM +0400, Stanislav Kinsbursky wrote:
>>> This patch set is a bug fix for Bruce's 3.5 branch.
>>> I'll rebase this for 3.4 and resend.
>>
>> Apologies for neglecting this, I'm done with the bakeathon and should be
>> back to this soon.
>>
>> But, I'm a bit confused: you say you'll rebase this, but I've only seen
>> two rebased patches for 3.4, and neither looks like a simple rebase of
>> this one.
>
> Oh, I see; the backport of "SUNRPC: new svc_bind() routine introduced"
> is a combination of the patch by the same name upstream with this one.
>
> In future for backports I'd rather keep a one-to-one correspondance
> between the original patches and the backported patches. (Even if that
> means 4.2 might not be as "bisectable".)
>
> Also, get this patch into stable by just adding a "cc:
> stable@vger.kernel.org" with the signed-off at the end of this patch.
>
> I've gone ahead and fixed that up; results in the "for-3.4" and
> "for-3.5" branches of
>

```
> git://linux-nfs.org/~bfields/linux-topics.git  
>  
> Let me know if anything looks wrong.  
>
```

Hi, Bruce. Thanks for your time and guidance with this patch set.
But I'm a bit confused - what I have to do now? Take the patches from your 3.4
branch and send them to "stable"?

```
> --b.  
>  
>>  
>> OK, I'll look more closely and probably I'll figure out. But in  
>> general, a little more detail in changelogs would help me process  
>> patches more quickly:  
>>  
>> - Please make sure it's clear whether a given patch is a bug  
>> fix, a new feature, or code reshuffling that isn't intended to  
>> change behavior. If it's a bug fix, tell me whether we've had  
>> the bug forever or whether it's a recent regression. And  
>> (relevant here) if it's a recent regression, reference the ID  
>> of the commit that introduced it.  
>> - If something is a backport, please reference in the changelog  
>> the commit ID of the backported patch, especially if it's not  
>> obviously the same.  
>>  
>> --b.  
>>  
>>  
>>>  
>>> In case of destroying mount namespace on child reaper exit, nsproxy is zeroed  
>>> to the point already. So, dereferencing of it is invalid.  
>>> This patch hard-code "init_net" for all network namespace references for NFS  
>>> callback services. This will be fixed with proper NFS callback  
>>> containerization.  
>>>  
>>> Signed-off-by: Stanislav Kinsbursky<skinsbursky@parallels.com>  
>>> ---  
>>> fs/nfs/callback.c | 11 +++++-----  
>>> 1 files changed, 5 insertions(+), 6 deletions(-)  
>>>  
>>> diff --git a/fs/nfs/callback.c b/fs/nfs/callback.c  
>>> index 970659d..23ff18f 100644  
>>> --- a/fs/nfs/callback.c  
>>> +++ b/fs/nfs/callback.c  
>>> @@ -17,7 +17,6 @@
```

```

>>> #include<linux/kthread.h>
>>> #include<linux/sunrpc/svcauth_gss.h>
>>> #include<linux/sunrpc/bc_xprt.h>
>>> -#include<linux/nsproxy.h>
>>>
>>> #include<net/inet_sock.h>
>>>
>>> @@ -107,7 +106,7 @@ nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
>>> {
>>>     int ret;
>>>
>>> -     ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET,
>>> +     ret = svc_create_xprt(serv, "tcp", &init_net, PF_INET,
>>>         nfs_callback_set_tcpport, SVC_SOCK_ANONYMOUS);
>>>     if (ret<= 0)
>>>         goto out_err;
>>> @@ -115,7 +114,7 @@ nfs4_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
>>>     dprintk("NFS: Callback listener port = %u (af %u)\n",
>>>         nfs_callback_tcpport, PF_INET);
>>>
>>> -     ret = svc_create_xprt(serv, "tcp", xprt->xprt_net, PF_INET6,
>>> +     ret = svc_create_xprt(serv, "tcp", &init_net, PF_INET6,
>>>         nfs_callback_set_tcpport, SVC_SOCK_ANONYMOUS);
>>>     if (ret> 0) {
>>>         nfs_callback_tcpport6 = ret;
>>> @@ -184,7 +183,7 @@ nfs41_callback_up(struct svc_serv *serv, struct rpc_xprt *xprt)
>>>     * fore channel connection.
>>>     * Returns the input port (0) and sets the svc_serv bc_xprt on success
>>>     */
>>> -     ret = svc_create_xprt(serv, "tcp-bc", xprt->xprt_net, PF_INET, 0,
>>> +     ret = svc_create_xprt(serv, "tcp-bc", &init_net, PF_INET, 0,
>>>         SVC_SOCK_ANONYMOUS);
>>>     if (ret< 0) {
>>>         rqstp = ERR_PTR(ret);
>>> @@ -254,7 +253,7 @@ int nfs_callback_up(u32 minorversion, struct rpc_xprt *xprt)
>>>     char svc_name[12];
>>>     int ret = 0;
>>>     int minorversion_setup;
>>> -     struct net *net = current->nsproxy->net_ns;
>>> +     struct net *net = &init_net;
>>>
>>>     mutex_lock(&nfs_callback_mutex);
>>>     if (cb_info->users++ || cb_info->task != NULL) {
>>> @@ -330,7 +329,7 @@ void nfs_callback_down(int minorversion)
>>>     cb_info->users--;
>>>     if (cb_info->users == 0&& cb_info->task != NULL) {
>>>         kthread_stop(cb_info->task);
>>> -     svc_shutdown_net(cb_info->serv, current->nsproxy->net_ns);

```

```
>>> + svc_shutdown_net(cb_info->serv,&init_net);
>>>   svc_exit_thread(cb_info->rqst);
>>>   cb_info->serv = NULL;
>>>   cb_info->rqst = NULL;
>>>
```

--
Best regards,
Stanislav Kinsbursky

Subject: Re: [PATCH] NFS: hard-code init_net for NFS callback transports

Posted by [bfields](#) on Wed, 13 Jun 2012 11:15:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Wed, Jun 13, 2012 at 12:16:07PM +0400, Stanislav Kinsbursky wrote:

```
> >On Mon, Jun 11, 2012 at 08:37:18AM -0400, J. Bruce Fields wrote:
> >>On Fri, Jun 01, 2012 at 01:55:47PM +0400, Stanislav Kinsbursky wrote:
> >>>This patch set is a bug fix for Bruce's 3.5 branch.
> >>>I'll rebase this for 3.4 and resend.
> >>
> >>Apologies for neglecting this, I'm done with the bakeathon and should be
> >>back to this soon.
> >>
> >>But, I'm a bit confused: you say you'll rebase this, but I've only seen
> >>two rebased patches for 3.4, and neither looks like a simple rebase of
> >>this one.
> >
> >Oh, I see; the backport of "SUNRPC: new svc_bind() routine introduced"
> >is a combination of the patch by the same name upstream with this one.
> >
> >In future for backports I'd rather keep a one-to-one correspondance
> >between the original patches and the backported patches. (Even if that
> >means 4.2 might not be as "bisectable".)
> >
> >Also, get this patch into stable by just adding a "cc:
> >stable@vger.kernel.org" with the signed-off at the end of this patch.
> >
> >I've gone ahead and fixed that up; results in the "for-3.4" and
> >"for-3.5" branches of
> >
> >git://linux-nfs.org/~bfields/linux-topics.git
> >
> >Let me know if anything looks wrong.
```

>
> Hi, Bruce. Thanks for your time and guidance with this patch set.
> But I'm a bit confused - what I have to do now? Take the patches
> from your 3.4 branch and send them to "stable"?

No, I'll take care of them.--b.

--b.
