
Subject: Netstat on Deb ovz vs Deb Proxmox
Posted by [Christian Blauch](#) on Mon, 18 Jun 2012 16:18:02 GMT
[View Forum Message](#) <> [Reply to Message](#)

-----BEGIN PGP SIGNED MESSAGE-----

Hash: SHA1

Hi guys,

i'm working on a monitoring solution for my hardware nodes.
Hosts A with Debian Squeeze and linux-image-2.6.32-5-ovnz-amd64 from the Debian Repository and Hosts B Debian Squeeze with Proxmox 2.6.32-12-pve from the Proxmoxrepo.
Both working with ovz Containers. When i'm trying to check netstat on Hosts A i see the Connections from the Hardwarenode, such as ntp. Hosts B (Proxmox) tells me the whole Connectiontree including every VM connection. That result is bad for my checks and i don't wanna write seperate checks for A & B.
Any ideas ?

-----BEGIN PGP SIGNATURE-----

Version: GnuPG/MacGPG2 v2.0.17 (Darwin)

Comment: GPGTools - <http://gpgtools.org>

Comment: Using GnuPG with Mozilla - <http://enigmail.mozdev.org/>

iQEcBAEBAgAGBQJP31S5AAoJENzPm0AOTN5bJzglAJPEnA0oUaBIDWwlpkT1 OrCv
HKIAKDFiqgkKZ7rVvDyxm7hgqRJVvgnq76c/RbF9dOXt71XiP10EtHGamJWs j1XN
72Squ6AhLCUakk1hqaNXITTs963VGXx9ZqwtghXct5yEFte1nYEgzCvUbMb q8r3
vpkCb1rViomKtykCZGPMDiHd08K91dcWEEtqGDr1is3WDw2rLX7VxThpM0DD Un6M
o2UZCcDQxW2EI3FbhRwEAFywjgWaMeh+u4tWlcp3mOhvtt2ANcKjIso2c7Kb Vhvx
us2Y5YXuawj1BGJ0qfW1s8KdqxfopSYJ4yVyKIFyTB+KADibsEo6NT7BBs4I nOA=
=g/TT

-----END PGP SIGNATURE-----

Subject: Re: Netstat on Deb ovz vs Deb Proxmox
Posted by [Joseph Hauptmann](#) on Tue, 19 Jun 2012 08:39:40 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi OpenVZ-Community, Hi Christian,

I noticed the same "problem" with the 2.6.32 kernels. Interestingly it only seems to happen on my rpm-based Kernels from the OpenVZ-Repo. The kernels I patched and compiled myself don't seem to behave that way.

Also, not all processes that open ports seem to be visible via netstat on the hw-node. Here the difference in behaviour between munin and apache2:

```
[root@srv05 ~]# vzctl exec 512 "netstat -tulpen | grep 4949"
tcp    0    0 0.0.0.0:4949      0.0.0.0:*
LISTEN 0      23963289  14168/munin-node
[root@srv05 ~]# vzctl exec 510 "netstat -tulpen | grep 4949"
tcp    0    0 0.0.0.0:4949      0.0.0.0:*
LISTEN 0      154512328  31520/munin-node
[root@srv05 ~]# netstat -tulpen|grep 4949
tcp    0    0 0.0.0.0:4949
0.0.0.0:*          LISTEN  0      56159312
652391/munin-node
[root@srv05 ~]# netstat -tulpen|grep :80
tcp    0    0 0.0.0.0:80
0.0.0.0:*          LISTEN  0      547379989
191426/apache2
tcp    0    0 :::80
 :::*          LISTEN  0      28979
10656/httpd
```

I only use venet-based networking on all my nodes.

Am 2012-06-18 18:18, schrieb Christian Blaich:

```
>
> Hi guys,
>
> i'm working on a monitoring solution for my hardware nodes.
> Hosts A with Debian Squeeze and linux-image-2.6.32-5-openvz-amd64 from
> the Debian Repository and Hosts B Debian Squeeze with Proxmox
> 2.6.32-12-pve from the Proxmoxrepo.
> Both working with ovz Containers. When i'm trying to check netstat on
> Hosts A i see the Connections from the Hardwarenode, such as ntp. Hosts
> B (Proxmox) tells me the whole Connectiontree including every VM
connection.
> That result is bad for my checks and i don't wanna write seperate checks
> for A & B.
> Any ideas ?
>
>
>
>
>
>
--
```

Joseph Hauptmann

/digiconcept/ - GmbH.
1080 Wien
Blindengasse 52/1

Tel. +43 1 218 0 212 - 24
Fax +43 1 218 0 212 - 10
