
Subject: [PATCH v4 7/9] IPC: message queue receive cleanup
Posted by [Stanislav Kinsbursky](#) on Mon, 13 Aug 2012 12:32:11 GMT
[View Forum Message](#) <> [Reply to Message](#)

This patch moves all message related manipulation into one function msg_fill().
Actually, two functions because of the compat one.

Signed-off-by: Stanislav Kinsbursky <skinsbursky@parallels.com>

Signed-off-by: Cyrill Gorcunov <gorcunov@openvz.org>

Conflicts:

arch/tile/kernel/compat.c

include/linux/compat.h

arch/tile/kernel/compat.c | 29 ++++++

include/linux/compat.h | 2 ++

include/linux/msg.h | 5 +++--

ipc/compat.c | 33 ++++++-----

ipc/msg.c | 44 ++++++-----

5 files changed, 74 insertions(+), 39 deletions(-)

diff --git a/arch/tile/kernel/compat.c b/arch/tile/kernel/compat.c

index d67459b..e74d61b 100644

--- a/arch/tile/kernel/compat.c

+++ b/arch/tile/kernel/compat.c

```
@@ -94,6 +94,35 @@ long compat_sys_sched_rr_get_interval(compat_pid_t pid,
    return ret;
}
```

```
+/*
```

```
+ * The usual compat_sys_msgsnd() and _msgrcv() seem to be assuming
```

```
+ * some different calling convention than our normal 32-bit tile code.
```

```
+ */
```

```
+
```

```
+/* Already defined in ipc/compat.c, but we need it here. */
```

```
+struct compat_msgbuf {
```

```
+    compat_long_t mtype;
```

```
+    char mtext[1];
```

```
+};
```

```
+
```

```
+long tile_compat_sys_msgsnd(int msqid,
```

```
+    struct compat_msgbuf __user *msgp,
```

```
+    size_t msgsz, int msgflg)
```

```
+{
```

```
+    compat_long_t mtype;
```

```
+
```

```
+    if (get_user(mtype, &msgp->mtype))
```

```

+ return -EFAULT;
+ return do_msgsnd(msqid, mtype, msgp->mtext, msgsz, msgflg);
+}
+
+long tile_compat_sys_msgrcv(int msqid,
+    struct compat_msgbuf __user *msgp,
+    size_t msgsz, long msgtyp, int msgflg)
+{
+ return do_msgrcv(msqid, msgp, msgsz, msgtyp, msgflg, compat_do_msg_fill);
+}
+
/* Provide the compat syscall number to call mapping. */
#undef __SYSCALL
#define __SYSCALL(nr, call) [nr] = (call),
diff --git a/include/linux/compat.h b/include/linux/compat.h
index 4e89039..6e035dc 100644
--- a/include/linux/compat.h
+++ b/include/linux/compat.h
@@ -245,6 +245,7 @@ struct compat_sysctl_args;
 struct compat_kexec_segment;
 struct compat_mq_attr;
 struct compat_msgbuf;
+struct msg_msg;

extern void compat_exit_robust_list(struct task_struct *curr);

@@ -258,6 +259,7 @@ compat_sys_get_robust_list(int pid, compat_uptr_t __user *head_ptr,
#ifdef CONFIG_ARCH_WANT_OLD_COMPAT_IPC
long compat_sys_semctl(int first, int second, int third, void __user *uptr);
long compat_sys_msgsnd(int first, int second, int third, void __user *uptr);
+long compat_do_msg_fill(void __user *dest, struct msg_msg *msg, size_t bufsz);
long compat_sys_msgrcv(int first, int second, int msgtyp, int third,
    int version, void __user *uptr);
long compat_sys_shmat(int first, int second, compat_uptr_t third, int version,
diff --git a/include/linux/msg.h b/include/linux/msg.h
index 6689e73..9411b76 100644
--- a/include/linux/msg.h
+++ b/include/linux/msg.h
@@ -105,8 +105,9 @@ struct msg_queue {
/* Helper routines for sys_msgsnd and sys_msgrcv */
extern long do_msgsnd(int msqid, long mtype, void __user *mtext,
    size_t msgsz, int msgflg);
-extern long do_msgrcv(int msqid, long *pmtyp, void __user *mtext,
-    size_t msgsz, long msgtyp, int msgflg);
+extern long do_msgrcv(int msqid, void __user *buf, size_t bufsz, long msgtyp,
+    int msgflg,
+    long (*msg_fill)(void __user *, struct msg_msg *, size_t ));

```

```

#endif /* __KERNEL__ */

diff --git a/ipc/compat.c b/ipc/compat.c
index 7cfdb5b..6b07f5c 100644
--- a/ipc/compat.c
+++ b/ipc/compat.c
@@ -341,13 +341,23 @@ long compat_sys_msgsnd(int first, int second, int third, void __user
*uptr)
    return do_msgsnd(first, type, up->mtext, second, third);
}

+long compat_do_msg_fill(void __user *dest, struct msg_msg *msg, size_t bufsz)
+{
+ struct compat_msgbuf __user *msgp;
+ size_t msgsz;
+
+ if (put_user(msg->m_type, &msgp->mtype))
+ return -EFAULT;
+
+ msgsz = (bufsz > msg->m_ts) ? msg->m_ts : bufsz;
+ if (store_msg(msgp->mtext, msg, msgsz))
+ return -EFAULT;
+ return msgsz;
+}
+
long compat_sys_msgrcv(int first, int second, int msgtyp, int third,
    int version, void __user *uptr)
{
- struct compat_msgbuf __user *up;
- long type;
- int err;
-
    if (first < 0)
        return -EINVAL;
    if (second < 0)
@@ -355,14 +365,14 @@ long compat_sys_msgrcv(int first, int second, int msgtyp, int third,
@@ -355,14 +365,14 @@ long compat_sys_msgrcv(int first, int second, int msgtyp, int third,
    if (!version) {
        struct compat_ipc_kludge ipck;
- err = -EINVAL;
        if (!uptr)
- goto out;
- err = -EFAULT;
+ return -EINVAL;
        if (copy_from_user (&ipck, uptr, sizeof(ipck)))
- goto out;
+ return -EFAULT;
        uptr = compat_ptr(ipck.msgp);

```

```

    msgtyp = ipck.msgtyp;
}
- up = uptr;
- err = do_msgrcv(first, &type, up->mtext, second, msgtyp, third);
- if (err < 0)
- goto out;
- if (put_user(type, &up->mtype))
- err = -EFAULT;
-out:
- return err;
+ return do_msgrcv(first, uptr, second, msgtyp, third, compat_do_msg_fill);
}
#else
long compat_sys_semctl(int semid, int semnum, int cmd, int arg)
diff --git a/ipc/msg.c b/ipc/msg.c
index 6bd66d3..08009f5 100644
--- a/ipc/msg.c
+++ b/ipc/msg.c
@@ -762,15 +762,30 @@ static inline int convert_mode(long *msgtyp, int msgflg)
    return SEARCH_EQUAL;
}

-long do_msgrcv(int msqid, long *pmtyp, void __user *mtext,
- size_t msgsz, long msgtyp, int msgflg)
+static long do_msg_fill(void __user *dest, struct msg_msg *msg, size_t bufsz)
+{
+ struct msgbuf __user *msgp = dest;
+ size_t msgsz;
+
+ if (put_user(msg->m_type, &msgp->mtype))
+ return -EFAULT;
+
+ msgsz = (bufsz > msg->m_ts) ? msg->m_ts : bufsz;
+ if (store_msg(msgp->mtext, msg, msgsz))
+ return -EFAULT;
+ return msgsz;
+}
+
+long do_msgrcv(int msqid, void __user *buf, size_t bufsz, long msgtyp,
+ int msgflg,
+ long (*msg_handler)(void __user *, struct msg_msg *, size_t ))
{
    struct msg_queue *msq;
    struct msg_msg *msg;
    int mode;
    struct ipc_namespace *ns;

- if (msqid < 0 || (long) msgsz < 0)

```

```

+ if (msqid < 0 || (long) bufsz < 0)
    return -EINVAL;
    mode = convert_mode(&msgtyp, msgflg);
    ns = current->nsproxy->ipc_ns;
@@ -813,7 +828,7 @@ long do_msggrcv(int msqid, long *pmtyp, void __user *mtext,
    * Found a suitable message.
    * Unlink it from the queue.
    */
- if ((msgsz < msg->m_ts) && !(msgflg & MSG_NOERROR)) {
+ if ((bufsz < msg->m_ts) && !(msgflg & MSG_NOERROR)) {
    msg = ERR_PTR(-E2BIG);
    goto out_unlock;
}
@@ -840,7 +855,7 @@ long do_msggrcv(int msqid, long *pmtyp, void __user *mtext,
    if (msgflg & MSG_NOERROR)
        msr_d.r_maxsize = INT_MAX;
    else
- msr_d.r_maxsize = msgsz;
+ msr_d.r_maxsize = bufsz;
    msr_d.r_msg = ERR_PTR(-EAGAIN);
    current->state = TASK_INTERRUPTIBLE;
    msg_unlock(msq);
@@ -903,29 +918,16 @@ out_unlock:
    if (IS_ERR(msg))
        return PTR_ERR(msg);

- msgsz = (msgsz > msg->m_ts) ? msg->m_ts : msgsz;
- *pmtyp = msg->m_type;
- if (store_msg(mtext, msg, msgsz))
- msgsz = -EFAULT;
-
+ bufsz = msg_handler(buf, msg, bufsz);
    free_msg(msg);

- return msgsz;
+ return bufsz;
}

SYSCALL_DEFINE5(msggrcv, int, msqid, struct msgbuf __user *, msgp, size_t, msgsz,
    long, msgtyp, int, msgflg)
{
- long err, mtype;
-
- err = do_msggrcv(msqid, &mtype, msgp->mtext, msgsz, msgtyp, msgflg);
- if (err < 0)
- goto out;
-
- if (put_user(mtype, &msgp->mtype))

```

```
- err = -EFAULT;
-out:
- return err;
+ return do_msgrcv(msqid, msgp, msgsz, msgtyp, msgflg, do_msg_fill);
}
```

```
#ifdef CONFIG_PROC_FS
```
