
Subject: independent communication through the bridge
Posted by [yuri_kurenkov](#) on Thu, 08 Nov 2012 13:10:40 GMT
[View Forum Message](#) <> [Reply to Message](#)

```
# vzctl create CTID
# vzctl set CTID --netiff_add eth0,,,FF:FF:FF:FF:FF:FF,vmbr0
```

```
NETIF=" ifname=eth0,bridge=vmbr0,mac=00:18:51:49:05:C2,host_ifname=v
eth108.0,host_mac=FF:FF:FF:FF:FF:FF "
```

```
# vzctl start CTID
```

```
Starting container...
Adding delta dev=/dev/ploop4 img=/vz/private/CTID/root.hdd/root.hdd (rw)
Mounting /dev/ploop4p1 at /vz/root/CTID fstype=ext4 data='balloon_ino=12,'
Container is mounted
Setting CPU units: 1000
Configure veth devices: vethCTID.0
Unable to create veth: Cannot assign requested address
Container start failed (try to check kernel messages, e.g. "dmesg | tail")
Killing container ...
Container was stopped
Unmounting file system at /vz/root/CTID
Unmounting device /dev/ploop4
Container is unmounted
```

Posted by [yuri_kurenkov](#) on Mon, 12 Nov 2012 09:22:20 GMT
[View Forum Message](#) <> [Reply to Message](#)
