

---

Subject: \*SOLVED\* startup scripts, network setup  
Posted by [szocske](#) on Tue, 19 Sep 2006 11:28:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi!

I am looking for any documentation (preferably something comprehensive like the old PDF manual, which seems outdated in this regard) on the VPE startup mechanisms, and the scripts involved.

My current suspicion about the startup mechanism is the following:

On vzctl start VEID, the file `/etc/vz/conf/VEID.conf` is consulted for config options. One of these is "OSTEMPLATE", in my case with value "debian-3.1-i386-minimal".

Prefix matching is done on this string with the filenames in `/etc/vz/dists/*.conf`. In my case, `debian-3.1.conf` is the best match. It contains further config options, like `ADD_IP` or `POST_CREATE`, which contain script names, relative to the path `/etc/vz/dists/scripts`.

On these events, the corresponding scripts are run inside the given virtual environment.

So, the question is: is the above correct? What is the `VEID.start` script I have been advised to use, and where is it supposed to be placed?

Second: Where can I configure what scripts to run on the host machine (or HW node, excuse my Xenism...) on VE startup? I must add `veth-s` to a bridge.

Thanks for all the help and the great product:

Gabor Szokoli

---

Subject: Re: startup scripts, network setup  
Posted by [Vasily Tarasov](#) on Tue, 19 Sep 2006 12:01:39 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

Quote: So, the question is: is the above correct?

You're right! Above is correct.

Quote:

What is the `VEID.start` script I have been advised to use, and where is it supposed to be placed?

Such files should reside in /etc/vz/conf/ directory.  
This script runs inside Virtual Environment after VE start.

Quote:Where can I configure what scripts to run on the host machine (or HW node, excuse my Xenism...) on VE startup? I must add veth-s to a bridge.

At the moment there is no such script. There are plans about creating such file in the near future. BTW, what name for the this file do you suggest? We have some disputes about it...

Thanks!

---

Subject: Re: startup scripts, network setup  
Posted by [szocske](#) on Tue, 19 Sep 2006 12:27:25 GMT  
[View Forum Message](#) <> [Reply to Message](#)

vass wrote on Tue, 19 September 2006 08:01Hello,

At the moment there is no such script. There are plans about creating such file in the near future. BTW, what name for the this file do you suggest? We have some disputes about it...

I don't think I have the experience to make an insightful suggestion, but I'd be happy with a \_HOST postfix after the existing option names, like ADD\_IP\_HOST=debian\_add\_ip\_host.sh, POST\_CREATE\_HOST=debian\_postcreate\_host.sh, etc...

It's not that urgent though, we can use wrapper scripts for VE startup, or ssh back to the host from POST\_CREATE.

Seriously though, prefix matching on the OSTEMPLATE?  
Do all partially matching .conf files get loaded, (debian.conf and debian-3.1.conf in my case) or best match only?

Is there a list of all possible parameter names for the VEID.conf and the dist/distname.conf files somewhere, btw? And could I theoretically duplicate entries between them, and if yes, which overrides the other?

Thank you for your time:

Gabor Szokoli

---

Subject: Re: startup scripts, network setup  
Posted by [Vasily Tarasov](#) on Tue, 19 Sep 2006 13:19:50 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Quote:I don't think I have the experience to make an insightful suggestion, but I'd be happy with a `_HOST` postfix after the existing option names, like `ADD_IP_HOST=debian_add_ip_host.sh`, `POST_CREATE_HOST=debian_postcreate_host.sh`, etc...

AFAIK there will be only one file like `<veid>.start` but it will be ran on HN. Something `<veid>.host-start`...

Quote:Do all partially matching `.conf` files get loaded, (`debian.conf` and `debian-3.1.conf` in my case) or best match only?

The rule is the following:

Suppose name of template is "debian-3.1"

If file `debian-3.1.conf` exists it will be loaded, no other files will be processed. But if `debian-3.1.conf` doesn't exist, then otemplate name "debian-3.1" will be truncated till first occurrence of "-" from the end. From "debian-3.1" we have "debian", thus `debian.conf` file will be loaded. If `debian.conf` doesn't exist default file will be loaded.

Quote:

Is there a list of all possible parameter names for the `VEID.conf` and the `dist/distname.conf` files somewhere, btw? And could I theoretically duplicate entries between them, and if yes, which overrides the other?

`man vps.conf` gives the list.

`dist/distname.conf` and `vps.conf` have different parameters. So no duplicating, overriding is possible.

HTH,  
vass.

HTH,  
vass.

---

---

Subject: Re: startup scripts, network setup  
Posted by [szocske](#) on Tue, 19 Sep 2006 14:01:42 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Thank you again.

---

---

Subject: Re: startup scripts, network setup  
Posted by [szocske](#) on Thu, 21 Sep 2006 09:17:24 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

vass wrote on Tue, 19 September 2006 09:19Quote:

Is there a list of all possible parameter names for the VEID.conf and the dist/distname.conf files somewhere, btw?

man vps.conf gives the list.

Great!

It does fail to mention the possibility to use \$VEID though.

This made me wonder: how would you formulate a generic VETH= line, where some bytes of the MAC address are VEID-derived thus unique?

(so I can just use the same VEID.conf file for all my otherwise identical VEs.)

---

---

Subject: Re: startup scripts, network setup

Posted by [Vasily Tarasov](#) on Thu, 21 Sep 2006 09:36:12 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Quote:It does fail to mention the possibility to use \$VEID though.

Well, I suppose the logic of man developers was something like that: the person looks at manpage about vps.conf, observes there:

Quote:

VE\_ROOT="directory"

Corresponds to the --root option.

then moves to manpage about vzctl and discover there \$VEID:

Quote:

--root path

Sets the path to root directory for this VPS. This is essentially a mount point for VPS root. Value must contain string \$VEID, which will be substituted with numeric VPS ID. Changing this parameter is not recommended, better edit vz(5) global configuration file.

As concerns

Quote:

This made me wonder: how would you formulate a generic VETH= line, where some bytes of the MAC address are VEID-derived thus unique?

Sorry. I don't understand you quite. AFAIK MAC address for veth device can be set by user with hand, no relationship with VEID...

---

---

Subject: Re: startup scripts, network setup

Posted by [szocske](#) on Thu, 21 Sep 2006 10:56:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

vass wrote on Thu, 21 September 2006 05:36

Well, I suppose the logic of man developers was something like that:

OK, OK, since then I realised I can't even write

```
VETH="veth$VEID.0 ... "
```

Quote:

As concerns

Quote:

This made me wonder: how would you formulate a generic VETH= line, where some bytes of the MAC address are VEID-derived thus unique?

Sorry. I don't understand you quite. AFAIK MAC address for veth device can be set by user with hand, no relationship with VEID...

True.

But MAC addresses must be unique: this is the only reason for separate VEID.conf files in our setup.

I'd like to be able to write something like this:

```
VETH=" veth${VEID}.0,10.20.30.40.$VEID_LOWBYTE.$VEID_HIBYTE,eth0,10  
.20.30.41.$VEID_LOWBYTE.$VEID_HIBYTE "
```

---

---

Subject: Re: startup scripts, network setup

Posted by [Vasily Tarasov](#) on Thu, 21 Sep 2006 11:01:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Now, when I understand what you want, I agree: there is no such possibility...

---