
Subject: Time inside container

Posted by [ilou](#) on Mon, 06 Jan 2014 22:26:12 GMT

[View Forum Message](#) <> [Reply to Message](#)

I am new here, Hi to all.

I've got some Openvz VPS from some hosting provider.

The time was out by 2 hours, even though I did set the proper timezone from inside the container.

I contacted the support.

The answer was they need to run some cronjob (that they trigger twice a day) to sync the VMs to the hardware node. Indeed this is supposed to be required in case the VM has been reboot or reinstalled according to the support.

Is that the way it has to be done ?

My understanding was rather that in anycase the container time was locked to the node time that it receives from it no matter what (reboot or reinstall) ?

I don't get the reason why the node would require some cron task to put things back in sync. To me the HN would just need proper time (i.e. ntpd)

Or am I missing something ?

Thanks in advance for any clarification.

Subject: Re: Time inside container

Posted by [dipps](#) on Sun, 12 Jan 2014 10:31:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

The container and the HN share the same kernel. I would have thought that kernel time in the container would track kernel time in the HN. Isn't that how it works?

Subject: Re: Time inside container

Posted by [ilou](#) on Sun, 12 Jan 2014 12:49:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

dipps wrote on Sun, 12 January 2014 05:31 I would have thought that kernel time in the container would track kernel time in the HN. Isn't that how it works?

Yes that is pretty much the way I understand it as well ... hence my OP: why would some kind of cron task be run in order resync the container in case it'd lost the "master clock" ?

... or would that mean that in this case it is the HN that hasn't proper time ?
Maybe the provider doesn't run ntpd on the HN or run different hosting services on same HN which prevents him to have things setup this way? I haven't got the clue at this point.

I am just trying to understand the proper way it should be done so that I can discuss with the provider with a better understanding of this all.

Subject: Re: Time inside container
Posted by [dipps](#) on Sun, 12 Jan 2014 13:49:01 GMT
[View Forum Message](#) <> [Reply to Message](#)

There's a section "Changing System Time from VPS" in the OpenVZ Users Guide. It recommends running ntpd in one container, then giving this container capability sys_time so it can set the time for the HN. And presumably the other containers.

Is anyone able to confirm that container time is based on HN time?

Subject: Re: Time inside container
Posted by [Paparaciz](#) on Wed, 15 Jan 2014 19:09:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,
Probably the time is wrong in HN, and hoster have to ensure that time in HN is right.
in CT you only have to set proper timezone.

running ntpd in CT will not help even with sys_time capability. few years ago I tried, but after ~1min time in CT changes back to HN time. dunno how this works today, but anyway this is wrong way to go.

Subject: Re: Time inside container
Posted by [dipps](#) on Tue, 18 Mar 2014 08:38:01 GMT
[View Forum Message](#) <> [Reply to Message](#)

This seems to be working for me:

HN: centos 6.4, 2.6.32-042stab078.28
Container: debian 7.4

Container has --capability sys_time:on and runs openntpd - I don't need all of xntpd. It's keeping in sync and the CT updates time on the HN.

The HN time was pretty close to start with, so to tell if it was working, I manually set it a minute wrong. 2 days later it was in sync again.

Paparaciz, interested why you think this is the wrong way to go. So far it does all I need.

Subject: Re: Time inside container
Posted by [Paparaciz](#) on Tue, 18 Mar 2014 09:18:41 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi dipps,
don't remember exact details, but as I said:

running ntpd in CT will not help even with sys_time capability. few years ago I tried, but after ~1min time in CT changes back to HN time. dunno how this works today.

it is wrong way because time sync should be done in HN, not in CT.

Subject: Re: Time inside container
Posted by [dipps](#) on Tue, 18 Mar 2014 11:38:22 GMT
[View Forum Message](#) <> [Reply to Message](#)

Paparaciz wrote on Tue, 18 March 2014 19:48.. dunno how this works today.

Looks OK so far! (as the falling man said before he hit the ground)

Paparaciz wrote it is wrong way because time sync should be done in HN, not in CT.

I would like to run as little in the HN as possible, for security reasons. The full xntpd seems a pretty big deal. openntpd seems more lightweight, but I still like restricting it to a CT.

Subject: Re: Time inside container
Posted by [blahugo@yahoo.de](#) on Fri, 21 Mar 2014 14:26:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

It is possible to run ntpd inside a container and sync the HN.
This is our standard setup.

You'll have to grant the container the capability sys_time.

```
# vzctl set VEID --capability sys_time:on --save
```

And configure your ntpd inside the container to sync the hardware clock.

On RHEL-based systems for example:

```
# /etc/sysconfig/ntpd
```

```
# Drop root to id 'ntp:ntp' by default.
```

```
OPTIONS="-u ntp:ntp -p /var/run/ntpd.pid"
```

```
# Set to 'yes' to sync hw clock after successful ntpdate.  
SYNC_HWCLOCK=yes
```

Lookout for your Debian config file.

On RHEL6-based systems this is caused by the compile flag
CONFIG_SECURITY_FILE_CAPABILITIES=y.

Find this on the HN:
grep CAPABILITIES /boot/config-\$(uname -r)

Hope this helps.

regards,
blahugo
