
Subject: raw disk access from container

Posted by [smal2014](#) on Tue, 04 Feb 2014 12:20:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

I've been trying to evaluate if OpenVZ would work to give physical access to a raw device from the container. So far I have been unsuccessful (partly). This is on Centos 6.5 host and container.

Basically, here's what I've done :

[host]

```
# lvcreate -L 500m /dev/virtual-machines
```

```
# raw /dev/raw/raw1 /dev/virtual-machines/lvol0
```

```
# raw -qa
```

```
/dev/raw/raw1: bound to major 253, minor 9
```

```
# vzctl set 1 --devnodes "raw/raw1:rwq raw/rawctl:rwq" --save
```

```
# vzctl enter 1
```

[container]

```
# [root@ /]# raw -qa
```

```
/dev/raw/raw1: bound to major 253, minor
```

```
# [root@ /]# udevadm test /dev/raw/raw1
```

```
run_command: calling: test
```

```
...
```

```
unable to open device '/sys/dev/raw/raw1'
```

I've got to the point where I can see /dev/raw/rawctl be able to query it. Although it is not putting the raw device in the /sys/dev/block

I've put the following in /etc/udev/rules.d/60-raw.rules (although didn't really understand) :

```
SUBSYSTEM=="block", ENV{MAJOR}=="253", ENV{MINOR}=="9", GROUP:="ats",  
OWNER="nobody"
```

I'm sure I'm missing important pieces. Basically I can't open the raw device I created.

Thanks!

Subject: Re: raw disk access from container

Posted by [smal2014](#) on Wed, 05 Feb 2014 03:51:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

I might have fixed my own problem temporarily. The device /dev/dm-8 from the logical volume creation showed up. I could open that device without any problems.

I used --devices "b:253:9:rwq" or --devnodes <vg>/<lv>:rwq and then /dev/dm-8 popped up.
