

---

Subject: Snapshotscript Ploop/Backup

Posted by [luzifer2222](#) on Fri, 09 May 2014 15:14:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hey Guys,

I need help with the Snapshot-script.

I take this script to do my snapshots:

```
#!/bin/bash
```

```
array_der_virtuellen_maschinen=$(/usr/sbin/vzlist -a1H)
```

```
for virtuelle_maschine in $array_der_virtuellen_maschinen;
do
```

```
BACKUPPATH=/raid/.backup_vz/$virtuelle_maschine/$virtuelle_maschine-$( date
+%F_%H_%M )
```

```
#create BACKUP-PATH
```

```
/bin/mkdir -p $BACKUPPATH
```

```
# Known snapshot ID
```

```
ID=$(uuidgen)
```

```
VE_PRIVATE=$(/usr/sbin/vzlist -H -o private $virtuelle_maschine)
```

```
# Take a snapshot without suspending a CT and saving its config
```

```
/usr/sbin/vzctl snapshot $virtuelle_maschine --id $ID
```

```
# Perform a backup using your favorite backup tool
```

```
# (cp is just an example)
```

```
/usr/bin/rsync -av $VE_PRIVATE/root.hdd/* $BACKUPPATH/
```

```
# Delete (merge) the snapshot
```

```
/usr/sbin/vzctl snapshot-delete $virtuelle_maschine --id $ID
```

```
# remove old backups
```

```
/bin/rm -rf $( find /raid/.backup_vz/$virtuelle_maschine/* -type d -name "$virtuelle_maschine*"
-exec ls -d1rt "{}" + | head -n-4 )
```

```
done
```

```
chmod 600 /raid/.backup_vz
```

```
echo "BACKUP FINISHED."
```

But I do not understand why I first create a snapshot then copy it to my backup path and after that I delete the snapshot.

Every time I backup my CT 's I have to copy the complete root.hdd directory, but my CT Ploop

devices are huge and it takes a lot of time to copy it.  
Is there a opportunity to copy just the created snapshot files?

I hope anyone could help me. Thank you.

---