
Subject: Problem amavis

Posted by [Kolab](#) on Tue, 07 Jul 2015 08:59:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

I just installed Kolab 3.4 on a VM OpenVZ (CentOS 7.1.1503).

Everything works fine apart from the amavisd service.

It can not start.

Result, emails are blocked in the postfix queue.

If I disable the use of amavis-new in postfix, emails can circulate.

The error code when running the service:

code = exited, status = 227 / NO_NEW_PRIVILEGES

Ok, and what can I do to fix this ?

Thank you for your help!

Best Regards

Martin

```
[root@kolab ~]# service amavisd status
```

```
Redirecting to /bin/systemctl status amavisd.service
```

```
amavisd.service - Amavisd-new is an interface between MTA and content checkers.
```

```
Loaded: loaded (/usr/lib/systemd/system/amavisd.service; enabled)
```

```
Active: failed (Result: start-limit) since Mon 2015-07-06 09:23:36 EDT; 45min ago
```

```
Docs:
```

```
Process: 465 ExecStart=/usr/sbin/amavisd -c /etc/amavisd/amavisd.conf (code=exited, status=227/NO_NEW_PRIVILEGES)
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[4235]: Failed at step NO_NEW_PRIVILEGES spawning /usr/sbin/amavisd: Invalid argument
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[1]: amavisd.service: control process exited, code=exited status=227
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[1]: Failed to start Amavisd-new is an interface between MTA and content checkers..
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[1]: Unit amavisd.service entered failed state.
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[1]: amavisd.service holdoff time over, scheduling restart.
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[1]: Stopping Amavisd-new is an interface between MTA and content checkers....
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[1]: Starting Amavisd-new is an interface between MTA and content checkers....
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[1]: amavisd.service start request repeated too quickly, refusing to start.
```

```
Jul 02 05:46:43 kolab.qi.fr systemd[1]: Failed to start Amavisd-new is an interface between MTA and content checkers..
```

Jul 02 05:46:43 kolab.qi.fr systemd[1]: Unit amavisd.service entered failed state.
[root@kolab ~]#

```
[root@kolab ~]# postqueue -p
-Queue ID- --Size-- ----Arrival Time---- -Sender/Recipient-----
DD866188A082    365 Wed Jul  1 11:57:28 toto.martin@qi.fr
                (connect to 127.0.0.1[127.0.0.1]:10024: Connection refused)
                toto.martin@qi.fr
```

```
-- 1 Kbytes in 1 Request.
You have mail in /var/spool/mail/root
[root@kolab ~]# /etc/init.d/clamd stop
```

LOG

```
Jul  1 13:28:03 kolab clamd[3741]: SelfCheck: Database status OK.
Jul  1 13:34:48 kolab postfix/qmgr[11624]: DD866188A082: from=<toto.martin@qi.fr>, size=365,
nrcpt=1 (queue active)
Jul  1 13:34:48 kolab postfix/smtp[20438]: connect to 127.0.0.1[127.0.0.1]:10024: Connection
refused
Jul  1 13:34:48 kolab postfix/smtp[20438]: DD866188A082: to=<toto.martin@qi.fr>, relay=none,
delay=5840, delays=5840/0.01/0/0, dsn=4.4.1, status=deferred (co$
Jul  1 13:38:03 kolab clamd[3741]: SelfCheck: Database status OK.
```

Subject: Re: Problem amavis
Posted by [mallerton](#) on Mon, 10 Aug 2015 19:51:52 GMT
[View Forum Message](#) <> [Reply to Message](#)

did you resolve this? I think you might be able to do so by removing the line
NoNewPrivileges=true from /usr/lib/systemd/system/amavisd.service
