
Subject: [PATCH] Don't give bad kprobes example aka ") < 0))" typo

Posted by [Alexey Dobriyan](#) on Wed, 15 Nov 2006 11:50:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

Signed-off-by: Alexey Dobriyan <adobriyan@openvz.org>

Documentation/kprobes.txt | 5 +++--
1 file changed, 3 insertions(+), 2 deletions(-)

```
--- a/Documentation/kprobes.txt
+++ b/Documentation/kprobes.txt
@@ -442,9 +442,10 @@ static int __init kprobe_init(void)
    kp.fault_handler = handler_fault;
    kp.symbol_name = "do_fork";

- if ((ret = register_kprobe(&kp) < 0)) {
+ ret = register_kprobe(&kp);
+ if (ret < 0) {
    printk("register_kprobe failed, returned %d\n", ret);
- return -1;
+ return ret;
    }
    printk("kprobe registered\n");
    return 0;
```

Subject: Re: [PATCH] Don't give bad kprobes example aka ") < 0))" typo

Posted by [Christoph Hellwig](#) on Wed, 15 Nov 2006 11:57:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Wed, Nov 15, 2006 at 06:56:19PM +0300, Alexey Dobriyan wrote:

> Signed-off-by: Alexey Dobriyan <adobriyan@openvz.org>

> ---

>

> Documentation/kprobes.txt | 5 +++--

> 1 file changed, 3 insertions(+), 2 deletions(-)

>

> --- a/Documentation/kprobes.txt

> +++ b/Documentation/kprobes.txt

> @@ -442,9 +442,10 @@ static int __init kprobe_init(void)

> kp.fault_handler = handler_fault;

> kp.symbol_name = "do_fork";

>

> - if ((ret = register_kprobe(&kp) < 0)) {

> + ret = register_kprobe(&kp);

> + if (ret < 0) {

> printk("register_kprobe failed, returned %d\n", ret);

```
> - return -1;  
> + return ret;
```

This looks good, thanks.
