

---

Subject: **\*SOLVED\*** sysctl from inside VE fails to set a parameter

Posted by [iziz](#) on Thu, 16 Nov 2006 09:25:50 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

I'm not satisfied with default Linux kernel behaviour in out of memory situation. I try to change it to smth more appropriate for one of my VEs from inside it and see strange error:

```
[root@my.host:~]$ sysctl -w vm.overcommit_memory=2
error: unknown error 1 setting key 'vm.overcommit_memory'
```

Any clues who generates this? How to change vm.overcommit\_memory for one particular VE?

---

---

Subject: Re: sysctl from inside VE fails to set a parameter

Posted by [dev](#) on Thu, 16 Nov 2006 10:45:25 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

AFAIR, overcommit mode can be changed for whole node only now.

If you need to protect your whole VE from OOM killer set oomguarpages.

---

---

Subject: Re: sysctl from inside VE fails to set a parameter

Posted by [iziz](#) on Thu, 16 Nov 2006 10:50:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

So if I try 'sysctl -w vm.overcommit\_memory=2' in root node it should work for all VEs, right?

---

---

Subject: Re: sysctl from inside VE fails to set a parameter

Posted by [dev](#) on Thu, 16 Nov 2006 11:03:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

yup.

---

---

Subject: Re: sysctl from inside VE fails to set a parameter

Posted by [iziz](#) on Thu, 16 Nov 2006 11:07:01 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

thanks!

---