

---

Subject: [PATCH 4/5] fixing errors handling during pci\_driver resume stage [misc]  
Posted by [Dmitriy Monakhov](#) on Tue, 09 Jan 2007 09:01:47 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

pci drivers have to return correct error code during resume stage in case of errors.

Signed-off-by: Dmitriy Monakhov <dmonakhov@openvz.org>

-----

```
diff --git a/drivers/ide/pci/sc1200.c b/drivers/ide/pci/sc1200.c
index ff80937..a426905 100644
--- a/drivers/ide/pci/sc1200.c
+++ b/drivers/ide/pci/sc1200.c
@@ -394,10 +394,16 @@ static int sc1200_suspend (struct pci_de
 static int sc1200_resume (struct pci_dev *dev)
 {
     ide_hwif_t *hwif = NULL;
+ int err;

     pci_set_power_state(dev, PCI_D0); // bring chip back from sleep state
     dev->current_state = PM_EVENT_ON;
- pci_enable_device(dev);
+ err = pci_enable_device(dev);
+ if (err) {
+     dev_err(&dev->dev, "Cannot enable PCI device, aborting.\n");
+     return err;
+ }
+
     //
     // loop over all interfaces that are part of this pci device:
     //
```

```
diff --git a/drivers/misc/tifm_7xx1.c b/drivers/misc/tifm_7xx1.c
index 2ab7add..d659ad9 100644
--- a/drivers/misc/tifm_7xx1.c
+++ b/drivers/misc/tifm_7xx1.c
@@ -274,10 +274,15 @@ static int tifm_7xx1_suspend(struct pci_
 static int tifm_7xx1_resume(struct pci_dev *dev)
 {
     struct tifm_adapter *fm = pci_get_drvdata(dev);
- unsigned long flags;
+ unsigned long flags, err;

     pci_restore_state(dev);
-     pci_enable_device(dev);
+ err = pci_enable_device(dev);
+ if (err) {
+     dev_err(&dev->dev, "Cannot enable PCI device, aborting.\n");
+     return err;
+ }
```

```

+ }
+
    pci_set_power_state(dev, PCI_D0);
    pci_set_master(dev);

diff --git a/drivers/mmc/sdhci.c b/drivers/mmc/sdhci.c
index c2d13d7..736f74c 100644
--- a/drivers/mmc/sdhci.c
+++ b/drivers/mmc/sdhci.c
@@ -1109,7 +1109,11 @@ static int sdhci_resume (struct pci_dev

    pci_set_power_state(pdev, PCI_D0);
    pci_restore_state(pdev);
- pci_enable_device(pdev);
+ ret = pci_enable_device(pdev);
+ if (ret) {
+ dev_err(&pdev->dev, "Cannot enable PCI device, aborting.\n");
+ return ret;
+ }

    for (i = 0; i < chip->num_slots; i++) {
        if (!chip->hosts[i])
diff --git a/drivers/parisc/superio.c b/drivers/parisc/superio.c
index 1fd97f7..4428ffa 100644
--- a/drivers/parisc/superio.c
+++ b/drivers/parisc/superio.c
@@ -199,7 +199,8 @@ superio_init(struct pci_dev *pcidev)
    pci_write_config_word (pdev, PCI_COMMAND, word);

    pci_set_master (pdev);
- pci_enable_device(pdev);
+ if (pci_enable_device(pdev))
+ return;

    /*
     * Next project is programming the onboard interrupt controllers.
@@ -275,6 +276,7 @@ superio_init(struct pci_dev *pcidev)
    SUPERIO, (void *)sio)) {

    printk(KERN_ERR PFX "could not get irq\n");
+ pci_disable_device(pdev);
    BUG();
    return;
}

```

---