
Subject: OpenVZ and Debian
Posted by [adebisi](#) on Sun, 15 Jan 2006 22:11:27 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi all,
i read many many posts about vserver VS OpenVZ so here i am

I would like to try it but i am not able to compile kernel after patch.

I receive a lot of hunks during patching kernel and after make menuconfig when i did make bzImage ld error and die.

I read that kernel patch was tested only on redhat and CENTOS..

There is no way to install OpenVZ on a debian system ?

Thanks in advance

Subject: Re: OpenVZ and Debian
Posted by [Valmont](#) on Sun, 15 Jan 2006 22:31:21 GMT
[View Forum Message](#) <> [Reply to Message](#)

Probably you patch kernel-source of wrong version or it from your distr.

You should get kernel from <http://www.kernel.org> 2.6.8)
and apply patch to it, or get already patched, full version from here:
<http://download.openvz.org/kernel/022stab061.1/ovzkernel-2.6.8-022stab061.1.src.rpm>

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Sun, 15 Jan 2006 23:18:48 GMT
[View Forum Message](#) <> [Reply to Message](#)

No.
I downloaded 2.6.8 from kernel.org and after applied patch.

Anyway i will try rpm source and let you know.

Subject: Re: OpenVZ and Debian

Posted by [adebisi](#) on Mon, 16 Jan 2006 00:27:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

My fault.

I downloaded 2.6.0 instead of 2.6.8

I am really sorry to let you loose time about my errors.

Subject: Re: OpenVZ and Debian

Posted by [adebisi](#) on Mon, 16 Jan 2006 02:14:20 GMT

[View Forum Message](#) <> [Reply to Message](#)

Anyway...

I receive following error when i try to compile module builtin:

```
kernel/built-in.o(.text+0x25da4): In function `init_ve_proc':
: undefined reference to `proc_fs_type'
kernel/built-in.o(.text+0x2605b): In function `init_ve_devpts':
: undefined reference to `devpts_fs_type'
kernel/built-in.o(.text+0x2610b): In function `init_ve_shmem':
: undefined reference to `tmpfs_fs_type'
kernel/built-in.o(.text+0x261af): In function `init_ve_sysfs':
: undefined reference to `class_obj_subsys'
kernel/built-in.o(.text+0x261c7): In function `init_ve_sysfs':
: undefined reference to `class_obj_subsys'
kernel/built-in.o(.text+0x261cf): In function `init_ve_sysfs':
: undefined reference to `class_obj_subsys'
kernel/built-in.o(.text+0x2621b): In function `init_ve_sysfs':
: undefined reference to `class_subsys'
kernel/built-in.o(.text+0x26233): In function `init_ve_sysfs':
: undefined reference to `class_subsys'
kernel/built-in.o(.text+0x2623b): In function `init_ve_sysfs':
: undefined reference to `class_subsys'
kernel/built-in.o(.text+0x2628b): In function `init_ve_sysfs':
: undefined reference to `net_class'
kernel/built-in.o(.text+0x26292): In function `init_ve_sysfs':
: undefined reference to `net_class'
kernel/built-in.o(.text+0x2629a): In function `init_ve_sysfs':
: undefined reference to `net_class'
make: *** [.tmp_vmlinux1] Error 1
```

If i try to compile as modules i receive of course another error like undefined symbol and so on..

Where i am wrong ?

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Mon, 16 Jan 2006 05:33:20 GMT
[View Forum Message](#) <> [Reply to Message](#)

First I hope that OpenVZ patch applied well, there was no rejects and so on.

Second, it is hard to tell what's wrong without having your .config. Note that some combinations won't work (see bug #52).

So, you'd better take one of the existing configs from <http://download.openvz.org/kernel/current/configs/> and put it as .config to your source tree, then run make oldconfig and compile the kernel as usual. Or check bug #52 for known issues and change config options accordingly.

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Mon, 16 Jan 2006 13:08:41 GMT
[View Forum Message](#) <> [Reply to Message](#)

Patch was applied well.
Problem was .config but with your help and after reading your instructions everything works now.

Thanks a lot all

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Mon, 16 Jan 2006 13:44:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

mmm
kernel works but after I install from source vzctl I receive this error when I try to start /etc/init.d/vz

/etc/init.d/vz: line 26: /etc/rc.d/init.d/functions: No such file or directory

Anyway I did find to try where possible file functions is and these are results:

/usr/lib/vzctl/scripts/vps-functions

I need to use this one instead or there is another solution?

I read also this thread:

<http://forum.openvz.org/index.php?t=tree&th=184&mid=822&&rev=&reveal=>
but I can't still solve the problem.

What do you suggest ?

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Mon, 16 Jan 2006 13:53:21 GMT
[View Forum Message](#) <> [Reply to Message](#)

Debian needs its own init script, since it is not like RedHat or Gentoo. Currently we have one for RedHat-like systems (included into vzctl rpm) and the one for Gentoo systems (available from Gentoo portage).

So it needs to be written...even by you, if you take a look at other scripts from the same directory and see what do they do to print success/error messages and so on. I can definitely help.

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Mon, 16 Jan 2006 21:25:38 GMT
[View Forum Message](#) <> [Reply to Message](#)

Ok looklike it works now.

I am actually trying to create a vs debian.

Anyway i had to add following to your init script:

(from functions file taken from redhat 9)

Quote:

```
#. /etc/rc.d/init.d/functions
```

```
action() {  
    STRING=$1  
    echo -n "$STRING "  
    shift  
    #initlog $INITLOG_ARGS -c "$*" && success "$STRING" || failure "$STRING"  
    rc=$?  
    echo  
    return $rc  
}
```

```
echo_success() {  
    [ "$BOOTUP" = "color" ] && $MOVE_TO_COL  
    echo -n "[ "  
    [ "$BOOTUP" = "color" ] && $SETCOLOR_SUCCESS  
    echo -n "$OK"  
    [ "$BOOTUP" = "color" ] && $SETCOLOR_NORMAL  
    echo -n "]"  
    echo -ne "\r"  
    return 0  
}
```

```
success() {
# if [ -z "${IN_INITLOG:-}" ]; then
#   initlog $INITLOG_ARGS -n $0 -s "$1" -e 1
#   else
#     # silly hack to avoid EPIPE killing rc.sysinit
#     trap "" SIGPIPE
#     echo "$0 \"\$1\" 1" >&21
#     trap - SIGPIPE
#     [ "$BOOTUP" != "verbose" -a -z "$LSB" ] && echo_success
#     return 0
#   }
}
#Disable everywhere initlog command cause i didnt find any #initlog package for debian.
```

Of course i could also create a file functions with these functions and let your script include it.

I used your binary packages to do that.

So .. i am checking and let you know if it works totally or not.

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Mon, 16 Jan 2006 22:19:17 GMT
[View Forum Message](#) <> [Reply to Message](#)

So
if i try to include those functions in a file and then include that file in vz init script without comment anything it looklike works fine but..

After debootstraped and done some configuration like in kir debian template tutorial i receive the following error:

Quote:
vzctl start 777
Starting VPS ...
VPS is mounted
Adding IP address(es): 1.1.1.7
arp send: unknown iface eth : No such device
vps-net_add WARNING: arp send -c 1 -w 1 -D -e 1.1.1.7 eth FAILED
RTNETLINK answers: Network is down
vps-net_add ERROR: Unable to add route /sbin/ip route add 1.1.1.7 dev venet0 src 1.1.1.11
VPS start failed
Stopping VPS ...
VPS was stopped
vzquota : (error) Quota off syscall for id 777: Device or resource busy
vzquota setlimit -f failed [3]
VPS is unmounted

Ethernet module or anyway ethernet config has some problem and quota looklike have too.

Checking and checking...

Adding IP address(es): 1.1.1.6

Running: /usr/lib/vzctl/scripts/vps-net_add

arp send: unknown iface eth : No such device

vps-net_add WARNING: arp send -c 1 -w 1 -D -e 1.1.1.6 eth FAILED

RTNETLINK answers: Network is down

vps-net_add ERROR: Unable to add route /sbin/ip route add 1.1.1.6 dev venet0 src 1.1.1.11

iface eth ? not eth0 ? help needed :d

Subject: Re: OpenVZ and Debian

Posted by [kir](#) on Tue, 17 Jan 2006 07:09:32 GMT

[View Forum Message](#) <> [Reply to Message](#)

Can you post the output of '/sbin/ip a l; /sbin/ip r l' here?

Subject: Re: OpenVZ and Debian

Posted by [adebisi](#) on Tue, 17 Jan 2006 07:59:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

vps:~# /sbin/ip a l

1: lo: <LOOPBACK,UP> mtu 16436 qdisc noqueue
link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
inet 127.0.0.1/8 scope host lo

2: eth0: <BROADCAST,MULTICAST,UP> mtu 1500 qdisc pfifo_fast qlen 1000
link/ether 00:13:8f:0c:16:de brd ff:ff:ff:ff:ff:ff
inet 1.1.1.11/28 brd 1.1.1.15 scope global eth0

vps:~# /sbin/ip r l

1.1.1.0/28 dev eth0 proto kernel scope link src 1.1.1.11
default via 1.1.1.14 dev eth0

address and route looklike work well

Subject: Re: OpenVZ and Debian

Posted by [kir](#) on Tue, 17 Jan 2006 08:29:15 GMT

[View Forum Message](#) <> [Reply to Message](#)

It looks like venet0 device is not up.

It happened because in the stuff you added to /etc/init.d/vz there is a shell function called 'action' which should execute the command -- and you commented out that actual command execution:

```
#initlog $INITLOG_ARGS -c "$*" && success "$$STRING" || failure "$$STRING"
```

Please put something like this instead of the above line:

```
*$ && success "$$STRING" || failure "$$STRING"
```

so the actual code passed into the function will be executed.

Alternatively, to set up venet0 device, you have to do the following:

```
modprobe vznetdev
modprobe vznet
ip link set venet0 up
ip addr add 0.0.0.0/0 dev venet0
sysctl -w net.ipv4.conf.venet0.send_redirects=0
```

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Tue, 17 Jan 2006 13:35:57 GMT
[View Forum Message](#) <> [Reply to Message](#)

it works.

Quote:Please put something like this instead of the above line:

```
*$ && success "$$STRING" || failure "$$STRING"
```

I just need this on functions file.

That's my functions file if you need:

```
Quote:vps:~# cat /etc/init.d/functions
action() {
STRING=$1
echo -n "$STRING "
shift
$$STRING
*$ && success "$$STRING" || failure "$$STRING"
rc=$?
echo
return $rc
}
```

```
echo_success() {
```

```

[ "$BOOTUP" = "color" ] && $MOVE_TO_COL
echo -n "["
[ "$BOOTUP" = "color" ] && $SETCOLOR_SUCCESS
echo -n "$OK"
[ "$BOOTUP" = "color" ] && $SETCOLOR_NORMAL
echo -n "]"
echo -ne "\r"
return 0
}

success() {
trap - SIGPIPE
[ "$BOOTUP" != "verbose" -a -z "$LSB" ] && echo_success
return 0
}

```

Thanks for all!

Subject: Re: OpenVZ and Debian
 Posted by [adebisi](#) on Tue, 17 Jan 2006 13:44:46 GMT
[View Forum Message](#) <> [Reply to Message](#)

```

Quote:vps:~# vzctl start 777
Starting VPS ...
Running: /usr/sbin/vzquota show 777
Running: /usr/sbin/vzquota on 777 -r 0 -b 1048676 -B 1153534 -i 200100 -l 220100 -e 0 -n 0 -s 0
Mounting root: /vz/root/777 /vz/private/777
VPS is mounted
Set iptables mask 6079
Running: /usr/sbin/vzquota stat 777 -f
Running: vzquota setlimit 777 -b 1048576 -B 1153434 -i 200000 -l 220000 -e 0 -n 0
Adding IP address(es): 1.1.1.7
Running: /usr/lib/vzctl/scripts/vps-net_add
arp send: unknown iface eth : No such device
vps-net_add WARNING: arp send -c 1 -w 1 -D -e 1.1.1.7 eth FAILED
arp send: unknown iface eth : No such device
vps-net_add WARNING: arp send -c 1 -w 1 -U -i 1.1.1.7 -e 1.1.1.7 eth FAILED
Running VPS script: /etc/sysconfig/vz-scripts/dists/scripts/debian-add_ip.sh
Setting CPU units: 1000
VPS start in progress...
vps:~#

```

Vps starts but when i login i am not able to ping or connect to any host.

Quote:

```

root@vps:~# ifconfig
lo      Link encap:Local Loopback

```



```
inet addr:127.0.0.1 Mask:255.0.0.0
UP LOOPBACK RUNNING MTU:16436 Metric:1
RX packets:3 errors:0 dropped:0 overruns:0 frame:0
TX packets:3 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:0
RX bytes:280 (280.0 b) TX bytes:280 (280.0 b)
```

```
venet0 Link encap:UNSPEC HWaddr 00-00-FF-00-00-00-00-00-00-00-00-00-00-00-00-00
inet addr:127.0.0.1 P-t-P:127.0.0.1 Bcast:0.0.0.0 Mask:255.255.255.255
UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
RX packets:0 errors:0 dropped:0 overruns:0 frame:0
TX packets:18 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:0
RX bytes:0 (0.0 b) TX bytes:882 (882.0 b)
```

```
venet0:0 Link encap:UNSPEC HWaddr 00-00-FF-FF-FF-FF-00-00-00-00-00-00-00-00-00-00
inet addr:1.1.1.7 P-t-P:1.1.1.7 Bcast:0.0.0.0 Mask:255.255.255.255
UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
```

```
root@vps:/# route -N
```

```
Kernel IP routing table
```

Destination	Gateway	Genmask	Flags	Metric	Ref	Use	Iface
191.255.255.1	0.0.0.0	255.255.255.255	UH	0	0	0	venet0
0.0.0.0	191.255.255.1	0.0.0.0	UG	0	0	0	venet0

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Tue, 17 Jan 2006 14:23:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

Quote:Vps starts but when i login i am not able to ping or connect to any host.

First, you should use *real* IP address for you VPS, if you want to be able to access internet from it.

Second, you probably missed setting nameserver inside a VPS.

```
Quote:Running: /usr/lib/vzctl/scripts/vps-net_add
arp send: unknown iface eth : No such device
vps-net_add WARNING: arp send -c 1 -w 1 -D -e 1.1.1.7 eth FAILED
```

Can you please execute the following like and post its output here?
. /usr/lib/vzctl/scripts/vps-functions && vzgetnetdev && echo \$NETDEVICES

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Tue, 17 Jan 2006 15:08:06 GMT

[View Forum Message](#) <> [Reply to Message](#)

Quote:.. /usr/lib/vzctl/scripts/vps-functions && vzgetnetdev && echo \$NETDEVICES
eth

Anyway i try to contact ip on my lan such 1.1.1.1 or 1.1.1.14 for example and after i tried to go out just ping ip so i dont need for this dns settings.

Should i enable nat to share connection ?

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Tue, 17 Jan 2006 15:21:40 GMT
[View Forum Message](#) <> [Reply to Message](#)

For the troubleshooting, can you please post the output of these two commands here?

```
/sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE'
```

```
/sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE' | awk '/^[0-9].*/&&/UP/ {print substr($2, 0, length($2)-1)}'
```

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Tue, 17 Jan 2006 15:24:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

It is not clear whether you should use NAT or not - I do not know your network setup...

Some networking problems are caused by the fact that ppl forgot to enable IP forwarding (net.ipv4.ip_forward = 1). For details, see Quick Install document.

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Tue, 17 Jan 2006 16:03:10 GMT
[View Forum Message](#) <> [Reply to Message](#)

[kir](#) wrote on Tue, 17 January 2006 16:24It is not clear whether you should use NAT or not - I do not know your network setup...

Some networking problems are caused by the fact that ppl forgot to enable IP forwarding (net.ipv4.ip_forward = 1). For details, see Quick Install document.

My network is:

Private LAN: 1.1.1.0/28
Gateway: 1.1.1.14
OpenVZ: 1.1.1.11
VPS 777: 1.1.1.7

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Tue, 17 Jan 2006 16:08:59 GMT
[View Forum Message](#) <> [Reply to Message](#)

So I assume you use NAT somewhere on the gateway...no need to NAT at OpenVZ box then.

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Tue, 17 Jan 2006 19:31:24 GMT
[View Forum Message](#) <> [Reply to Message](#)

```
Quote:vps:~# /sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE'
link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
2: eth0: <BROADCAST,MULTICAST,UP> mtu 1500 qdisc pfifo_fast qlen 1000
link/ether 00:13:8f:0c:16:de brd ff:ff:ff:ff:ff:ff
link/void
vps:~#
vps:~# /sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE' | awk '/^[0-9].*/&&/UP/ {print
substr($2, 0, length($2)-1)}'
eth
```

As you can see list link report eth and not eth0 or something like that.
I dont know if it's a problem or not but i can ping and connect to vps server(1.1.1.11) from vps
guest(1.1.1.7) but i am not able to reach other host on my lan neither reach internet.

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Wed, 18 Jan 2006 14:15:10 GMT
[View Forum Message](#) <> [Reply to Message](#)

MMM from that output you can understand what's wrong with networking ?

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Wed, 18 Jan 2006 14:40:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

Sorry I can not understand your question...

Subject: Re: OpenVZ and Debian
Posted by [dev](#) on Wed, 18 Jan 2006 18:57:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

please, check that
cat /proc/sys/net/ipv4/ip_forward
shows you '1', not 0.

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Wed, 18 Jan 2006 19:43:00 GMT
[View Forum Message](#) <> [Reply to Message](#)

Quote:Adding IP address(es): 1.1.1.8
Running: /usr/lib/vzctl/scripts/vps-net_add
arp send: unknown iface eth : No such device
vps-net_add WARNING: arp send -c 1 -w 1 -D -e 1.1.1.8 eth FAILED
arp send: unknown iface eth : No such device
vps-net_add WARNING: arp send -c 1 -w 1 -U -i 1.1.1.8 -e 1.1.1.8 eth FAILED
Running VPS script: /etc/sysconfig/vz-scripts/dists/scripts/debian-add_ip.sh
Setting CPU units: 1000
VPS start in progress...

That's what i meaning.

After if i login to vps 777 and do ip addr:

Quote:lo Link encap:Local Loopback
 inet addr:127.0.0.1 Mask:255.0.0.0
 UP LOOPBACK RUNNING MTU:16436 Metric:1
 RX packets:2 errors:0 dropped:0 overruns:0 frame:0
 TX packets:2 errors:0 dropped:0 overruns:0 carrier:0
 collisions:0 txqueuelen:0
 RX bytes:168 (168.0 b) TX bytes:168 (168.0 b)

venet0 Link encap:UNSPEC HWaddr 00-00-FF-00-00-00-00-00-00-00-00-00-00-00-00-00-00
 inet addr:127.0.0.1 P-t-P:127.0.0.1 Bcast:0.0.0.0 Mask:255.255.255.255
 UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
 RX packets:0 errors:0 dropped:0 overruns:0 frame:0
 TX packets:2 errors:0 dropped:0 overruns:0 carrier:0
 collisions:0 txqueuelen:0
 RX bytes:0 (0.0 b) TX bytes:98 (98.0 b)

```
venet0:0 Link encap:UNSPEC HWaddr 00-00-FF-FF-FF-FF-00-00-00-00-00-00-00-00-00-00
  inet addr:1.1.1.8 P-t-P:1.1.1.8 Bcast:0.0.0.0 Mask:255.255.255.255
  UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
```

Outside vps guest this is route:

Quote:Kernel IP routing table

Destination	Gateway	Genmask	Flags	Metric	Ref	Use	Iface
1.1.1.8	0.0.0.0	255.255.255.255	UH 0	0	0	0	venet0
1.1.1.0	0.0.0.0	255.255.255.240	U 0	0	0	0	eth0
0.0.0.0	1.1.1.14	0.0.0.0	UG 0	0	0	0	eth0

and this is ip addr output:

Quote:

```
1: lo: <LOOPBACK,UP> mtu 16436 qdisc noqueue
  link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
  inet 127.0.0.1/8 scope host lo
2: eth0: <BROADCAST,MULTICAST,UP> mtu 1500 qdisc pfifo_fast qlen 1000
  link/ether 00:13:8f:0c:16:de brd ff:ff:ff:ff:ff:ff
  inet 1.1.1.11/28 brd 1.1.1.15 scope global eth0
3: venet0: <BROADCAST,POINTOPOINT,NOARP,UP> mtu 1500 qdisc noqueue
  link/void
```

this is sysctl.conf:

Quote:#OPENVZ#

```
# On Hardware Node we generally need
# packet forwarding enabled and proxy arp disabled
net.ipv4.ip_forward = 1
net.ipv4.conf.default.proxy_arp = 0
# Enables source route verification
net.ipv4.conf.all.rp_filter = 1
# Enables the magic-sysrq key
kernel.sysrq = 1
# TCP Explicit Congestion Notification
#net.ipv4.tcp_ecn = 0
# we do not want all our interfaces to send redirects
net.ipv4.conf.default.send_redirects = 1
net.ipv4.conf.all.send_redirects = 0
```

That's all

Where i am wrong ?

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Wed, 18 Jan 2006 20:00:20 GMT
[View Forum Message](#) <> [Reply to Message](#)

Have you actually applied the setting from /etc/sysctl.conf to the running kernel? I.e., what does cat /proc/sys/net/ipv4/ip_forward shows you?

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Wed, 18 Jan 2006 20:27:43 GMT
[View Forum Message](#) <> [Reply to Message](#)

kir wrote on Wed, 18 January 2006 21:00Have you actually applied the setting from /etc/sysctl.conf to the running kernel? I.e., what does cat /proc/sys/net/ipv4/ip_forward shows you?

1

I verify many times.

Subject: Re: OpenVZ and Debian
Posted by [adebisi](#) on Thu, 19 Jan 2006 17:25:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

I mean why when i start vps i receive this error?

```
Quote:Adding IP address(es): 1.1.1.8
Running: /usr/lib/vzctl/scripts/vps-net_add
arp send: unknown iface eth : No such device
vps-net_add WARNING: arp send -c 1 -w 1 -D -e 1.1.1.8 eth FAILED
arp send: unknown iface eth : No such device
vps-net_add WARNING: arp send -c 1 -w 1 -U -i 1.1.1.8 -e 1.1.1.8 eth FAILED
Running VPS script: /etc/sysconfig/vz-scripts/dists/scripts/debian-add_ip.sh
Setting CPU units: 1000
VPS start in progress...
```

Subject: Re: OpenVZ and Debian
Posted by [phlar](#) on Tue, 07 Feb 2006 21:06:09 GMT
[View Forum Message](#) <> [Reply to Message](#)

kir wrote on Tue, 17 January 2006 16:21For the troubleshooting, can you please post the output of these two commands here?

```
/sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE'
```

```
/sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE' | awk '/^[0-9].*/&&/UP/ {print substr($2, 0, length($2)-1)}'
```

The output is eth but it should be eth0.

The solution is to change the awk script that the output is eth0.

```
/sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE' | awk '/^[0-9].*/&&/UP/ {print substr($2, 0, length($2))}'
```

regards
ralph

Subject: Re: OpenVZ and Debian
Posted by [kir](#) on Wed, 08 Feb 2006 07:18:20 GMT
[View Forum Message](#) <> [Reply to Message](#)

phlar,

The problem is if I execute the command you give on my Fedora Core 4 box, it will give me 'eth0:' i.e. with comma which should be stripped off. Looks like debian awk and fedora core awk do not agree on the syntax of substr.

```
[kir@kir ~]$ /sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE' | awk '/^[0-9].*/&&/UP/ {print substr($2, 0, length($2))}'  
eth0:
```

So what I propose is to use this construct:

```
/sbin/ip link list | egrep -v -E 'LOOPBACK|NOARP|SLAVE' | awk '/^[0-9].*/&&/UP/ {print $2}' | tr -d ':'
```

It should work fine everywhere

Subject: Re: OpenVZ and Debian
Posted by [phlar](#) on Wed, 08 Feb 2006 08:41:40 GMT
[View Forum Message](#) <> [Reply to Message](#)

kir wrote on Wed, 08 February 2006 08:18phlar,

The problem is if I execute the command you give on my Fedora Core 4 box, it will give me 'eth0:' i.e. with comma which should be stripped off. Looks like debian awk and fedora core awk do not

agree on the syntax of substr.

Yes, i suspect that the debian-awk starts not at the index zero. The first position is 1 not 0. And it is possible to start at positions lower than zero.

```
openvz:~# echo "test"|awk '{print substr($1,1,4)}'  
test  
openvz:~# echo "test"|awk '{print substr($1,0,4)}'  
tes  
openvz:~# echo "test"|awk '{print substr($1,-1,4)}'  
te
```
