
Subject: *SOLVED* iptables: hashlimit (is a BUG?)
Posted by [smsprog](#) on Tue, 30 Jan 2007 05:59:27 GMT
[View Forum Message](#) <> [Reply to Message](#)

```
[root@openvz ~]# uname -a
Linux openvz 2.6.9-023stab040.1 #1 Tue Jan 16 00:40:25 MSK 2007 i686 i686 i386 GNU/Linux
[root@openvz ~]# iptables -A INPUT -p tcp -m tcp --dport 80 -m state --state NEW -m hashlimit
--hashlimit 1/hour --hashlimit-burst 2 --hashlimit-mode srcip --hashlimit-name HTTP -j ACCEPT
iptables: Unknown error 4294967295
```

Subject: Re: iptables: hashlimit (is a BUG?)
Posted by [dim](#) on Tue, 30 Jan 2007 08:47:57 GMT
[View Forum Message](#) <> [Reply to Message](#)

2.6.9 kernel has no such module.
2.6.18 kernel has this module, but it is disabled in our configs. So, you need to build kernel yourself in order to use it.

Subject: Re: iptables: hashlimit (is a BUG?)
Posted by [lazy](#) on Tue, 15 Sep 2009 10:38:10 GMT
[View Forum Message](#) <> [Reply to Message](#)

kernel rhel5 64.7 64 bit running Debian 5.0 64 bit
ipv6 is not compiled in, kernel config in att
iptables 1.4.2 from debian

any pointers what to do ?

```
strace iptables -I FORWARD -p tcp -s x.x.x.0/23 -m hashlimit --hashlimit-above 2000/second
--hashlimit-mode srcip --hashlimit-srcmask 23 -j DROP
```

```
...
socket(PF_INET, SOCK_RAW, IPPROTO_RAW) = 3
open("/proc/sys/kernel/modprobe", O_RDONLY) = 4
read(4, "/sbin/modprobe\n"..., 1024) = 15
close(4) = 0
clone(child_stack=0, flags=CLONE_CHILD_CLEARTID|CLONE_CHILD_SETTID|SIGCHLD,
child_tidptr=0x2ace19cebe40) = 30911
wait4(-1, [{WIFEXITED(s) && WEXITSTATUS(s) == 0}], 0, NULL) = 30911
--- SIGCHLD (Child exited) @ 0 (0) ---
getsockopt(3, SOL_IP, 0x42 /* IP_??? */, "
hashlimit\0\357\31\316*\0\0\315\17\32\316*\0\0\22\20\20\31\ 316\0 "..., [30]) = 0
close(3) = 0
socket(PF_INET, SOCK_RAW, IPPROTO_RAW) = 3
getsockopt(3, SOL_IP, 0x42 /* IP_??? */, 0x7fff11027ee0, 0x7fff11027f0c) = -1
EPROTONOSUPPORT (Protocol not supported)
```

```
close(3) = 0
open("/lib/xtables/libxt_tcp.so", O_RDONLY) = 3
read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0`\f\0\0\0\0\0\0@ "..., 832) = 832
fstat(3, {st_mode=S_IFREG|0644, st_size=11408, ...}) = 0
mmap(NULL, 2106704, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0) =
0x2ace1a0fd000
mprotect(0x2ace1a0ff000, 2097152, PROT_NONE) = 0
mmap(0x2ace1a2ff000, 4096, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x2000) = 0x2ace1a2ff000
close(3) = 0
write(2, "iptables v1.4.2: "..., 17iptables v1.4.2: ) = 17
write(2, "Unknown arg `(null)'"..., 20Unknown arg `(null)') = 20
write(2, "\n"..., 1
) = 1
write(2, "Try `iptables -h' or 'iptables --'...", 61Try `iptables -h' or 'iptables --help' for more
information.
) = 61
exit_group(2)
```

File Attachments

1) [cfg](#), downloaded 857 times
