

---

Posted by [HappyAlex](#) on Sun, 04 Mar 2007 10:23:39 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

```
ifconfig venet0:1 10.10.10.3
```

Quote:

```
vzctl set 50 --netif_add eth0,00:12:34:56:78:9A,veth101.0,00:12:34:56:78:9B --save  
ifconfig veth101.0 0  
echo 1 > /proc/sys/net/ipv4/conf/veth101.0/forwarding  
echo 1 > /proc/sys/net/ipv4/conf/veth101.0/proxy_arp  
echo 1 > /proc/sys/net/ipv4/conf/eth0/forwarding  
echo 1 > /proc/sys/net/ipv4/conf/eth0/proxy_arp
```

```
vzctl enter 50
```

Quote:

```
/sbin/ifconfig eth0 0  
/sbin/ip addr add 10.10.10.2 dev eth0
```

```
ip route add 10.10.10.2 dev veth101.0
```

```
[root@hosting2 ~]# ping 10.10.10.2  
PING 10.10.10.2 (10.10.10.2) 56(84) bytes of data.  
From 85.115.xxx.xx icmp_seq=1 Destination Host Unreachable  
From 85.115.xxx.xx icmp_seq=2 Destination Host Unreachable
```

Quote:

Kernel IP routing table

Destination	Gateway	Genmask	Flags	MSS	Window	irtt	Iface
85.115.xxx.xY	0.0.0.0	255.255.255.255	UH	0 0	0	0	venet0
10.10.10.2	0.0.0.0	255.255.255.255	UH	0 0	0	0	veth101.0
85.115.xxx.xZ	0.0.0.0	255.255.255.255	UH	0 0	0	0	venet0
85.115.193.48	0.0.0.0	255.255.255.240	U	0 0	0	0	eth0
0.0.0.0	85.115.xx.xx	0.0.0.0	UG	0 0	0	0	eth0

```
/sbin/ip route add default dev eth0
```

---

---

Posted by [Andrey Mirkin](#) on Mon, 05 Mar 2007 18:01:24 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---