
Subject: Same as Physical PC

Posted by [Jun OKAJIMA](#) on Sun, 27 May 2007 15:52:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

Cant I make a very same env as real one to VE?

It has just very same /dev as real Linux, and also same /proc as real Linux.

I know it is no meaning for server virtualization, which is the purpose of OpenVZ, because it loses all of security. But it is convenient for development, testing, or such purposes.

I tried like below, in the OpenVZ live CD.

```
# mount --bind /dev /var/lib/vz/private/101/dev
# mount --proc /proc /var/lib/vz/private/101/proc
# vzctl start 101
```

But, it ended up with below.

Starting VE ...

vzquota : (error) Quota on syscall for 101: Device or resource busy

vzquota on failed [3]

To make the matters worse, something like this failed in same way.

I am sure that this must be possible, because the below URL did it.

http://forum.openvz.org/index.php?t=msg&goto=13000&# msg_13000

But I failed. Why?. The env I used is the live CD which downloaded from your site.

Any help?

```
# mkdir /aaa
# mount -t tmpfs none /aaa
# echo "hello world" >/aaa/bbb
# mount --bind /aaa /var/lib/vz/private/101/tmp
# vzctl start 101
( and "vzquota" error happened. WHY??? and what I should do?)
```

Note: I know that adding "DEVICES=" lines to a config file is necessary to access actual physical devices.

--- Okajima, Jun. Tokyo, Japan.

Subject: Re: Same as Physical PC

Posted by [Vasily Tarasov](#) on Mon, 28 May 2007 10:48:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

It is a usual mistake. As described in the post you referenced to:

<snip>

You're mounting to `__private__` directory, that is not right: in order to see information on external mounted filesystem in VE, you should start VE and then mount to `__root__` directory:

```
mount --bind /mnt/testhome /vz/root/102/home/
```

</snip>

Otherwise quota will complain ;)

HTH,
Vasily

On Mon, 2007-05-28 at 00:52 +0900, Jun OKAJIMA wrote:

>

> Cant I make a very same env as real one to VE?

> It has just very same /dev as real Linux, and also same /proc as real Linux.

> I know it is no meaning for server virtualization, which is the purpose of OpenVZ, because it loses all of security. But it is convenient for development, testing, or such purposes.

>

> -----

>

> I tried like below, in the OpenVZ live CD.

>

```
> # mount --bind /dev /var/lib/vz/private/101/dev
```

```
> # mount --proc /proc /var/lib/vz/private/101/proc
```

```
> # vzctl start 101
```

>

> But, it ended up with below.

>

> -----

> Starting VE ...

```
> vzquota : (error) Quota on syscall for 101: Device or resource busy
```

```
> vzquota on failed [3]
```

> -----

>

> To make the matters worse, something like this failed in same way.

> I am sure that this must be possible, because the below URL did it.

> http://forum.openvz.org/index.php?t=msg&goto=13000&# msg_13000

> But I failed. Why?. The env I used is the live CD which downloaded from your site.

```
> Any help?
>
> # mkdir /aaa
> # mount -t tmpfs none /aaa
> # echo "hello world" >/aaa/bbb
> # mount --bind /aaa /var/lib/vz/private/101/tmp
> # vzctl start 101
> ( and "vzquota" error happened. WHY??? and what I should do?)
>
>
>
> Note: I know that adding "DEVICES=" lines to a config file is necessary to access
>   actual physical devices.
>
>
>           --- Okajima, Jun. Tokyo, Japan.
>
>
>
```
