

---

**Subject:** One NIC, Multiple Gateways

**Posted by** [blyoung](#) **on Thu, 09 Feb 2006 08:16:14 GMT**

[View Forum Message](#) <> [Reply to Message](#)

---

I have two gateways and one NIC. I want to be able to send some of the VPS to one gateway and some to another. I have been trying to accomplish this by altering the routing within the a particular VPS without success. The venet0 structure is different from what I am used to and I can't seem to find a way around or through the 191.255.255.1 interface.

Further illustration:

Host: 192.168.0.130, default route: 192.168.0.1

VPS101: 192.168.0.131

VPS102: 192.168.0.132

I want to make VPS102 route through 192.168.0.254 instead of 192.168.0.1 (the default configuration).

Am I going about this the wrong way? Is it even doable?

Thanks,

blyoung

---

---

**Subject:** Re: One NIC, Multiple Gateways

**Posted by** [dev](#) **on Thu, 16 Feb 2006 12:34:08 GMT**

[View Forum Message](#) <> [Reply to Message](#)

---

sure it is doable! but it has nothing to do with openvz actually.

You just need to setup src-based routing rules in host system. e.g.

```
# /sbin/ip rule add from $IP table $TBL  
# /sbin/ip route add default dev eth0 via $GW table $TBL
```

where \$IP is ip address which should use non-default GW.

\$GW is gateway for this IP addr

\$TBL - any free table number, I use numbers from 6 to ...

every next non-std GW will require another table number

read `man ip` for routing rules details.

---

---

**Subject:** Re: One NIC, Multiple Gateways

**Posted by** [blyoung](#) **on Thu, 16 Feb 2006 16:08:01 GMT**

[View Forum Message](#) <> [Reply to Message](#)

---

Thanks,

The documentation leads you to believe you can do it inside the VPS itself. With the virtual interface, I simply didn't think it was possible.

-Bryan

---

---

Subject: Re: One NIC, Multiple Gateways  
Posted by [kir](#) on Thu, 20 Jul 2006 17:43:53 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This thread is summarised on [wiki:Source based routing](#).

---

---

Subject: Re: One NIC, Multiple Gateways  
Posted by [mangust](#) on Thu, 24 Apr 2008 13:29:22 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

i have problem going the way in Wiki.  
I don't want to assign any IP address on external interface. I want to use all public addresses for VEs. And manage HN from private. I have:

```
[root@trinity ~]# ifconfig -a
eth0    Link encap:Ethernet HWaddr 00:1E:4F:2D:F1:63
        inet addr:192.168.1.52 Bcast:192.168.1.255 Mask:255.255.255.0
        inet6 addr: fe80::21e:4fff:fe2d:f163/64 Scope:Link
              UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
              RX packets:289 errors:0 dropped:0 overruns:0 frame:0
              TX packets:178 errors:0 dropped:0 overruns:0 carrier:0
              collisions:0 txqueuelen:1000
              RX bytes:254155 (248.1 KiB) TX bytes:33567 (32.7 KiB)
              Interrupt:169 Memory:f8000000-f8012100

eth1    Link encap:Ethernet HWaddr 00:1E:4F:2D:F1:65
        BROADCAST MULTICAST MTU:1500 Metric:1
        RX packets:0 errors:0 dropped:0 overruns:0 frame:0
        TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
        collisions:0 txqueuelen:1000
        RX bytes:0 (0.0 b) TX bytes:0 (0.0 b)
        Interrupt:169 Memory:f4000000-f4012100

lo     Link encap:Local Loopback
        inet addr:127.0.0.1 Mask:255.0.0.0
        inet6 addr: ::1/128 Scope:Host
              UP LOOPBACK RUNNING MTU:16436 Metric:1
              RX packets:3 errors:0 dropped:0 overruns:0 frame:0
              TX packets:3 errors:0 dropped:0 overruns:0 carrier:0
              collisions:0 txqueuelen:0
```

```

RX bytes:299 (299.0 b) TX bytes:299 (299.0 b)

sit0    Link encap:IPv6-in-IPv4
        NOARP MTU:1480 Metric:1
        RX packets:0 errors:0 dropped:0 overruns:0 frame:0
        TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
        collisions:0 txqueuelen:0
        RX bytes:0 (0.0 b) TX bytes:0 (0.0 b)

venet0  Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00
        UP BROADCAST POINTOPOINT RUNNING NOARP MTU:1500 Metric:1
        RX packets:347 errors:0 dropped:0 overruns:0 frame:0
        TX packets:202 errors:0 dropped:0 overruns:0 carrier:0
        collisions:0 txqueuelen:0
        RX bytes:46953 (45.8 KiB) TX bytes:44352 (43.3 KiB)
[root@trinity ~]# /sbin/ip rule add from 62.15.232.176/29 table 115
[root@trinity ~]# /sbin/ip route add default dev eth1 via 62.15.232.182 table 115
RTNETLINK answers: Network is unreachable
[root@trinity ~]# /sbin/ip route add 62.15.232.176/29 dev eth1
RTNETLINK answers: No such device
[root@trinity ~]# ifconfig eth1
eth1    Link encap:Ethernet HWaddr 00:1E:4F:2D:F1:65
        BROADCAST MULTICAST MTU:1500 Metric:1
        RX packets:0 errors:0 dropped:0 overruns:0 frame:0
        TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
        collisions:0 txqueuelen:1000
        RX bytes:0 (0.0 b) TX bytes:0 (0.0 b)
        Interrupt:169 Memory:f4000000-f4012100

[root@trinity ~]# ifconfig eth1 up
[root@trinity ~]# /sbin/ip route add 62.15.232.176/29 dev eth1
RTNETLINK answers: No such device
[root@trinity ~]# ifconfig eth1 inet 1.2.3.4
[root@trinity ~]# /sbin/ip route add 62.15.232.176/29 dev eth1
[root@trinity ~]# /sbin/ip route add default dev eth1 via 62.15.232.182 table 115
[root@trinity ~]# vzlist -a
      CTID   NPROC STATUS   IP_ADDR      HOSTNAME
        1     86 running  192.168.193.12 ServiceCT
      115      5 running  62.15.232.178 178.232.15.62.static.jazztel.es
[root@trinity ~]# ping 62.15.232.178
PING 62.15.232.178 (62.15.232.178) 56(84) bytes of data.
64 bytes from 62.15.232.178: icmp_seq=1 ttl=64 time=0.041 ms

```

but still can't ping from outside  
 i did something wrong? and why ip tell me story about "No such device"? i don't want to assign any address.

thanks

---