
Subject: Tweak /proc/ipmi removal

Posted by [Alexey Dobriyan](#) on Fri, 03 Aug 2007 13:30:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

Driver does

```
proc_mkdir("ipmi", NULL);
```

but

```
remove_proc_entry(proc_ipmi_root->name, &proc_root);
```

This is OK and working if only slightly inconsistent.

Also changing proc_root to NULL will help OpenVZ which has multiple proc roots and, as we now know, requires matching parents in such cases.

Please, apply.

Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>

```
drivers/char/ipmi/ipmi_msghandler.c | 2 +-  
1 file changed, 1 insertion(+), 1 deletion(-)
```

```
--- a/drivers/char/ipmi/ipmi_msghandler.c
```

```
+++ b/drivers/char/ipmi/ipmi_msghandler.c
```

```
@@ -4136,7 +4136,7 @@ static __exit void cleanup_ipmi(void)  
    del_timer_sync(&ipmi_timer);
```

```
#ifdef CONFIG_PROC_FS
```

```
- remove_proc_entry(proc_ipmi_root->name, &proc_root);
```

```
+ remove_proc_entry(proc_ipmi_root->name, NULL);
```

```
#endif /* CONFIG_PROC_FS */
```

```
driver_unregister(&ipmidriver);
```
