

---

Posted by [Hibin](#) on Sat, 01 Sep 2007 18:48:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Quote:ping N.N.N.N  
connect: No buffer space available

---

---

Posted by [vaverin](#) on Mon, 03 Sep 2007 09:22:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

[https://wiki.openvz.org/Stracing\\_a\\_program](https://wiki.openvz.org/Stracing_a_program)

---

---

Posted by [Hibin](#) on Mon, 03 Sep 2007 11:02:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

```
7933 execve("/bin/ping", ["ping", "N.N.N.N"], [/* 17 vars */]) = 0
7933 uname({sys="Linux", node="ve106.domain.ru", ...}) = 0
7933 brk(0) = 0x555555670000
7933 mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS,
-1, 0) = 0x2ac3ebe70000
7933 access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
7933 open("/etc/ld.so.cache", O_RDONLY) = 3
7933 fstat(3, {st_mode=S_IFREG|0644, st_size=21020, ...}) = 0
7933 mmap(NULL, 21020, PROT_READ, MAP_PRIVATE, 3, 0) = 0x2ac3ebe71000
```

```

7933 close(3) = 0
7933 open("/lib64/libresolv.so.2", O_RDONLY) = 3
7933 read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\2406\0\0"..., 832) = 832
7933 fstat(3, {st_mode=S_IFREG|0755, st_size=90672, ...}) = 0
7933 mmap(NULL, 1133256, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE,
3, 0) = 0x2ac3ebf71000
7933 mprotect(0x2ac3ebf82000, 1063624, PROT_NONE) = 0
7933 mmap(0x2ac3ec082000, 8192, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x11000) = 0x2ac3ec082000
7933 mmap(0x2ac3ec084000, 6856, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x2ac3ec084000
7933 close(3) = 0
7933 open("/lib64/tls/libc.so.6", O_RDONLY) = 3
7933 read(3, "\177ELF\2\1\1\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\240\304"..., 832) = 832
7933 fstat(3, {st_mode=S_IFREG|0755, st_size=1617520, ...}) = 0
7933 mmap(NULL, 2314184, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE,
3, 0) = 0x2ac3ec086000
7933 mprotect(0x2ac3ec1b2000, 1085384, PROT_NONE) = 0
7933 mmap(0x2ac3ec2b2000, 20480, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_DENYWRITE, 3, 0x12c000) = 0x2ac3ec2b2000
7933 mmap(0x2ac3ec2b7000, 16328, PROT_READ|PROT_WRITE,
MAP_PRIVATE|MAP_FIXED|MAP_ANONYMOUS, -1, 0) = 0x2ac3ec2b7000
7933 close(3) = 0
7933 mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS,
-1, 0) = 0x2ac3ec2bb000
7933 mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS,
-1, 0) = 0x2ac3ec2bc000
7933 mprotect(0x2ac3ec2b2000, 12288, PROT_READ) = 0
7933 mprotect(0x2ac3ec082000, 4096, PROT_READ) = 0
7933 mprotect(0x2ac3ebf6f000, 4096, PROT_READ) = 0
7933 arch_prctl(ARCH_SET_FS, 0x2ac3ec2bbe20) = 0
7933 munmap(0x2ac3ebe71000, 21020) = 0
7933 socket(PF_INET, SOCK_RAW, IPPROTO_ICMP) = 3
7933 getuid() = 0
7933 setuid(0) = 0
7933 socket(PF_INET, SOCK_DGRAM, IPPROTO_IP) = 4
7933 connect(4, {sa_family=AF_INET, sin_port=htons(1025), sin_addr=inet_addr("N.N.N.N")},
16) = -1 ENOBUFS (No buffer space available)
7933 dup(2) = 5
7933fcntl(5, F_GETFL) = 0x8002 (flags O_RDWR|O_LARGEFILE)
7933 brk(0) = 0x555555670000
7933 brk(0x555555691000) = 0x555555691000
7933 fstat(5, {st_mode=S_IFCHR|0600, st_rdev=makedev(136, 0), ...}) = 0
7933 mmap(NULL, 4096, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS,
-1, 0) = 0x2ac3ebe71000
7933 lseek(5, 0, SEEK_CUR) = -1 ESPIPE (Illegal seek)
7933 write(5, "connect: No buffer space availab"..., 35) = 35
7933 close(5) = 0

```

7933 munmap(0x2ac3ebe71000, 4096) = 0  
7933 exit\_group(2) = ?

---

---

Posted by [vaverin](#) on Tue, 04 Sep 2007 06:36:49 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

<http://nice3z.myfinejob.com/node/3>

[http://www.ibm.com/developerworks/ru/library/es-clusterserie\\_spt2/](http://www.ibm.com/developerworks/ru/library/es-clusterserie_spt2/)

---

---

Posted by [Hibin](#) on Tue, 04 Sep 2007 13:20:50 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---