

---

Subject: [PATCH 4/4] Use task\_pgrp() in autofs/autofs4  
Posted by [Sukadev Bhattiprolu](#) on Thu, 22 Feb 2007 23:33:23 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>  
Subject: [PATCH 4/4] Use task\_pgrp() in autofs/autofs4

Replace process\_group(tsk) with pid\_nr(task\_pgrp(tsk)) in autofs and autofs4.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>  
Cc: Cedric Le Goater <cclg@fr.ibm.com>  
Cc: Dave Hansen <haveblue@us.ibm.com>  
Cc: Serge Hallyn <serue@us.ibm.com>  
Cc: containers@lists.osdl.org

---

```
fs/autofs/inode.c |  2 ++
fs/autofs/root.c |  4 +---
fs/autofs4/inode.c |  2 ++
fs/autofs4/root.c |  4 +---
4 files changed, 6 insertions(+), 6 deletions(-)
```

Index: lx26-20-mm1/fs/autofs/root.c

```
=====
--- lx26-20-mm1.orig/fs/autofs/root.c 2007-02-16 15:44:24.000000000 -0800
+++ lx26-20-mm1/fs/autofs/root.c 2007-02-16 15:45:17.000000000 -0800
@@ @ -215,7 +215,7 @@ static struct dentry *autofs_root_lookup
    oz_mode = autofs_oz_mode(sbi);
    DPRINTK("autofs_lookup: pid = %u, pgrp = %u, catatonic = %d, "
           "oz_mode = %d\n", pid_nr(task_pid(current)),
-      process_group(current), sbi->catatonic,
+      pid_nr(task_pgrp(current)), sbi->catatonic,
           oz_mode);

/*
@@ @ -536,7 +536,7 @@ static int autofs_root_ioctl(struct inode
    struct autofs_sb_info *sbi = autofs_sbi(inode->i_sb);
    void __user *argp = (void __user *)arg;

- DPRINTK(("autofs_ioctl: cmd = 0x%08x, arg = 0x%08lx, sbi = %p, pgrp =
%u\n",cmd,arg,sbi,process_group(current)));
+ DPRINTK(("autofs_ioctl: cmd = 0x%08x, arg = 0x%08lx, sbi = %p, pgrp =
%u\n",cmd,arg,sbi,pid_nr(task_pgrp(current))));
```

```
    if (_IOC_TYPE(cmd) != _IOC_TYPE(AUTOFS_IOC_FIRST) ||
        _IOC_NR(cmd) - _IOC_NR(AUTOFS_IOC_FIRST) >= AUTOFS_IOC_COUNT)
```

Index: lx26-20-mm1/fs/autofs4/root.c

```

--- lx26-20-mm1.orig/fs/autofs4/root.c 2007-02-16 15:44:30.000000000 -0800
+++ lx26-20-mm1/fs/autofs4/root.c 2007-02-16 15:45:17.000000000 -0800
@@ @ -583,7 +583,7 @@ static struct dentry *autofs4_lookup(str
oz_mode = autofs4_oz_mode(sbi);

DPRINTK("pid = %u, pgrp = %u, catatonic = %d, oz_mode = %d",
- pid_nr(task_pid(current)), process_group(current),
+ pid_nr(task_pid(current)), pid_nr(task_pgrp(current)),
sbi->catatonic, oz_mode);

unhashed = autofs4_lookup_unhashed(sbi, dentry->d_parent, &dentry->d_name);
@@ @ -975,7 +975,7 @@ static int autofs4_root_ioctl(struct ino
void __user *p = (void __user *)arg;

DPRINTK("cmd = 0x%08x, arg = 0x%08lx, sbi = %p, pgrp = %u",
- cmd,arg,sbi,process_group(current));
+ cmd,arg,sbi,pid_nr(task_pgrp(current)));

if (_IOC_TYPE(cmd) != _IOC_TYPE(AUTOFS_IOC_FIRST) ||
    _IOC_NR(cmd) - _IOC_NR(AUTOFS_IOC_FIRST) >= AUTOFS_IOC_COUNT)
Index: lx26-20-mm1/fs/autofs/inode.c
=====
--- lx26-20-mm1.orig/fs/autofs/inode.c 2007-02-16 15:44:24.000000000 -0800
+++ lx26-20-mm1/fs/autofs/inode.c 2007-02-16 15:45:17.000000000 -0800
@@ @ -80,7 +80,7 @@ static int parse_options(char *options,
*uid = current->uid;
*gid = current->gid;
- *pgrp = process_group(current);
+ *pgrp = pid_nr(task_pgrp(current));

*minproto = *maxproto = AUTOFS_PROTO_VERSION;

Index: lx26-20-mm1/fs/autofs4/inode.c
=====
--- lx26-20-mm1.orig/fs/autofs4/inode.c 2007-02-16 15:44:30.000000000 -0800
+++ lx26-20-mm1/fs/autofs4/inode.c 2007-02-16 15:45:17.000000000 -0800
@@ @ -229,7 +229,7 @@ static int parse_options(char *options,
*uid = current->uid;
*gid = current->gid;
- *pgrp = process_group(current);
+ *pgrp = pid_nr(task_pgrp(current));

*minproto = AUTOFS_MIN_PROTO_VERSION;
*maxproto = AUTOFS_MAX_PROTO_VERSION;

```

---

Containers mailing list

Containers@lists.osdl.org  
<https://lists.osdl.org/mailman/listinfo/containers>

---