

---

Subject: [PATCH 5/5] Use task\_pgrp() task\_session() in copy\_process()  
Posted by [Sukadev Bhattiprolu](#) on Tue, 13 Mar 2007 04:45:46 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>  
Subject: [PATCH 5/5] Use task\_pgrp() task\_session() in copy\_process().

Use task\_pgrp() and task\_session() in copy\_process(), and  
avoid find\_pid() call when attaching the task to its process  
group and session.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>  
Cc: Cedric Le Goater <clg@fr.ibm.com>  
Cc: Dave Hansen <haveblue@us.ibm.com>  
Cc: Serge Hallyn <serue@us.ibm.com>  
Cc: containers@lists.osdl.org  
Acked-by: Eric W. Biederman <ebiederm@xmission.com>

---  
kernel/fork.c | 9 +++-----  
1 file changed, 3 insertions(+), 6 deletions(-)

Index: lx26-21-rc3-mm2/kernel/fork.c

```
=====
--- lx26-21-rc3-mm2.orig/kernel/fork.c 2007-03-12 17:18:03.000000000 -0700
+++ lx26-21-rc3-mm2/kernel/fork.c 2007-03-12 17:18:11.000000000 -0700
@@ -1252,14 +1252,11 @@ static struct task_struct *copy_process(
    tracehook_init_task(p);

    if (thread_group_leader(p)) {
- pid_t pgid = process_group(current);
- pid_t sid = process_session(current);
-
    p->signal->tty = current->signal->tty;
- p->signal->pgrp = pgid;
+ p->signal->pgrp = process_group(current);
    set_signal_session(p->signal, process_session(current));
- attach_pid(p, PIDTYPE_PGID, find_pid(pgid));
- attach_pid(p, PIDTYPE_SID, find_pid(sid));
+ attach_pid(p, PIDTYPE_PGID, task_pgrp(current));
+ attach_pid(p, PIDTYPE_SID, task_session(current));

    list_add_tail_rcu(&p->tasks, &init_task.tasks);
    __get_cpu_var(process_counts)++;
=====
```

---

Containers mailing list  
Containers@lists.osdl.org  
<https://lists.osdl.org/mailman/listinfo/containers>

---