Subject: [PATCH 4/5] Define is_global_init() and is_container_init()
Posted by Sukadev Bhattiprolu on Sun, 15 Jul 2007 04:58:07 GMT
View Forum Message <> Reply to Message

Subject: [PATCH 4/5] Define is_global_init() and is_container_init().

From: Serge E. Hallyn <serue@us.ibm.com>

is_init() is an ambiguous name for the pid==1 check. Split it into
is_global_init() and is_container_init().

A container init has it's tsk->pid == 1.

A global init also has it's tsk->pid == 1 and it's active pid namespace
is the init_pid_ns. But rather than check the active pid namespace,
compare the task structure with 'init_pid_ns.child_reaper', which is
initialized during boot to the /sbin/init process and never changes.

Changelog:

2.6.22-rc4-mm2-pidns1:
- Use 'init_pid_ns.child_reaper' to determine if a given task is the
  global init (/sbin/init) process. This would improve performance
  and remove dependence on the task_pid().

2.6.21-mm2-pidns2:

- [Sukadev Bhattiprolu] Changed is_container_init() calls in {powerpc,
  ppc,avr32}/traps.c for the _exception() call to is_global_init().
  This way, we kill only the container if the container's init has a
  bug rather than force a kernel panic.

Signed-off-by: Serge E. Hallyn <serue@us.ibm.com>
Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Acked-by: Pavel Emelianov <xemul@openvz.org>

Cc: Eric W. Biederman <ebiederm@xmission.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Herbert Poetzel <herbert@13thfloor.at>
---
arch/alpha/mm/fault.c | 2 +-
arch/arm/mm/fault.c | 2 +-
arch/arm26/mm/fault.c | 2 +-
arch/avr32/kernel/traps.c | 2 +-
arch/avr32/mm/fault.c | 6 +++---
arch/i386/lib/usercopy.c | 2 +-

```
 arch/i386/mm/fault.c                |    2 +-
 arch/ia64/mm/fault.c                |    2 +-
 arch/m68k/mm/fault.c                |    2 +-
 arch/mips/mm/fault.c                |    2 +-
 arch/powerpc/kernel/traps.c         |    2 +-
 arch/powerpc/mm/fault.c             |    2 +-
 arch/powerpc/platforms/pseries/ras.c |    2 +-
 arch/ppc/kernel/traps.c             |    2 +-
 arch/ppc/mm/fault.c                 |    2 +-
 arch/s390/lib/uaccess_pt.c          |    2 +-
 arch/s390/mm/fault.c                |    2 +-
 arch/sh/mm/fault.c                  |    2 +-
 arch/sh64/mm/fault.c                |    6 ++++---
 arch/um/kernel/trap.c               |    2 +-
 arch/x86_64/mm/fault.c              |    2 +-
 arch/xtensa/mm/fault.c              |    2 +-
 drivers/char/sysrq.c                |    2 +-
 include/linux/sched.h               |   12 ++++++++++--
 kernel/capability.c                 |    3 ++-
 kernel/exit.c                       |    2 +-
 kernel/kexec.c                      |    2 +-
 kernel/pid.c                        |    7 +++++++
 kernel/signal.c                     |    2 +-
 kernel/sysctl.c                     |    2 +-
 mm/oom_kill.c                       |    4 ++--
 security/commoncap.c                |    3 ++-
 32 files changed, 54 insertions(+), 37 deletions(-)

Index: lx26-22-rc6-mm1/include/linux/sched.h
===================================================================
--- lx26-22-rc6-mm1.orig/include/linux/sched.h 2007-07-13 13:06:52.000000000 -0700
+++ lx26-22-rc6-mm1/include/linux/sched.h 2007-07-13 13:12:18.000000000 -0700
@@ -1219,12 +1219,20 @@ static inline int pid_alive(struct task_
 }

 /**
- * is_init - check if a task structure is init
+ * is_global_init - check if a task structure is init
  * @tsk: Task structure to be checked.
  *
  * Check if a task structure is the first user space task the kernel created.
+ *
+ * TODO: We should inline this function after some cleanups in pid_namespace.h
+ */
+extern int is_global_init(struct task_struct *tsk);
+
+/*
+ * is_container_init:
```

```
+ * check whether in the task is init in it's own pid namespace.
  */
-static inline int is_init(struct task_struct *tsk)
+static inline int is_container_init(struct task_struct *tsk)
 {
  return tsk->pid == 1;
 }
Index: lx26-22-rc6-mm1/kernel/pid.c
===================================================================
--- lx26-22-rc6-mm1.orig/kernel/pid.c 2007-07-13 13:08:42.000000000 -0700
+++ lx26-22-rc6-mm1/kernel/pid.c 2007-07-13 13:12:18.000000000 -0700
@@ -69,6 +69,13 @@ struct pid_namespace init_pid_ns = {
  .last_pid = 0,
  .child_reaper = &init_task
 };
+EXPORT_SYMBOL(init_pid_ns);
+
+int is_global_init(struct task_struct *tsk)
+{
+ return tsk == init_pid_ns.child_reaper;
+}
+EXPORT_SYMBOL(is_global_init);

 /*
  * Note: disable interrupts while the pidmap_lock is held as an
Index: lx26-22-rc6-mm1/arch/alpha/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/alpha/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/alpha/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -192,7 +192,7 @@ do_page_fault(unsigned long address, uns
  /* We ran out of memory, or some other thing happened to us that
     made us unable to handle the page fault gracefully.  */
  out_of_memory:
- if (is_init(current)) {
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/arm/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/arm/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/arm/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -197,7 +197,7 @@ survive:
   return fault;
  }

- if (!is_init(tsk))
+ if (!is_global_init(tsk))
```

```
   goto out;

  /*
Index: lx26-22-rc6-mm1/arch/arm26/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/arm26/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/arm26/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -185,7 +185,7 @@ survive:
  }

  fault = -3; /* out of memory */
- if (!is_init(tsk))
+ if (!is_global_init(tsk))
   goto out;

  /*
Index: lx26-22-rc6-mm1/arch/i386/lib/usercopy.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/i386/lib/usercopy.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/i386/lib/usercopy.c 2007-07-13 13:12:18.000000000 -0700
@@ -748,7 +748,7 @@ survive:
    retval = get_user_pages(current, current->mm,
      (unsigned long )to, 1, 1, 0, &pg, NULL);

-   if (retval == -ENOMEM && is_init(current)) {
+   if (retval == -ENOMEM && is_global_init(current)) {
     up_read(&current->mm->mmap_sem);
     congestion_wait(WRITE, HZ/50);
     goto survive;
Index: lx26-22-rc6-mm1/arch/i386/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/i386/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/i386/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -595,7 +595,7 @@ no_context:
  */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(tsk)) {
+ if (is_global_init(tsk)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/ia64/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/ia64/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/ia64/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -270,7 +270,7 @@ ia64_do_page_fault (unsigned long addres
```

```
   out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/m68k/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/m68k/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/m68k/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -181,7 +181,7 @@ good_area:
  */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/mips/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/mips/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/mips/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -174,7 +174,7 @@ no_context:
  */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(tsk)) {
+ if (is_global_init(tsk)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/powerpc/kernel/traps.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/powerpc/kernel/traps.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/powerpc/kernel/traps.c 2007-07-13 13:12:18.000000000 -0700
@@ -191,7 +191,7 @@ void _exception(int signr, struct pt_reg
   * generate the same exception over and over again and we get
   * nowhere.  Better to kill it and let the kernel panic.
   */
- if (is_init(current)) {
+ if (is_global_init(current)) {
   __sighandler_t handler;

   spin_lock_irq(&current->sighand->siglock);
Index: lx26-22-rc6-mm1/arch/powerpc/mm/fault.c
===================================================================
```

```
--- lx26-22-rc6-mm1.orig/arch/powerpc/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/powerpc/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -374,7 +374,7 @@ bad_area_nosemaphore:
  */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/powerpc/platforms/pseries/ras.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/powerpc/platforms/pseries/ras.c 2007-07-13 13:05:38.000000000
-0700
+++ lx26-22-rc6-mm1/arch/powerpc/platforms/pseries/ras.c 2007-07-13 13:12:18.000000000
-0700
@@ -332,7 +332,7 @@ static int recover_mce(struct pt_regs *r
      err->disposition == RTAS_DISP_NOT_RECOVERED &&
      err->target == RTAS_TARGET_MEMORY &&
      err->type == RTAS_TYPE_ECC_UNCORR &&
-     !(current->pid == 0 || is_init(current))) {
+     !(current->pid == 0 || is_global_init(current))) {
   /* Kill off a user process with an ECC error */
   printk(KERN_ERR "MCE: uncorrectable ecc error for pid %d\n",
          current->pid);
Index: lx26-22-rc6-mm1/arch/ppc/kernel/traps.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/ppc/kernel/traps.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/ppc/kernel/traps.c 2007-07-13 13:12:18.000000000 -0700
@@ -121,7 +121,7 @@ void _exception(int signr, struct pt_reg
   * generate the same exception over and over again and we get
   * nowhere.  Better to kill it and let the kernel panic.
   */
- if (is_init(current)) {
+ if (is_global_init(current)) {
   __sighandler_t handler;

   spin_lock_irq(&current->sighand->siglock);
Index: lx26-22-rc6-mm1/arch/ppc/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/ppc/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/ppc/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -292,7 +292,7 @@ bad_area:
  */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
```

```
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/s390/lib/uaccess_pt.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/s390/lib/uaccess_pt.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/s390/lib/uaccess_pt.c 2007-07-13 13:12:18.000000000 -0700
@@ -65,7 +65,7 @@ out:

 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/s390/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/s390/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/s390/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -211,7 +211,7 @@ static int do_out_of_memory(struct pt_re
  struct mm_struct *mm = tsk->mm;

  up_read(&mm->mmap_sem);
- if (is_init(tsk)) {
+ if (is_global_init(tsk)) {
   yield();
   down_read(&mm->mmap_sem);
   return 1;
Index: lx26-22-rc6-mm1/arch/sh/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/sh/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/sh/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -191,7 +191,7 @@ no_context:
  */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/sh64/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/sh64/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/sh64/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -276,7 +276,7 @@ bad_area:
```

```
    show_regs(regs);
 #endif
   }
-  if (is_init(tsk)) {
+  if (is_global_init(tsk)) {
    panic("INIT had user mode bad_area\n");
   }
   tsk->thread.address = address;
@@ -318,14 +318,14 @@ no_context:
  * us unable to handle the page fault gracefully.
  */
 out_of_memory:
- if (is_init(current)) {
+ if (is_global_init(current)) {
   panic("INIT out of memory\n");
   yield();
   goto survive;
  }
  printk("fault:Out of memory\n");
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
Index: lx26-22-rc6-mm1/arch/um/kernel/trap.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/um/kernel/trap.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/um/kernel/trap.c 2007-07-13 13:12:18.000000000 -0700
@@ -120,7 +120,7 @@ out_nosemaphore:
  * us unable to handle the page fault gracefully.
  */
 out_of_memory:
- if (is_init(current)) {
+ if (is_global_init(current)) {
   up_read(&mm->mmap_sem);
   yield();
   down_read(&mm->mmap_sem);
Index: lx26-22-rc6-mm1/arch/x86_64/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/x86_64/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/x86_64/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -558,7 +558,7 @@ no_context:
  */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
```

```
   yield();
   goto again;
  }
Index: lx26-22-rc6-mm1/arch/xtensa/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/xtensa/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/xtensa/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -144,7 +144,7 @@ bad_area:
    */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
Index: lx26-22-rc6-mm1/drivers/char/sysrq.c
===================================================================
--- lx26-22-rc6-mm1.orig/drivers/char/sysrq.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/drivers/char/sysrq.c 2007-07-13 13:12:18.000000000 -0700
@@ -250,7 +250,7 @@ static void send_sig_all(int sig)
  struct task_struct *p;

  for_each_process(p) {
-  if (p->mm && !is_init(p))
+  if (p->mm && !is_global_init(p))
     /* Not swapper, init nor kernel thread */
     force_sig(sig, p);
  }
Index: lx26-22-rc6-mm1/kernel/capability.c
===================================================================
--- lx26-22-rc6-mm1.orig/kernel/capability.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/kernel/capability.c 2007-07-13 13:12:18.000000000 -0700
@@ -12,6 +12,7 @@
 #include <linux/module.h>
 #include <linux/security.h>
 #include <linux/syscalls.h>
+#include <linux/pid_namespace.h>
 #include <asm/uaccess.h>

 unsigned securebits = SECUREBITS_DEFAULT; /* systemwide security settings */
@@ -135,7 +136,7 @@ static inline int cap_set_all(kernel_cap
       int found = 0;

       do_each_thread(g, target) {
-               if (target == current || is_init(target))
+               if (target == current || is_container_init(target))
                        continue;
```

```
                found = 1;
        if (security_capset_check(target, effective, inheritable,
Index: lx26-22-rc6-mm1/kernel/exit.c
===================================================================
--- lx26-22-rc6-mm1.orig/kernel/exit.c 2007-07-13 13:12:01.000000000 -0700
+++ lx26-22-rc6-mm1/kernel/exit.c 2007-07-13 13:12:18.000000000 -0700
@@ -231,7 +231,7 @@ static int will_become_orphaned_pgrp(str
  do_each_pid_task(pgrp, PIDTYPE_PGID, p) {
   if (p == ignored_task
     || p->exit_state
-    || is_init(p->real_parent))
+    || is_global_init(p->real_parent))
    continue;
   if (task_pgrp(p->real_parent) != pgrp &&
       task_session(p->real_parent) == task_session(p)) {
Index: lx26-22-rc6-mm1/kernel/kexec.c
===================================================================
--- lx26-22-rc6-mm1.orig/kernel/kexec.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/kernel/kexec.c 2007-07-13 13:12:18.000000000 -0700
@@ -42,7 +42,7 @@ struct resource crashk_res = {

 int kexec_should_crash(struct task_struct *p)
 {
- if (in_interrupt() || !p->pid || is_init(p) || panic_on_oops)
+ if (in_interrupt() || !p->pid || is_global_init(p) || panic_on_oops)
   return 1;
  return 0;
 }
Index: lx26-22-rc6-mm1/kernel/sysctl.c
===================================================================
--- lx26-22-rc6-mm1.orig/kernel/sysctl.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/kernel/sysctl.c 2007-07-13 13:12:18.000000000 -0700
@@ -1924,7 +1924,7 @@ int proc_dointvec_bset(ctl_table *table,
   return -EPERM;
  }

- op = is_init(current) ? OP_SET : OP_AND;
+ op = is_global_init(current) ? OP_SET : OP_AND;
  return do_proc_dointvec(table,write,filp,buffer,lenp,ppos,
     do_proc_dointvec_bset_conv,&op);
 }
Index: lx26-22-rc6-mm1/mm/oom_kill.c
===================================================================
--- lx26-22-rc6-mm1.orig/mm/oom_kill.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/mm/oom_kill.c 2007-07-13 13:12:18.000000000 -0700
@@ -222,7 +222,7 @@ static struct task_struct *select_bad_pr
   if (!p->mm)
    continue;
```

```
   /* skip the init task */
-  if (is_init(p))
+  if (is_global_init(p))
    continue;

   /*
@@ -275,7 +275,7 @@ static struct task_struct *select_bad_pr
  */
 static void __oom_kill_task(struct task_struct *p, int verbose)
 {
- if (is_init(p)) {
+ if (is_global_init(p)) {
   WARN_ON(1);
   printk(KERN_WARNING "tried to kill init!\n");
   return;
Index: lx26-22-rc6-mm1/security/commoncap.c
===================================================================
--- lx26-22-rc6-mm1.orig/security/commoncap.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/security/commoncap.c 2007-07-13 13:12:18.000000000 -0700
@@ -23,6 +23,7 @@
 #include <linux/xattr.h>
 #include <linux/hugetlb.h>
 #include <linux/mount.h>
+#include <linux/sched.h>

 int cap_netlink_send(struct sock *sk, struct sk_buff *skb)
 {
@@ -261,7 +262,7 @@ void cap_bprm_apply_creds (struct linux_
  /* For init, we want to retain the capabilities set
   * in the init_task struct. Thus we skip the usual
   * capability rules */
- if (!is_init(current)) {
+ if (!is_global_init(current)) {
   current->cap_permitted = new_permitted;
   current->cap_effective =
       cap_intersect (new_permitted, bprm->cap_effective);
Index: lx26-22-rc6-mm1/arch/avr32/kernel/traps.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/avr32/kernel/traps.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/avr32/kernel/traps.c 2007-07-13 13:12:18.000000000 -0700
@@ -89,7 +89,7 @@ void _exception(long signr, struct pt_re
   * generate the same exception over and over again and we get
   * nowhere.  Better to kill it and let the kernel panic.
   */
- if (is_init(current)) {
+ if (is_global_init(current)) {
   __sighandler_t handler;
```

```
   spin_lock_irq(&current->sighand->siglock);
Index: lx26-22-rc6-mm1/arch/avr32/mm/fault.c
===================================================================
--- lx26-22-rc6-mm1.orig/arch/avr32/mm/fault.c 2007-07-13 13:05:38.000000000 -0700
+++ lx26-22-rc6-mm1/arch/avr32/mm/fault.c 2007-07-13 13:12:18.000000000 -0700
@@ -161,7 +161,7 @@ bad_area:
   if (exception_trace && printk_ratelimit())
    printk("%s%s[%d]: segfault at %08lx pc %08lx "
           "sp %08lx ecr %lu\n",
-          is_init(tsk) ? KERN_EMERG : KERN_INFO,
+          is_global_init(tsk) ? KERN_EMERG : KERN_INFO,
           tsk->comm, tsk->pid, address, regs->pc,
           regs->sp, ecr);
   _exception(SIGSEGV, regs, code, address);
@@ -210,7 +210,7 @@ no_context:
   */
 out_of_memory:
  up_read(&mm->mmap_sem);
- if (is_init(current)) {
+ if (is_global_init(current)) {
   yield();
   down_read(&mm->mmap_sem);
   goto survive;
@@ -232,7 +232,7 @@ do_sigbus:
  if (exception_trace)
   printk("%s%s[%d]: bus error at %08lx pc %08lx "
          "sp %08lx ecr %lu\n",
-         is_init(tsk) ? KERN_EMERG : KERN_INFO,
+         is_global_init(tsk) ? KERN_EMERG : KERN_INFO,
          tsk->comm, tsk->pid, address, regs->pc,
          regs->sp, ecr);

Index: lx26-22-rc6-mm1/kernel/signal.c
===================================================================
--- lx26-22-rc6-mm1.orig/kernel/signal.c 2007-07-13 13:12:01.000000000 -0700
+++ lx26-22-rc6-mm1/kernel/signal.c 2007-07-13 13:12:18.000000000 -0700
@@ -257,7 +257,7 @@ flush_signal_handlers(struct task_struct

 int unhandled_signal(struct task_struct *tsk, int sig)
 {
- if (is_init(tsk))
+ if (is_global_init(tsk))
   return 1;
  if (tsk->ptrace & PT_PTRACED)
   return 0;
```

Containers mailing list
Containers@lists.linux-foundation.org