

---

Subject: Re: [PATCH] Use task\_pid\_nr() in ip\_vs\_sync.c  
Posted by [Sukadev Bhattiprolu](#) on Wed, 29 Aug 2007 21:50:55 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Pavel Emelianov [xemul@openvz.org] wrote:  
| The sync\_master\_pid and sync\_backup\_pid are set in set\_sync\_pid()  
| and are used later for set/not-set checks and in printk. So it  
| is safe to use the global pid value in this case.  
|  
| Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

Acked-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

```
| ---  
|  
| diff --git a/net/ipv4/ipvs/ip_vs_sync.c b/net/ipv4/ipvs/ip_vs_sync.c  
| index 959c08d..d0798a5 100644  
| --- a/net/ipv4/ipvs/ip_vs_sync.c  
| +++ b/net/ipv4/ipvs/ip_vs_sync.c  
| @@ -794,7 +794,7 @@ static int sync_thread(void *startup)  
|  
|     add_wait_queue(&sync_wait, &wait);  
|  
| - set_sync_pid(state, current->pid);  
| + set_sync_pid(state, task_pid_nr(current));  
|     complete(tinfo->startup);  
|  
| /*
```

---

Containers mailing list  
[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---