

---

Subject: [PATCH 5/5][NFS] Use macro instead of explicit check for mandatory locks  
Posted by [Pavel Emelianov](#) on Wed, 12 Sep 2007 11:28:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The \_\_MANDATORY\_LOCK(inode) macro makes the same check, but makes the code more readable.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>  
Cc: Trond Myklebust <trond.myklebust@fys.uio.no>

---

fs/nfs/file.c | 3 +-  
1 files changed, 1 insertion(+), 2 deletions(-)

```
diff --git a/fs/nfs/file.c b/fs/nfs/file.c
index 73ddd2e..8dc2cde 100644
--- a/fs/nfs/file.c
+++ b/fs/nfs/file.c
@@ -605,8 +605,7 @@ static int nfs_lock(struct file *filp, i
 nfs_inc_stats(inode, NFSIOS_VFSLOCK);

 /* No mandatory locks over NFS */
- if ((inode->i_mode & (S_ISGID | S_IXGRP)) == S_ISGID &&
-     fl->fl_type != F_UNLCK)
+ if (__MANDATORY_LOCK(inode) && fl->fl_type != F_UNLCK)
    return -ENOLCK;

 if (IS_GETLK(cmd))
```

---