
Subject: [RFC][PATCH 0/2] New API to change the IDs of an existing IPC
Posted by [Pierre Peiffer](#) on Fri, 28 Sep 2007 14:58:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi,

As I'm seeing some discussion/interest about IPC, I would like to propose these patches, which provide an easy way to change the ID of an exiting IPC.
This work is done around the checkpoint/restart of applications. In the case of the IPCs, we need (among others) this functionality.

May be there is some other interest about this, so, the RFC concerns both the coding and the interest.

The first patch provide the functionality in kernel side, the second export it in user space. They apply on top of the latest -rc8 kernel. I can adapt them for the latest -mm.

Thanks,

--
Pierre

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [RFC][PATCH 0/2] New API to change the IDs of an existing IPC
Posted by [Michael Kerrisk](#) on Sun, 30 Sep 2007 06:30:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Pierre,

> As I'm seeing some discussion/interest about IPC, I would like to propose
> these patches, which provide an easy way to change the ID of an exiting IPC.
> This work is done around the checkpoint/restart of applications. In the case of
> the IPCs, we need (among others) this functionality.

Can you give some more detailed explanation of why this functionaility is needed. (Maybe this was explained in other threads, but if so I've missed it.)

Cheers,

Michael

Containers mailing list
Containers@lists.linux-foundation.org

Subject: Re: [RFC][PATCH 0/2] New API to change the IDs of an existing IPC

Posted by [Pierre Peiffer](#) on Mon, 01 Oct 2007 07:19:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

> Hi Pierre,

>

>> As I'm seeing some discussion/interest about IPC, I would like to propose

>> these patches, which provide an easy way to change the ID of an exiting IPC.

>> This work is done around the checkpoint/restart of applications. In the case of

>> the IPCs, we need (among others) this functionality.

>

> Can you give some more detailed explanation of why this

> functionality is needed.

Sure; in the case of the checkpoint/restart, when you restart an application, what you want is to recreate all system resources with the same properties they had, when you have checkpointed it. For IPCs, this means that you need to recreate all the IPCs with the same IDs (at least). For now, this ID is computed by the system when an IPC is created and you can't specify or modify it.

These patches give you the possibility of changing this ID once the IPC is created.

--

Pierre Peiffer

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
