
Subject: [patch -mm 5/5] mqueue namespace : make sysctl work per namespace
Posted by [Cedric Le Goater](#) on Tue, 02 Oct 2007 08:46:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Cedric Le Goater <clg@fr.ibm.com>

Largely inspired from ipc/ipc_sysctl.c

Todo:

- check CONFIG_* options
- move code to ipc/mqueue_sysctl.c ?

Signed-off-by: Cedric Le Goater <clg@fr.ibm.com>

ipc/mqueue.c | 40 ++++++-----
1 file changed, 37 insertions(+), 3 deletions(-)

Index: 2.6.23-rc8-mm2/ipc/mqueue.c

=====

```
--- 2.6.23-rc8-mm2.orig/ipc/mqueue.c
+++ 2.6.23-rc8-mm2/ipc/mqueue.c
@@ -1260,6 +1260,40 @@ static struct file_system_type mqueue_fs
    .kill_sb = kill_litter_super,
};

+static void *get_mq(ctl_table *table)
+{
+    char *which = table->data;
+    struct mq_namespace *mq_ns = current->nsproxy->mq_ns;
+    which = (which - (char *)&init_mq_ns) + (char *)mq_ns;
+    return which;
+
+#
+ifdef CONFIG_PROC_FS
+static int proc_mq_dointvec(ctl_table *table, int write, struct file *filp,
+    void __user *buffer, size_t *lenn, loff_t *ppos)
+{
+    struct ctl_table mq_table;
+    memcpy(&mq_table, table, sizeof(mq_table));
+    mq_table.data = get_mq(table);
+
+    return proc_dointvec(&mq_table, write, filp, buffer, lenn, ppos);
+
+#
+static int proc_mq_dointvec_minmax(ctl_table *table, int write,
+    struct file *filp, void __user *buffer, size_t *lenn, loff_t *ppos)
+{
+    struct ctl_table mq_table;
```

```

+ memcpy(&mq_table, table, sizeof(mq_table));
+ mq_table.data = get_mq(table);
+
+ return proc_dointvec_minmax(&mq_table, write, filp, buffer,
+    lenp, ppos);
+}
#endif
#define proc_mq_dointvec_minmax NULL
#define proc_mq_dointvec NULL
#endif
+
static int msg_max_limit_min = DFLT_MSGMAX;
static int msg_max_limit_max = HARD_MSGMAX;

@@ -1272,14 +1306,14 @@ static ctl_table mq_sysctls[] = {
    .data = &init_mq_ns.queues_max,
    . maxlen = sizeof(int),
    .mode = 0644,
-   .proc_handler = &proc_dointvec,
+   .proc_handler = &proc_mq_dointvec,
},
{
    .procname = "msg_max",
    .data = &init_mq_ns.msg_max,
    . maxlen = sizeof(int),
    .mode = 0644,
-   .proc_handler = &proc_dointvec_minmax,
+   .proc_handler = &proc_mq_dointvec_minmax,
    .extra1 = &msg_max_limit_min,
    .extra2 = &msg_max_limit_max,
},
@@ -1288,7 +1322,7 @@ static ctl_table mq_sysctls[] = {
    .data = &init_mq_ns.msgsize_max,
    . maxlen = sizeof(int),
    .mode = 0644,
-   .proc_handler = &proc_dointvec_minmax,
+   .proc_handler = &proc_mq_dointvec_minmax,
    .extra1 = &msg_maxsize_limit_min,
    .extra2 = &msg_maxsize_limit_max,
},
--
```

Containers mailing list
 Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
