
Subject: [PATCH] namespaces: introduce sys_hijack (v8)

Posted by [serue](#) on Fri, 02 Nov 2007 20:32:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

Apparently my hijack test program was just too mean-n-lean to show just how fragile sys_hijack was. Once it tried to do any kind of actual work before doing an exec(), it would segfault. Apparently just letting dup_task_struct() do `"*tsk = *hijacked_task"` was bogus.

Mark, I'm sorry, this is without your powerpc/x86_64 patches. But note that I took out the 'copy_a_thread' stuff which was bogus anyway.

It's incomplete, I need to walk through the task_struct and copy more of the relevant pieces from the hijacked task_struct. But this appears to be robust.

Tested with entering unshared uts namespace and with cloned pidns+mountns+utsns container.

thanks,
-serge

PS: also a typo fix in the hijack.c code.

>From 0efe7d1f607438be986d7000571fda406a866b12 Mon Sep 17 00:00:00 2001
From: sergeh@us.ibm.com <sergeh@us.ibm.com>
Date: Tue, 16 Oct 2007 09:36:49 -0700
Subject: [PATCH] namespaces: introduce sys_hijack (v8)

Move most of do_fork() into a new do_fork_task() which acts on a new argument, task, rather than on current. do_fork() becomes a call to do_fork_task(current, ...).

Introduce sys_hijack (for x86 only so far). It is like clone, but in place of a stack pointer (which is assumed null) it accepts a pid. The process identified by that pid is the one which is actually cloned. Some state - include the file table, the signals and sighand (and hence tty), and the ->parent are taken from the calling process.

A process to be hijacked may be identified by process id. Alternatively, an open fd for a cgroup 'tasks' file may be specified. The first available task in that cgroup will then be hijacked.

In order to hijack a process, the calling process must be allowed to ptrace the target.

The effect is a sort of namespace enter. The following program uses `sys_hijack` to 'enter' all namespaces of the specified task. For instance in one terminal, do

```
mount -t cgroup -ons /cgroup
hostname
qemu
ns_exec -u /bin/sh
hostname serge
echo $$
1073
cat /proc/$$/cgroup
ns:/node_1073
```

In another terminal then do

```
hostname
qemu
cat /proc/$$/cgroup
ns:/
hijack pid 1073
hostname
serge
cat /proc/$$/cgroup
ns:/node_1073
hijack cgroup /cgroup/node_1073/tasks
```

Changelog:

Aug 23: send a stop signal to the hijacked process (like `ptrace` does).

Oct 09: Update for 2.6.23-rc8-mm2 (mainly `pidns`)
Don't take `task_lock` under `rcu_read_lock`
Send hijacked process to `cgroup_fork()` as the first argument.
Removed some unneeded `task_locks`.

Oct 16: Fix bug introduced into `alloc_pid`.

Oct 16: Add 'int which' argument to `sys_hijack` to allow later expansion to use `cgroup` in place of `pid` to specify what to hijack.

Oct 24: Implement hijack by open `cgroup` file.

Nov 02: Switch copying of task info: do full copy from current, then copy relevant pieces from hijacked task.

```
=====
hijack.c
=====
```

```
#define _BSD_SOURCE
```

```

#include <unistd.h>
#include <sys/syscall.h>
#include <sys/types.h>
#include <sys/wait.h>
#include <sys/stat.h>
#include <fcntl.h>
#include <sched.h>

void usage(char *me)
{
    printf("Usage: %s pid <pid> | %s cgroup <cgroup_tasks_file>\n", me, me);
}

int exec_shell(void)
{
    execl("/bin/sh", "/bin/sh", NULL);
}

int main(int argc, char *argv[])
{
    int id;
    int ret;
    int status;
    int use_pid = 0;

    if (argc < 3 || !strcmp(argv[1], "-h")) {
        usage(argv[0]);
        return 1;
    }
    if (strcmp(argv[1], "pid") == 0)
        use_pid = 1;

    if (use_pid)
        id = atoi(argv[2]);
    else {
        id = open(argv[2], O_RDONLY);
        if (id == -1) {
            perror("cgroup open");
            return 1;
        }
    }

    ret = syscall(327, SIGCHLD, use_pid ? 1 : 2, (unsigned long)id);

    if (!use_pid)
        close(id);
    if (ret == 0) {
        return exec_shell();
    }
}

```

```

} else if (ret < 0) {
    perror("sys_hijack");
} else {
    printf("waiting on cloned process %d\n", ret);
    while(waitpid(-1, &status, __WALL) != -1)
        ;
    printf("cloned process exited with %d (waitpid ret %d)\n",
        status, ret);
}

return ret;
}

```

=====

Signed-off-by: Serge Hallyn <serue@us.ibm.com>

```

---
arch/i386/kernel/process.c      | 77 ++++++
arch/i386/kernel/syscall_table.S |  1 +
include/asm-i386/unistd.h      |  3 +-
include/linux/cgroup.h         | 10 +++-
include/linux/ptrace.h         |  1 +
include/linux/sched.h          |  7 +++
include/linux/syscalls.h       |  1 +
kernel/cgroup.c                | 69 ++++++
kernel/fork.c                  | 92 ++++++
kernel/ptrace.c                |  7 +++
10 files changed, 244 insertions(+), 24 deletions(-)

```

```

diff --git a/arch/i386/kernel/process.c b/arch/i386/kernel/process.c
index eab6c62..8add6e4 100644
--- a/arch/i386/kernel/process.c
+++ b/arch/i386/kernel/process.c
@@ -39,6 +39,7 @@
#include <linux/personality.h>
#include <linux/tick.h>
#include <linux/percpu.h>
+#include <linux/cgroup.h>

#include <asm/uaccess.h>
#include <asm/pgtable.h>
@@ -784,6 +785,82 @@ asmlinkage int sys_clone(struct pt_regs regs)
}

/*
+ * Called with task count bumped, drops task count before returning
+ */
+static int hijack_task(struct task_struct *task, struct pt_regs regs)
+{

```

```

+ unsigned long clone_flags = regs.ebx;
+ int ret = -EINVAL;
+
+ task_lock(task);
+ put_task_struct(task);
+ if (!ptrace_may_attach_locked(task)) {
+ ret = -EPERM;
+ goto out_put_task;
+ }
+ if (task->ptrace) {
+ ret = -EBUSY;
+ goto out_put_task;
+ }
+ force_sig_specific(SIGSTOP, task);
+
+ task_unlock(task);
+ ret = do_fork_task(task, clone_flags, regs.esp, &regs, 0,
+ NULL, NULL);
+ wake_up_process(task);
+ return ret;
+
+out_put_task:
+ task_unlock(task);
+ return ret;
+}
+
+static int hijack_pid(struct pt_regs regs)
+{
+ pid_t pid = regs.edx;
+ struct task_struct *task;
+
+ rcu_read_lock();
+ task = find_task_by_vpid(pid);
+ if (task)
+ get_task_struct(task);
+ rcu_read_unlock();
+
+ if (!task)
+ return -EINVAL;
+
+ return hijack_task(task, regs);
+}
+
+static int hijack_cgroup(struct pt_regs regs)
+{
+ unsigned int fd;
+ struct task_struct *task;
+

```

```

+ fd = (unsigned int) regs.edx;
+ task = task_from_cgroup_fd(fd);
+ if (IS_ERR(task))
+ return PTR_ERR(task);
+
+ return hijack_task(task, regs);
+}
+
+asmlinkage int sys_hijack(struct pt_regs regs)
+{
+ int which = regs.ecx;
+
+ switch (which) {
+ case HIJACK_PID:
+ return hijack_pid(regs);
+ case HIJACK_CGROUP:
+ return hijack_cgroup(regs);
+ default:
+ return -EINVAL;
+ }
+
+}
+
+/*
+ * This is trivial, and on the face of it looks like it
+ * could equally well be done in user mode.
+ */

```

```
diff --git a/arch/i386/kernel/syscall_table.S b/arch/i386/kernel/syscall_table.S
```

```
index df6e41e..495930c 100644
```

```
--- a/arch/i386/kernel/syscall_table.S
```

```
+++ b/arch/i386/kernel/syscall_table.S
```

```
@@ -326,3 +326,4 @@ ENTRY(sys_call_table)
```

```
.long sys_fallocate
```

```
.long sys_revokeat /* 325 */
```

```
.long sys_frevoke
```

```
+ .long sys_hijack
```

```
diff --git a/include/asm-i386/unistd.h b/include/asm-i386/unistd.h
```

```
index 006c1b3..fe6eeb4 100644
```

```
--- a/include/asm-i386/unistd.h
```

```
+++ b/include/asm-i386/unistd.h
```

```
@@ -332,10 +332,11 @@
```

```
#define __NR_fallocate 324
```

```
#define __NR_revokeat 325
```

```
#define __NR_frevoke 326
```

```
+#define __NR_hijack 327
```

```
#ifdef __KERNEL__
```

```

-#define NR_syscalls 327
+#define NR_syscalls 328

#define __ARCH_WANT_IPC_PARSE_VERSION
#define __ARCH_WANT_OLD_READDIR
diff --git a/include/linux/cgroup.h b/include/linux/cgroup.h
index 8747932..3edb820 100644
--- a/include/linux/cgroup.h
+++ b/include/linux/cgroup.h
@@ -26,7 +26,7 @@ extern int cgroup_init(void);
extern void cgroup_init_smp(void);
extern void cgroup_lock(void);
extern void cgroup_unlock(void);
-extern void cgroup_fork(struct task_struct *p);
+extern void cgroup_fork(struct task_struct *parent, struct task_struct *p);
extern void cgroup_fork_callbacks(struct task_struct *p);
extern void cgroup_post_fork(struct task_struct *p);
extern void cgroup_exit(struct task_struct *p, int run_callbacks);
@@ -304,12 +304,14 @@ struct task_struct *cgroup_iter_next(struct cgroup *cont,
    struct cgroup_iter *it);
void cgroup_iter_end(struct cgroup *cont, struct cgroup_iter *it);

+struct task_struct *task_from_cgroup_fd(unsigned int fd);
#else /* !CONFIG_CGROUPS */

static inline int cgroup_init_early(void) { return 0; }
static inline int cgroup_init(void) { return 0; }
static inline void cgroup_init_smp(void) {}
-static inline void cgroup_fork(struct task_struct *p) {}
+static inline void cgroup_fork(struct task_struct *parent,
+    struct task_struct *p) {}
static inline void cgroup_fork_callbacks(struct task_struct *p) {}
static inline void cgroup_post_fork(struct task_struct *p) {}
static inline void cgroup_exit(struct task_struct *p, int callbacks) {}
@@ -322,6 +324,10 @@ static inline int cgroupstats_build(struct cgroupstats *stats,
    return -EINVAL;
}

+static inline struct task_struct *task_from_cgroup_fd(unsigned int fd)
+{
+ return ERR_PTR(-EINVAL);
+}
#endif /* !CONFIG_CGROUPS */

#endif /* _LINUX_CGROUP_H */
diff --git a/include/linux/ptrace.h b/include/linux/ptrace.h
index ae8146a..727a4a9 100644
--- a/include/linux/ptrace.h

```

```

+++ b/include/linux/ptrace.h
@@ -97,6 +97,7 @@ extern void __ptrace_link(struct task_struct *child,
extern void __ptrace_unlink(struct task_struct *child);
extern void ptrace_untrace(struct task_struct *child);
extern int ptrace_may_attach(struct task_struct *task);
+extern int ptrace_may_attach_locked(struct task_struct *task);

static inline void ptrace_link(struct task_struct *child,
struct task_struct *new_parent)
diff --git a/include/linux/sched.h b/include/linux/sched.h
index 3436b98..18cde38 100644
--- a/include/linux/sched.h
+++ b/include/linux/sched.h
@@ -29,6 +29,12 @@
#define CLONE_NEWNET 0x40000000 /* New network namespace */

/*
+ * Hijack flags
+ */
+#define HIJACK_PID 1 /* 'id' is a pid */
+#define HIJACK_CGROUP 2 /* 'id' is an open fd for a cgroup dir */
+
+/*
* Scheduling policies
*/
#define SCHED_NORMAL 0
@@ -1658,6 +1664,7 @@ extern int allow_signal(int);
extern int disallow_signal(int);

extern int do_execve(char *, char __user * __user *, char __user * __user *, struct pt_regs *);
+extern long do_fork_task(struct task_struct *task, unsigned long, unsigned long, struct pt_regs *,
unsigned long, int __user *, int __user *);
extern long do_fork(unsigned long, unsigned long, struct pt_regs *, unsigned long, int __user *,
int __user *);
struct task_struct *fork_idle(int);

diff --git a/include/linux/syscalls.h b/include/linux/syscalls.h
index f696874..31f0c79 100644
--- a/include/linux/syscalls.h
+++ b/include/linux/syscalls.h
@@ -616,5 +616,6 @@ int kernel_execve(const char *filename, char *const argv[], char *const
envp[]);

asmlinkage long sys_revokeat(int dfd, const char __user *filename);
asmlinkage long sys_frevoke(unsigned int fd);
+asmlinkage long sys_hijack(unsigned long flags, int which, unsigned long id);

#endif

```

```

diff --git a/kernel/cgroup.c b/kernel/cgroup.c
index 8720881..2d1d67e 100644
--- a/kernel/cgroup.c
+++ b/kernel/cgroup.c
@@ -45,6 +45,7 @@
#include <linux/sort.h>
#include <linux/delayacct.h>
#include <linux/cgroupstats.h>
+#include <linux/file.h>

#include <asm/atomic.h>

@@ -2460,12 +2461,12 @@ static struct file_operations proc_cgroupstats_operations = {
 * At the point that cgroup_fork() is called, 'current' is the parent
 * task, and the passed argument 'child' points to the child task.
 */
-void cgroup_fork(struct task_struct *child)
+void cgroup_fork(struct task_struct *parent, struct task_struct *child)
{
- task_lock(current);
- child->cgroups = current->cgroups;
+ task_lock(parent);
+ child->cgroups = parent->cgroups;
  get_css_set(child->cgroups);
- task_unlock(current);
+ task_unlock(parent);
  INIT_LIST_HEAD(&child->cg_list);
}

@@ -2819,3 +2820,63 @@ static void cgroup_release_agent(struct work_struct *work)
  spin_unlock(&release_list_lock);
  mutex_unlock(&cgroup_mutex);
}
+
+static inline int task_available(struct task_struct *task)
+{
+ switch(task->state) {
+ case TASK_RUNNING:
+ case TASK_INTERRUPTIBLE:
+ return 1;
+ default:
+ return 0;
+ }
+}
+
+/*
+ * Takes an integer which is a open fd in current for a valid
+ * cgroupfs file. Returns a task in that cgroup, with its

```

```

+ * refcount bumped.
+ */
+struct task_struct *task_from_cgroup_fd(unsigned int fd)
+{
+ struct file *file;
+ struct cgroup *cgroup;
+ struct cgroup_iter it;
+ struct task_struct *task = NULL;
+
+ file = fget(fd);
+ if (!file)
+ return ERR_PTR(-EINVAL);
+
+ if (!file->f_dentry || !file->f_dentry->d_sb)
+ goto out_fput;
+ if (file->f_dentry->d_parent->d_sb->s_magic != CGROUP_SUPER_MAGIC)
+ goto out_fput;
+ if (strcmp(file->f_dentry->d_name.name, "tasks"))
+ goto out_fput;
+
+ rcu_read_lock();
+ cgroup = __d_cont(file->f_dentry->d_parent);
+ printk(KERN_NOTICE "cgroup is %lu\n", (unsigned long)cgroup);
+ if (!cgroup)
+ goto out_unlock;
+ cgroup_iter_start(cgroup, &it);
+ do {
+ task = cgroup_iter_next(cgroup, &it);
+ if (task)
+ printk(KERN_NOTICE "task %d state %d\n",
+ task->pid, task->state);
+ } while (task && !task_available(task));
+ cgroup_iter_end(cgroup, &it);
+ printk(KERN_NOTICE "task is %lu\n", (unsigned long)task);
+ if (task)
+ get_task_struct(task);
+
+out_unlock:
+ rcu_read_unlock();
+out_fput:
+ fput(file);
+ if (!task)
+ return ERR_PTR(-EINVAL);
+ return task;
+}
diff --git a/kernel/fork.c b/kernel/fork.c
index 64860ef..4d3d3f7 100644
--- a/kernel/fork.c

```

```

+++ b/kernel/fork.c
@@ -190,7 +190,7 @@ static struct task_struct *dup_task_struct(struct task_struct *orig)
    return NULL;
}

```

```

- setup_thread_stack(tsk, orig);
+ setup_thread_stack(tsk, current);

```

```

#ifdef CONFIG_CC_STACKPROTECTOR
    tsk->stack_canary = get_random_int();
@@ -621,13 +621,14 @@ struct fs_struct *copy_fs_struct(struct fs_struct *old)

```

```

EXPORT_SYMBOL_GPL(copy_fs_struct);

```

```

-static int copy_fs(unsigned long clone_flags, struct task_struct *tsk)

```

```

+static inline int copy_fs(unsigned long clone_flags,
+ struct task_struct * src, struct task_struct * tsk)

```

```

{
    if (clone_flags & CLONE_FS) {
- atomic_inc(&current->fs->count);
+ atomic_inc(&src->fs->count);
        return 0;
    }

```

```

- tsk->fs = __copy_fs_struct(current->fs);

```

```

+ tsk->fs = __copy_fs_struct(src->fs);

```

```

    if (!tsk->fs)
        return -ENOMEM;
    return 0;

```

```

@@ -965,6 +966,30 @@ static void rt_mutex_init_task(struct task_struct *p)

```

```

#endif

```

```

}

```

```

+void copy_hijackable_taskinfo(struct task_struct *p,

```

```

+ struct task_struct *task)

```

```

+{

```

```

+ p->uid = task->uid;

```

```

+ p->euid = task->euid;

```

```

+ p->suid = task->suid;

```

```

+ p->fsuid = task->fsuid;

```

```

+ p->gid = task->gid;

```

```

+ p->egid = task->egid;

```

```

+ p->sgid = task->sgid;

```

```

+ p->fsgid = task->fsgid;

```

```

+ p->cap_effective = task->cap_effective;

```

```

+ p->cap_inheritable = task->cap_inheritable;

```

```

+ p->cap_permitted = task->cap_permitted;

```

```

+ p->keep_capabilities = task->keep_capabilities;

```

```

+ p->user = task->user;

```

```

+ p->nsproxy = task->nsproxy;
+ /*
+  * TODO: continue taking relevant pieces from
+  * hijacked task, starting at:
+  *   key info
+  */
+}
+
+/*
+ * This creates a new process as a copy of the old one,
+ * but does not actually start it yet.
@@ -973,7 +998,8 @@ static void rt_mutex_init_task(struct task_struct *p)
+ * parts of the process environment (as per the clone
+ * flags). The actual kick-off is left to the caller.
+ */
-static struct task_struct *copy_process(unsigned long clone_flags,
+static struct task_struct *copy_process(struct task_struct *task,
+ unsigned long clone_flags,
+   unsigned long stack_start,
+   struct pt_regs *regs,
+   unsigned long stack_size,
@@ -1010,12 +1036,17 @@ static struct task_struct *copy_process(unsigned long clone_flags,
+ p = dup_task_struct(current);
+ if (!p)
+   goto fork_out;
+ if (current != task) {
+ copy_hijackable_taskinfo(p, task);
+ }

+   rt_mutex_init_task(p);

#ifdef CONFIG_TRACE_IRQFLAGS
- DEBUG_LOCKS_WARN_ON(!p->hardirqs_enabled);
- DEBUG_LOCKS_WARN_ON(!p->softirqs_enabled);
+ if (task == current) {
+ DEBUG_LOCKS_WARN_ON(!p->hardirqs_enabled);
+ DEBUG_LOCKS_WARN_ON(!p->softirqs_enabled);
+ }
#endif
+   retval = -EAGAIN;
+   if (atomic_read(&p->user->processes) >=
@@ -1084,7 +1115,7 @@ static struct task_struct *copy_process(unsigned long clone_flags,
+   #endif
+   p->io_context = NULL;
+   p->audit_context = NULL;
- cgroup_fork(p);
+ cgroup_fork(task, p);
#ifdef CONFIG_NUMA

```

```

    p->mempolicy = mpol_copy(p->mempolicy);
    if (IS_ERR(p->mempolicy)) {
@@ -1132,7 +1163,7 @@ static struct task_struct *copy_process(unsigned long clone_flags,
    goto bad_fork_cleanup_audit;
    if ((retval = copy_files(clone_flags, p)))
        goto bad_fork_cleanup_semundo;
- if ((retval = copy_fs(clone_flags, p)))
+ if ((retval = copy_fs(clone_flags, task, p)))
    goto bad_fork_cleanup_files;
    if ((retval = copy_sighand(clone_flags, p)))
        goto bad_fork_cleanup_fs;
@@ -1164,7 +1195,7 @@ static struct task_struct *copy_process(unsigned long clone_flags,
    p->pid = pid_nr(pid);
    p->tgid = p->pid;
    if (clone_flags & CLONE_THREAD)
- p->tgid = current->tgid;
+ p->tgid = task->tgid;

    p->set_child_tid = (clone_flags & CLONE_CHILD_SETTID) ? child_tidptr : NULL;
/*
@@ -1379,7 +1410,7 @@ struct task_struct * __cpuinit fork_idle(int cpu)
    struct task_struct *task;
    struct pt_regs regs;

- task = copy_process(CLONE_VM, 0, idle_regs(&regs), 0, NULL,
+ task = copy_process(current, CLONE_VM, 0, idle_regs(&regs), 0, NULL,
    &init_struct_pid);
    if (!IS_ERR(task))
        init_idle(task, cpu);
@@ -1404,12 +1435,12 @@ static int fork_traceflag(unsigned clone_flags)
}

/*
- * Ok, this is the main fork-routine.
- *
- * It copies the process, and if successful kick-starts
- * it and waits for it to finish using the VM if required.
+ * if called with task!=current, then caller must ensure that
+ * 1. it has a reference to task
+ * 2. current must have ptrace permission to task
*/
-long do_fork(unsigned long clone_flags,
+long do_fork_task(struct task_struct *task,
+ unsigned long clone_flags,
    unsigned long stack_start,
    struct pt_regs *regs,
    unsigned long stack_size,
@@ -1420,13 +1451,23 @@ long do_fork(unsigned long clone_flags,

```

```

int trace = 0;
long nr;

+ if (task != current) {
+ /* sanity checks */
+ /* we only want to allow hijacking the simplest cases */
+ if (clone_flags & CLONE_SYSVSEM)
+ return -EINVAL;
+ if (current->ptrace)
+ return -EPERM;
+ if (task->ptrace)
+ return -EINVAL;
+ }
+ if (unlikely(current->ptrace)) {
+ trace = fork_traceflag (clone_flags);
+ if (trace)
+ clone_flags |= CLONE_PTRACE;
+ }

- p = copy_process(clone_flags, stack_start, regs, stack_size,
+ p = copy_process(task, clone_flags, stack_start, regs, stack_size,
+ child_tidptr, NULL);
/*
* Do this prior waking up the new thread - the thread pointer
@@ -1481,6 +1522,23 @@ long do_fork(unsigned long clone_flags,
return nr;
}

+/*
+ * Ok, this is the main fork-routine.
+ *
+ * It copies the process, and if successful kick-starts
+ * it and waits for it to finish using the VM if required.
+ */
+long do_fork(unsigned long clone_flags,
+ unsigned long stack_start,
+ struct pt_regs *regs,
+ unsigned long stack_size,
+ int __user *parent_tidptr,
+ int __user *child_tidptr)
+{
+ return do_fork_task(current, clone_flags, stack_start,
+ regs, stack_size, parent_tidptr, child_tidptr);
+}
+
+ #ifndef ARCH_MIN_MMSTRUCT_ALIGN
+ #define ARCH_MIN_MMSTRUCT_ALIGN 0
+ #endif

```

```
diff --git a/kernel/ptrace.c b/kernel/ptrace.c
index 7c76f2f..c65c9fe 100644
--- a/kernel/ptrace.c
+++ b/kernel/ptrace.c
@@ -159,6 +159,13 @@ int ptrace_may_attach(struct task_struct *task)
    return !err;
}

+int ptrace_may_attach_locked(struct task_struct *task)
+{
+ int err;
+ err = may_attach(task);
+ return !err;
+}
+
int ptrace_attach(struct task_struct *task)
{
    int retval;
--
1.5.1
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [PATCH] namespaces: introduce sys_hijack (v8)
Posted by [Mark Nelson](#) on Sun, 04 Nov 2007 22:43:03 GMT
[View Forum Message](#) <> [Reply to Message](#)

Serge E. Hallyn wrote:

> Apparently my hijack test program was just too mean-n-lean to show just
> how fragile sys_hijack was. Once it tried to do any kind of actual work
> before doing an exec(), it would segfault. Apparently just letting
> dup_task_struct() do "*tsk = *hijacked_task" was bogus.
>
> Mark, I'm sorry, this is without your powerpc/x86_64 patches. But note
> that I took out the 'copy_a_thread' stuff which was bogus anyway.

That's fine - I needed to do more testing on them anyway :)

I'll work on re-spinning them against this v8 of sys_hijack after I finish
up with 2.6.23-mm1-lxc1.

Thanks!

Mark.

>
> It's incomplete, I need to walk through the task_struct and copy more of
> the relevant pieces from the hijacked task_struct. But this appears to
> be robust.
>
> Tested with entering unshared uts namespace and with cloned
> pidns+mountns+utsns container.
>
> thanks,
> -serge
>
> PS: also a typo fix in the hijack.c code.
>
>>From 0efe7d1f607438be986d7000571fda406a866b12 Mon Sep 17 00:00:00 2001
> From: sergeh@us.ibm.com <sergeh@us.ibm.com>
> Date: Tue, 16 Oct 2007 09:36:49 -0700
> Subject: [PATCH] namespaces: introduce sys_hijack (v8)
>
> Move most of do_fork() into a new do_fork_task() which acts on
> a new argument, task, rather than on current. do_fork() becomes
> a call to do_fork_task(current, ...).
>
> Introduce sys_hijack (for x86 only so far). It is like clone, but
> in place of a stack pointer (which is assumed null) it accepts a
> pid. The process identified by that pid is the one which is
> actually cloned. Some state - include the file table, the signals
> and sighand (and hence tty), and the ->parent are taken from the
> calling process.
>
> A process to be hijacked may be identified by process id.
> Alternatively, an open fd for a cgroup 'tasks' file may be
> specified. The first available task in that cgroup will then
> be hijacked.
>
> In order to hijack a process, the calling process must be
> allowed to ptrace the target.
>
> The effect is a sort of namespace enter. The following program
> uses sys_hijack to 'enter' all namespaces of the specified task.
> For instance in one terminal, do
>
> mount -t cgroup -ons /cgroup
> hostname
> qemu
> ns_exec -u /bin/sh
> hostname serge
> echo \$\$

```

> 1073
> cat /proc/$$/cgroup
> ns:/node_1073
>
> In another terminal then do
>
> hostname
> qemu
> cat /proc/$$/cgroup
> ns:/
> hijack pid 1073
> hostname
> serge
> cat /proc/$$/cgroup
> ns:/node_1073
> hijack cgroup /cgroup/node_1073/tasks
>
> Changelog:
> Aug 23: send a stop signal to the hijacked process
> (like ptrace does).
> Oct 09: Update for 2.6.23-rc8-mm2 (mainly pidns)
> Don't take task_lock under rcu_read_lock
> Send hijacked process to cgroup_fork() as
> the first argument.
> Removed some unneeded task_locks.
> Oct 16: Fix bug introduced into alloc_pid.
> Oct 16: Add 'int which' argument to sys_hijack to
> allow later expansion to use cgroup in place
> of pid to specify what to hijack.
> Oct 24: Implement hijack by open cgroup file.
> Nov 02: Switch copying of task info: do full copy
> from current, then copy relevant pieces from
> hijacked task.
>
> =====
> hijack.c
> =====
> #define _BSD_SOURCE
> #include <unistd.h>
> #include <sys/syscall.h>
> #include <sys/types.h>
> #include <sys/wait.h>
> #include <sys/stat.h>
> #include <fcntl.h>
> #include <sched.h>
>
> void usage(char *me)
> {

```

```

> printf("Usage: %s pid <pid> | %s cgroup <cgroup_tasks_file>\n", me, me);
> }
>
> int exec_shell(void)
> {
>     execl("/bin/sh", "/bin/sh", NULL);
> }
>
> int main(int argc, char *argv[])
> {
>     int id;
>     int ret;
>     int status;
>     int use_pid = 0;
>
>     if (argc < 3 || !strcmp(argv[1], "-h")) {
>         usage(argv[0]);
>         return 1;
>     }
>     if (strcmp(argv[1], "pid") == 0)
>         use_pid = 1;
>
>     if (use_pid)
>         id = atoi(argv[2]);
>     else {
>         id = open(argv[2], O_RDONLY);
>         if (id == -1) {
>             perror("cgroup open");
>             return 1;
>         }
>     }
>
>     ret = syscall(327, SIGCHLD, use_pid ? 1 : 2, (unsigned long)id);
>
>     if (!use_pid)
>         close(id);
>     if (ret == 0) {
>         return exec_shell();
>     } else if (ret < 0) {
>         perror("sys_hijack");
>     } else {
>         printf("waiting on cloned process %d\n", ret);
>         while(waitpid(-1, &status, __WALL) != -1)
>             ;
>         printf("cloned process exited with %d (waitpid ret %d)\n",
>             status, ret);
>     }
> }
>

```

```

> return ret;
> }
> =====
>
> Signed-off-by: Serge Hallyn <serue@us.ibm.com>
> ---
> arch/i386/kernel/process.c      | 77 ++++++
> arch/i386/kernel/syscall_table.S | 1 +
> include/asm-i386/unistd.h       | 3 +-
> include/linux/cgroup.h         | 10 +++
> include/linux/ptrace.h         | 1 +
> include/linux/sched.h          | 7 +++
> include/linux/syscalls.h       | 1 +
> kernel/cgroup.c                | 69 ++++++
> kernel/fork.c                   | 92 ++++++
> kernel/ptrace.c                 | 7 +++
> 10 files changed, 244 insertions(+), 24 deletions(-)
>
> diff --git a/arch/i386/kernel/process.c b/arch/i386/kernel/process.c
> index eab6c62..8add6e4 100644
> --- a/arch/i386/kernel/process.c
> +++ b/arch/i386/kernel/process.c
> @@ -39,6 +39,7 @@
> #include <linux/personality.h>
> #include <linux/tick.h>
> #include <linux/percpu.h>
> +#include <linux/cgroup.h>
>
> #include <asm/uaccess.h>
> #include <asm/pgtable.h>
> @@ -784,6 +785,82 @@ asmlinkage int sys_clone(struct pt_regs regs)
> }
>
> /*
> + * Called with task count bumped, drops task count before returning
> + */
> +static int hijack_task(struct task_struct *task, struct pt_regs regs)
> +{
> + unsigned long clone_flags = regs.ebx;
> + int ret = -EINVAL;
> +
> + task_lock(task);
> + put_task_struct(task);
> + if (!ptrace_may_attach_locked(task)) {
> + ret = -EPERM;
> + goto out_put_task;
> + }
> + if (task->ptrace) {

```

```

> + ret = -EBUSY;
> + goto out_put_task;
> + }
> + force_sig_specific(SIGSTOP, task);
> +
> + task_unlock(task);
> + ret = do_fork_task(task, clone_flags, regs.esp, &regs, 0,
> + NULL, NULL);
> + wake_up_process(task);
> + return ret;
> +
> +out_put_task:
> + task_unlock(task);
> + return ret;
> +}
> +
> +static int hijack_pid(struct pt_regs regs)
> +{
> + pid_t pid = regs.edx;
> + struct task_struct *task;
> +
> + rcu_read_lock();
> + task = find_task_by_vpid(pid);
> + if (task)
> + get_task_struct(task);
> + rcu_read_unlock();
> +
> + if (!task)
> + return -EINVAL;
> +
> + return hijack_task(task, regs);
> +}
> +
> +static int hijack_cgroup(struct pt_regs regs)
> +{
> + unsigned int fd;
> + struct task_struct *task;
> +
> + fd = (unsigned int) regs.edx;
> + task = task_from_cgroup_fd(fd);
> + if (IS_ERR(task))
> + return PTR_ERR(task);
> +
> + return hijack_task(task, regs);
> +}
> +
> +asmlinkage int sys_hijack(struct pt_regs regs)
> +{

```

```

> + int which = regs.ecx;
> +
> + switch (which) {
> + case HIJACK_PID:
> + return hijack_pid(regs);
> + case HIJACK_CGROUP:
> + return hijack_cgroup(regs);
> + default:
> + return -EINVAL;
> + }
> +
> +}
> +
> +/*
> * This is trivial, and on the face of it looks like it
> * could equally well be done in user mode.
> *
> diff --git a/arch/i386/kernel/syscall_table.S b/arch/i386/kernel/syscall_table.S
> index df6e41e..495930c 100644
> --- a/arch/i386/kernel/syscall_table.S
> +++ b/arch/i386/kernel/syscall_table.S
> @@ -326,3 +326,4 @@ ENTRY(sys_call_table)
> .long sys_fallocate
> .long sys_revokeat /* 325 */
> .long sys_frevoke
> + .long sys_hijack
> diff --git a/include/asm-i386/unistd.h b/include/asm-i386/unistd.h
> index 006c1b3..fe6eeb4 100644
> --- a/include/asm-i386/unistd.h
> +++ b/include/asm-i386/unistd.h
> @@ -332,10 +332,11 @@
> #define __NR_fallocate 324
> #define __NR_revokeat 325
> #define __NR_frevoke 326
> +#define __NR_hijack 327
>
> #ifdef __KERNEL__
>
> -#define NR_syscalls 327
> +#define NR_syscalls 328
>
> #define __ARCH_WANT_IPC_PARSE_VERSION
> #define __ARCH_WANT_OLD_READDIR
> diff --git a/include/linux/cgroup.h b/include/linux/cgroup.h
> index 8747932..3edb820 100644
> --- a/include/linux/cgroup.h
> +++ b/include/linux/cgroup.h
> @@ -26,7 +26,7 @@ extern int cgroup_init(void);

```

```

> extern void cgroup_init_smp(void);
> extern void cgroup_lock(void);
> extern void cgroup_unlock(void);
> -extern void cgroup_fork(struct task_struct *p);
> +extern void cgroup_fork(struct task_struct *parent, struct task_struct *p);
> extern void cgroup_fork_callbacks(struct task_struct *p);
> extern void cgroup_post_fork(struct task_struct *p);
> extern void cgroup_exit(struct task_struct *p, int run_callbacks);
> @@ -304,12 +304,14 @@ struct task_struct *cgroup_iter_next(struct cgroup *cont,
>     struct cgroup_iter *it);
> void cgroup_iter_end(struct cgroup *cont, struct cgroup_iter *it);
>
> +struct task_struct *task_from_cgroup_fd(unsigned int fd);
> #else /* !CONFIG_CGROUPS */
>
> static inline int cgroup_init_early(void) { return 0; }
> static inline int cgroup_init(void) { return 0; }
> static inline void cgroup_init_smp(void) {}
> -static inline void cgroup_fork(struct task_struct *p) {}
> +static inline void cgroup_fork(struct task_struct *parent,
> +     struct task_struct *p) {}
> static inline void cgroup_fork_callbacks(struct task_struct *p) {}
> static inline void cgroup_post_fork(struct task_struct *p) {}
> static inline void cgroup_exit(struct task_struct *p, int callbacks) {}
> @@ -322,6 +324,10 @@ static inline int cgroupstats_build(struct cgroupstats *stats,
>     return -EINVAL;
> }
>
> +static inline struct task_struct *task_from_cgroup_fd(unsigned int fd)
> +{
> + return ERR_PTR(-EINVAL);
> +}
> #endif /* !CONFIG_CGROUPS */
>
> #endif /* _LINUX_CGROUP_H */
> diff --git a/include/linux/ptrace.h b/include/linux/ptrace.h
> index ae8146a..727a4a9 100644
> --- a/include/linux/ptrace.h
> +++ b/include/linux/ptrace.h
> @@ -97,6 +97,7 @@ extern void __ptrace_link(struct task_struct *child,
> extern void __ptrace_unlink(struct task_struct *child);
> extern void ptrace_untrace(struct task_struct *child);
> extern int ptrace_may_attach(struct task_struct *task);
> +extern int ptrace_may_attach_locked(struct task_struct *task);
>
> static inline void ptrace_link(struct task_struct *child,
>     struct task_struct *new_parent)
> diff --git a/include/linux/sched.h b/include/linux/sched.h

```

```

> index 3436b98..18cde38 100644
> --- a/include/linux/sched.h
> +++ b/include/linux/sched.h
> @@ -29,6 +29,12 @@
> #define CLONE_NEWNET 0x40000000 /* New network namespace */
>
> /*
> + * Hijack flags
> + */
> +#define HIJACK_PID 1 /* 'id' is a pid */
> +#define HIJACK_CGROUP 2 /* 'id' is an open fd for a cgroup dir */
> +
> +/*
> * Scheduling policies
> */
> #define SCHED_NORMAL 0
> @@ -1658,6 +1664,7 @@ extern int allow_signal(int);
> extern int disallow_signal(int);
>
> extern int do_execve(char *, char __user * __user *, char __user * __user *, struct pt_regs *);
> +extern long do_fork_task(struct task_struct *task, unsigned long, unsigned long, struct pt_regs
*, unsigned long, int __user *, int __user *);
> extern long do_fork(unsigned long, unsigned long, struct pt_regs *, unsigned long, int __user *,
int __user *);
> struct task_struct *fork_idle(int);
>
> diff --git a/include/linux/syscalls.h b/include/linux/syscalls.h
> index f696874..31f0c79 100644
> --- a/include/linux/syscalls.h
> +++ b/include/linux/syscalls.h
> @@ -616,5 +616,6 @@ int kernel_execve(const char *filename, char *const argv[], char *const
envp[]);
>
> asmlinkage long sys_revokeat(int dfd, const char __user *filename);
> asmlinkage long sys_frevoke(unsigned int fd);
> +asmlinkage long sys_hijack(unsigned long flags, int which, unsigned long id);
>
> #endif
> diff --git a/kernel/cgroup.c b/kernel/cgroup.c
> index 8720881..2d1d67e 100644
> --- a/kernel/cgroup.c
> +++ b/kernel/cgroup.c
> @@ -45,6 +45,7 @@
> #include <linux/sort.h>
> #include <linux/delayacct.h>
> #include <linux/cgroupstats.h>
> +#include <linux/file.h>
>

```

```

> #include <asm/atomic.h>
>
> @@ -2460,12 +2461,12 @@ static struct file_operations proc_cgroupstats_operations = {
> * At the point that cgroup_fork() is called, 'current' is the parent
> * task, and the passed argument 'child' points to the child task.
> */
> -void cgroup_fork(struct task_struct *child)
> +void cgroup_fork(struct task_struct *parent, struct task_struct *child)
> {
> - task_lock(current);
> - child->cgroups = current->cgroups;
> + task_lock(parent);
> + child->cgroups = parent->cgroups;
> get_css_set(child->cgroups);
> - task_unlock(current);
> + task_unlock(parent);
> INIT_LIST_HEAD(&child->cg_list);
> }
>
> @@ -2819,3 +2820,63 @@ static void cgroup_release_agent(struct work_struct *work)
> spin_unlock(&release_list_lock);
> mutex_unlock(&cgroup_mutex);
> }
> +
> +static inline int task_available(struct task_struct *task)
> +{
> + switch(task->state) {
> + case TASK_RUNNING:
> + case TASK_INTERRUPTIBLE:
> + return 1;
> + default:
> + return 0;
> + }
> +}
> +
> +/*
> + * Takes an integer which is a open fd in current for a valid
> + * cgroupfs file. Returns a task in that cgroup, with its
> + * refcount bumped.
> + */
> +struct task_struct *task_from_cgroup_fd(unsigned int fd)
> +{
> + struct file *file;
> + struct cgroup *cgroup;
> + struct cgroup_iter it;
> + struct task_struct *task = NULL;
> +
> + file = fget(fd);

```

```

> + if (!file)
> + return ERR_PTR(-EINVAL);
> +
> + if (!file->f_dentry || !file->f_dentry->d_sb)
> + goto out_fput;
> + if (file->f_dentry->d_parent->d_sb->s_magic != CGROUP_SUPER_MAGIC)
> + goto out_fput;
> + if (strcmp(file->f_dentry->d_name.name, "tasks"))
> + goto out_fput;
> +
> + rcu_read_lock();
> + cgroup = __d_cont(file->f_dentry->d_parent);
> +printk(KERN_NOTICE "cgroup is %lu\n", (unsigned long)cgroup);
> + if (!cgroup)
> + goto out_unlock;
> + cgroup_iter_start(cgroup, &it);
> + do {
> + task = cgroup_iter_next(cgroup, &it);
> + if (task)
> + printk(KERN_NOTICE "task %d state %d\n",
> + task->pid, task->state);
> + } while (task && !task_available(task));
> + cgroup_iter_end(cgroup, &it);
> +printk(KERN_NOTICE "task is %lu\n", (unsigned long)task);
> + if (task)
> + get_task_struct(task);
> +
> +out_unlock:
> + rcu_read_unlock();
> +out_fput:
> + fput(file);
> + if (!task)
> + return ERR_PTR(-EINVAL);
> + return task;
> +}
> diff --git a/kernel/fork.c b/kernel/fork.c
> index 64860ef..4d3d3f7 100644
> --- a/kernel/fork.c
> +++ b/kernel/fork.c
> @@ -190,7 +190,7 @@ static struct task_struct *dup_task_struct(struct task_struct *orig)
> return NULL;
> }
>
> - setup_thread_stack(tsk, orig);
> + setup_thread_stack(tsk, current);
>
> #ifdef CONFIG_CC_STACKPROTECTOR
> tsk->stack_canary = get_random_int();

```

```

> @@ -621,13 +621,14 @@ struct fs_struct *copy_fs_struct(struct fs_struct *old)
>
> EXPORT_SYMBOL_GPL(copy_fs_struct);
>
> -static int copy_fs(unsigned long clone_flags, struct task_struct *tsk)
> +static inline int copy_fs(unsigned long clone_flags,
> + struct task_struct * src, struct task_struct * tsk)
> {
> if (clone_flags & CLONE_FS) {
> - atomic_inc(&current->fs->count);
> + atomic_inc(&src->fs->count);
> return 0;
> }
> - tsk->fs = __copy_fs_struct(current->fs);
> + tsk->fs = __copy_fs_struct(src->fs);
> if (!tsk->fs)
> return -ENOMEM;
> return 0;
> @@ -965,6 +966,30 @@ static void rt_mutex_init_task(struct task_struct *p)
> #endif
> }
>
> +void copy_hijackable_taskinfo(struct task_struct *p,
> + struct task_struct *task)
> +{
> + p->uid = task->uid;
> + p->euid = task->euid;
> + p->suid = task->suid;
> + p->fsuid = task->fsuid;
> + p->gid = task->gid;
> + p->egid = task->egid;
> + p->sgid = task->sgid;
> + p->fsgid = task->fsgid;
> + p->cap_effective = task->cap_effective;
> + p->cap_inheritable = task->cap_inheritable;
> + p->cap_permitted = task->cap_permitted;
> + p->keep_capabilities = task->keep_capabilities;
> + p->user = task->user;
> + p->nsproxy = task->nsproxy;
> + /*
> + * TODO: continue taking relevant pieces from
> + * hijacked task, starting at:
> + *   key info
> + */
> +}
> +
> /*
> * This creates a new process as a copy of the old one,

```

```

> * but does not actually start it yet.
> @@ -973,7 +998,8 @@ static void rt_mutex_init_task(struct task_struct *p)
> * parts of the process environment (as per the clone
> * flags). The actual kick-off is left to the caller.
> */
> -static struct task_struct *copy_process(unsigned long clone_flags,
> +static struct task_struct *copy_process(struct task_struct *task,
> + unsigned long clone_flags,
> + unsigned long stack_start,
> + struct pt_regs *regs,
> + unsigned long stack_size,
> @@ -1010,12 +1036,17 @@ static struct task_struct *copy_process(unsigned long clone_flags,
> p = dup_task_struct(current);
> if (!p)
> goto fork_out;
> + if (current != task) {
> + copy_hijackable_taskinfo(p, task);
> + }
>
> rt_mutex_init_task(p);
>
> #ifdef CONFIG_TRACE_IRQFLAGS
> - DEBUG_LOCKS_WARN_ON(!p->hardirqs_enabled);
> - DEBUG_LOCKS_WARN_ON(!p->softirqs_enabled);
> + if (task == current) {
> + DEBUG_LOCKS_WARN_ON(!p->hardirqs_enabled);
> + DEBUG_LOCKS_WARN_ON(!p->softirqs_enabled);
> + }
> #endif
> retval = -EAGAIN;
> if (atomic_read(&p->user->processes) >=
> @@ -1084,7 +1115,7 @@ static struct task_struct *copy_process(unsigned long clone_flags,
> #endif
> p->io_context = NULL;
> p->audit_context = NULL;
> - cgroup_fork(p);
> + cgroup_fork(task, p);
> #ifdef CONFIG_NUMA
> p->mempolicy = mpol_copy(p->mempolicy);
> if (IS_ERR(p->mempolicy)) {
> @@ -1132,7 +1163,7 @@ static struct task_struct *copy_process(unsigned long clone_flags,
> goto bad_fork_cleanup_audit;
> if ((retval = copy_files(clone_flags, p)))
> goto bad_fork_cleanup_semundo;
> - if ((retval = copy_fs(clone_flags, p)))
> + if ((retval = copy_fs(clone_flags, task, p)))
> goto bad_fork_cleanup_files;
> if ((retval = copy_sighand(clone_flags, p)))

```

```

> goto bad_fork_cleanup_fs;
> @@ -1164,7 +1195,7 @@ static struct task_struct *copy_process(unsigned long clone_flags,
> p->pid = pid_nr(pid);
> p->tgid = p->pid;
> if (clone_flags & CLONE_THREAD)
> - p->tgid = current->tgid;
> + p->tgid = task->tgid;
>
> p->set_child_tid = (clone_flags & CLONE_CHILD_SETTID) ? child_tidptr : NULL;
> /*
> @@ -1379,7 +1410,7 @@ struct task_struct * __cpuinit fork_idle(int cpu)
> struct task_struct *task;
> struct pt_regs regs;
>
> - task = copy_process(CLONE_VM, 0, idle_regs(&regs), 0, NULL,
> + task = copy_process(current, CLONE_VM, 0, idle_regs(&regs), 0, NULL,
>   &init_struct_pid);
> if (!IS_ERR(task))
>   init_idle(task, cpu);
> @@ -1404,12 +1435,12 @@ static int fork_traceflag(unsigned clone_flags)
> }
>
> /*
> - * Ok, this is the main fork-routine.
> - *
> - * It copies the process, and if successful kick-starts
> - * it and waits for it to finish using the VM if required.
> + * if called with task!=current, then caller must ensure that
> + * 1. it has a reference to task
> + * 2. current must have ptrace permission to task
> */
> -long do_fork(unsigned long clone_flags,
> +long do_fork_task(struct task_struct *task,
> + unsigned long clone_flags,
>   unsigned long stack_start,
>   struct pt_regs *regs,
>   unsigned long stack_size,
> @@ -1420,13 +1451,23 @@ long do_fork(unsigned long clone_flags,
> int trace = 0;
> long nr;
>
> + if (task != current) {
> + /* sanity checks */
> + /* we only want to allow hijacking the simplest cases */
> + if (clone_flags & CLONE_SYSVSEM)
> + return -EINVAL;
> + if (current->ptrace)
> + return -EPERM;

```

```

> + if (task->ptrace)
> + return -EINVAL;
> + }
> if (unlikely(current->ptrace)) {
> trace = fork_traceflag (clone_flags);
> if (trace)
> clone_flags |= CLONE_PTRACE;
> }
>
> - p = copy_process(clone_flags, stack_start, regs, stack_size,
> + p = copy_process(task, clone_flags, stack_start, regs, stack_size,
> child_tidptr, NULL);
> /*
> * Do this prior waking up the new thread - the thread pointer
> @@ -1481,6 +1522,23 @@ long do_fork(unsigned long clone_flags,
> return nr;
> }
>
> +/*
> + * Ok, this is the main fork-routine.
> + *
> + * It copies the process, and if successful kick-starts
> + * it and waits for it to finish using the VM if required.
> + */
> +long do_fork(unsigned long clone_flags,
> + unsigned long stack_start,
> + struct pt_regs *regs,
> + unsigned long stack_size,
> + int __user *parent_tidptr,
> + int __user *child_tidptr)
> +{
> + return do_fork_task(current, clone_flags, stack_start,
> + regs, stack_size, parent_tidptr, child_tidptr);
> +}
> +
> #ifndef ARCH_MIN_MMSTRUCT_ALIGN
> #define ARCH_MIN_MMSTRUCT_ALIGN 0
> #endif
> diff --git a/kernel/ptrace.c b/kernel/ptrace.c
> index 7c76f2f..c65c9fe 100644
> --- a/kernel/ptrace.c
> +++ b/kernel/ptrace.c
> @@ -159,6 +159,13 @@ int ptrace_may_attach(struct task_struct *task)
> return !err;
> }
>
> +int ptrace_may_attach_locked(struct task_struct *task)
> +{

```

```
> + int err;
> + err = may_attach(task);
> + return !err;
> +}
> +
> int ptrace_attach(struct task_struct *task)
> {
> int retval;
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [PATCH] namespaces: introduce sys_hijack (v8)
Posted by [Mark Nelson](#) on Mon, 05 Nov 2007 05:18:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Serge,

Quick fix (feel free to just fold it into your patch). There may be a smarter way of fixing this, but this worked for -lxc...

Thanks!

Mark.

ERR_PTR is now used in cgroup code so we need to include err.h

This fixes the build error with CGROUPS disabled:

```
In file included from include/linux/cpuset.h:14,
                 from mm/slub.c:19:
include/linux/cgroup.h: In function 'task_from_cgroup_fd':
include/linux/cgroup.h:329: error: implicit declaration of function 'ERR_PTR'
include/linux/cgroup.h:329: warning: return makes pointer from integer without a cast
make[2]: *** [mm/slub.o] Error 1
make[1]: *** [mm] Error 2
make: *** [sub-make] Error 2
```

Signed-off-by: Mark Nelson <markn@au1.ibm.com>

```
include/linux/cgroup.h | 1 +
1 file changed, 1 insertion(+)
```

Index: linux/include/linux/cgroup.h

=====

```
--- linux.orig/include/linux/cgroup.h  
+++ linux/include/linux/cgroup.h  
@@ -14,6 +14,7 @@  
#include <linux/nodemask.h>  
#include <linux/rcupdate.h>  
#include <linux/cgroupstats.h>  
+#include <linux/err.h>
```

```
#ifdef CONFIG_CGROUPS
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
