
Subject: [PATCH] proc: use BUG_ON() in de_put()
Posted by [Alexey Dobriyan](#) on Thu, 15 Nov 2007 16:12:49 GMT
[View Forum Message](#) <> [Reply to Message](#)

It's much more visible that some printk. I still has an unexplained oops
in proc, so let's leave it for a while.

Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>

```
fs/proc/inode.c | 7 +-----  
1 file changed, 1 insertion(+), 6 deletions(-)
```

```
--- a/fs/proc/inode.c  
+++ b/fs/proc/inode.c  
@@ -37,12 +37,7 @@ void de_put(struct proc_dir_entry *de)  
{  
    if (de) {  
        lock_kernel();  
-    if (!atomic_read(&de->count)) {  
-    printk("de_put: entry %s already free!\n", de->name);  
-    unlock_kernel();  
-    return;  
- }  
-  
+    BUG_ON(atomic_read(&de->count) == 0);  
    if (atomic_dec_and_test(&de->count)) {  
        if (de->deleted) {  
            printk("de_put: deferred delete of %s\n",
```

Subject: Re: [PATCH] proc: use BUG_ON() in de_put()
Posted by [akpm](#) on Fri, 16 Nov 2007 21:46:42 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Thu, 15 Nov 2007 19:12:49 +0300
Alexey Dobriyan <adobriyan@sw.ru> wrote:

> It's much more visible that some printk. I still has an unexplained oops
> in proc, so let's leave it for a while.

>
> Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>

> ---

>
> fs/proc/inode.c | 7 +-----
> 1 file changed, 1 insertion(+), 6 deletions(-)

>
> --- a/fs/proc/inode.c

```

> +++ b/fs/proc/inode.c
> @@ -37,12 +37,7 @@ void de_put(struct proc_dir_entry *de)
> {
> if (de) {
> lock_kernel();
> - if (!atomic_read(&de->count)) {
> - printk("de_put: entry %s already free!\n", de->name);
> - unlock_kernel();
> - return;
> - }
> -
> + BUG_ON(atomic_read(&de->count) == 0);
> if (atomic_dec_and_test(&de->count)) {
> if (de->deleted) {
> printk("de_put: deferred delete of %s\n",

```

I don't see that an error in here `_requires_` that we nuke the machine. Surely we can emit a warning and then recover in some fashion?

Subject: Re: [PATCH] proc: use BUG_ON() in de_put()
 Posted by [Alexey Dobriyan](#) on Thu, 22 Nov 2007 08:49:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Fri, Nov 16, 2007 at 01:46:42PM -0800, Andrew Morton wrote:

```

> On Thu, 15 Nov 2007 19:12:49 +0300
> Alexey Dobriyan <adobriyan@sw.ru> wrote:
>
> > It's much more visible that some printk. I still has an unexplained oops
> > in proc, so let's leave it for a while.

```

```

> > --- a/fs/proc/inode.c
> > +++ b/fs/proc/inode.c
> > @@ -37,12 +37,7 @@ void de_put(struct proc_dir_entry *de)
> > {
> > if (de) {
> > lock_kernel();
> > - if (!atomic_read(&de->count)) {
> > - printk("de_put: entry %s already free!\n", de->name);
> > - unlock_kernel();
> > - return;
> > - }
> > -
> > + BUG_ON(atomic_read(&de->count) == 0);
> > if (atomic_dec_and_test(&de->count)) {
> > if (de->deleted) {
> > printk("de_put: deferred delete of %s\n",
>

```

> I don't see that an error in here `_requires_` that we nuke the machine.
> Surely we can emit a warning and then recover in some fashion?

0 => -1 transition, google says this check triggered only once. I think we should just drop it.
