
Subject: [PATCH net-2.6.25 6/6][CORE] Remove the empty net_table

Posted by [Pavel Emelianov](#) on Sat, 01 Dec 2007 13:11:28 GMT

[View Forum Message](#) <> [Reply to Message](#)

I have removed all the entries from this table (core_table, ipv4_table and tr_table), so now we can safely drop it.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/include/linux/net.h b/include/linux/net.h
```

```
index f95f12c..c414d90 100644
```

```
--- a/include/linux/net.h
```

```
+++ b/include/linux/net.h
```

```
@@ -337,7 +337,6 @@ static const struct proto_ops name##_ops = { \
```

```
#ifdef CONFIG_SYSCTL
```

```
#include <linux/sysctl.h>
```

```
-extern ctl_table net_table[];
```

```
extern int net_msg_cost;
```

```
extern int net_msg_burst;
```

```
#endif
```

```
diff --git a/kernel/sysctl.c b/kernel/sysctl.c
```

```
index 946a01c..894a177 100644
```

```
--- a/kernel/sysctl.c
```

```
+++ b/kernel/sysctl.c
```

```
@@ -199,14 +199,6 @@ static struct ctl_table root_table[] = {
```

```
    .mode = 0555,
```

```
    .child = vm_table,
```

```
},
```

```
-#ifdef CONFIG_NET
```

```
- {
```

```
-    .ctl_name = CTL_NET,
```

```
-    .procname = "net",
```

```
-    .mode = 0555,
```

```
-    .child = net_table,
```

```
- },
```

```
-#endif
```

```
{
```

```
    .ctl_name = CTL_FS,
```

```
    .procname = "fs",
```

```
diff --git a/net/sysctl_net.c b/net/sysctl_net.c
```

```
index 16ad14b..665e856 100644
```

```
--- a/net/sysctl_net.c
```

```
+++ b/net/sysctl_net.c
```

```
@@ -30,10 +30,6 @@
```

```
#include <linux/if_tr.h>
```

#endif

-struct ctl_table net_table[] = {

- { 0 },

-};

-

static struct list_head *

net_ctl_header_lookup(struct ctl_table_root *root, struct nsproxy *namespaces)

{

--

1.5.3.4
