

---

Subject: Re: namespace support requires network modules to say "GPL"

Posted by [ebiederm](#) on Sun, 02 Dec 2007 01:14:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Jiri Slaby <jirislaby@gmail.com> writes:

```
> On 12/02/2007 12:13 AM, Eric W. Biederman wrote:
>> Mark Lord <lkml@rtr.ca> writes:
>>> Fine. But all of them want to call sk_alloc(),
>>
>> network drivers should be calling sk_alloc less then they should
>> call dev_get_by_XXXX. Only protocols call sk_alloc.
>>
>>> and many want to do register_netdev().
>>
>> I haven't even touched register_netdev.
>>
>>> So what should they be using there ?
>>
>> What are you having problems with?
>>
>> It is hard to answer specific questions without a context.
>
> VMware vmnet.
```

With a quick glance in that direction it appears to the result of a design bug in vmnet that they call sk\_alloc at all, and someone seems to have found a work around in vmnet for this situation.

My gut feel is that vmware should just use tun or tap (whichever is the appropriate one), and be done with it.

Eric

---

Containers mailing list

[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---