
Subject: [patch 02/38][IPV6] Makefile - Activate netns configuration when sysctl is off

Posted by [Daniel Lezcano](#) on Mon, 03 Dec 2007 16:16:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

Sysctl per namespace is not yet finished, like sysfs. In order to avoid problems related with that, I disable netns if sysctl is compiled in the kernel.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

Signed-off-by: Benjamin Thery <benjamin.thery@bull.net>

net/Kconfig | 2 +-
1 file changed, 1 insertion(+), 1 deletion(-)

Index: linux-2.6-netns/net/Kconfig

--- linux-2.6-netns.orig/net/Kconfig

+++ linux-2.6-netns/net/Kconfig

@@ -30,7 +30,7 @@ menu "Networking options"

config NET_NS

bool "Network namespace support"

default n

- depends on EXPERIMENTAL && !SYSFS

+ depends on EXPERIMENTAL && !SYSFS && !SYSCTL

help

Allow user space to create what appear to be multiple instances
of the network stack.

--

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
