
Subject: [patch 25/38][IPV6] route6 - create route6 proc files for the namespace

Posted by [Daniel Lezcano](#) on Mon, 03 Dec 2007 16:17:01 GMT

[View Forum Message](#) <> [Reply to Message](#)

Make /proc/net/ipv6_route and /proc/net/rt6_stats to be per namespace.
These proc files are now created when the network namespace is initialized.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

Signed-off-by: Benjamin Thery <benjamin.thery@bull.net>

```
net/ipv6/route.c | 27 ++++++-----
1 file changed, 21 insertions(+), 6 deletions(-)
```

Index: linux-2.6-netns/net/ipv6/route.c

=====

--- linux-2.6-netns.orig/net/ipv6/route.c

+++ linux-2.6-netns/net/ipv6/route.c

```
@@ -2486,6 +2486,24 @@ ctl_table ipv6_route_table[] = {
```

```
#endif
```

```
+static int ip6_route_net_init(struct net *net)
```

```
+{
```

```
+ proc_net_fops_create(net, "ipv6_route", 0, &ipv6_route_proc_fops);
```

```
+ proc_net_fops_create(net, "rt6_stats", S_IRUGO, &rt6_stats_seq_fops);
```

```
+ return 0;
```

```
+}
```

```
+
```

```
+static void ip6_route_net_exit(struct net *net)
```

```
+{
```

```
+ proc_net_remove(net, "ipv6_route");
```

```
+ proc_net_remove(net, "rt6_stats");
```

```
+}
```

```
+
```

```
+static struct pernet_operations ip6_route_net_ops = {
```

```
+ .init = ip6_route_net_init,
```

```
+ .exit = ip6_route_net_exit,
```

```
+};
```

```
+
```

```
void __init ip6_route_init(void)
```

```
{
```

```
ip6_dst_ops.kmem_cachep =
```

```
@@ -2493,9 +2511,8 @@ void __init ip6_route_init(void)
```

```
SLAB_HWCACHE_ALIGN|SLAB_PANIC, NULL);
```

```
ip6_dst_blackhole_ops.kmem_cachep = ip6_dst_ops.kmem_cachep;
```

```
+ register_pernet_subsys(&ip6_route_net_ops);
```

```
fib6_init();
```

```
- proc_net_fops_create(&init_net, "ipv6_route", 0, &ipv6_route_proc_fops);
- proc_net_fops_create(&init_net, "rt6_stats", S_IRUGO, &rt6_stats_seq_fops);
#ifdef CONFIG_XFRM
    xfrm6_init();
#endif
@@ -2510,13 +2527,11 @@ void __init ip6_route_init(void)

void ip6_route_cleanup(void)
{
+ unregister_pernet_subsys(&ip6_route_net_ops);
+
#ifdef CONFIG_IPV6_MULTIPLE_TABLES
    fib6_rules_cleanup();
#endif
-#ifdef CONFIG_PROC_FS
- proc_net_remove(&init_net, "ipv6_route");
- proc_net_remove(&init_net, "rt6_stats");
-#endif
#ifdef CONFIG_XFRM
    xfrm6_fini();
#endif

--
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
