
Subject: [patch 32/38][IPV6] rt6_info - dynamically allocate rt6_info

Posted by [Daniel Lezcano](#) on Mon, 03 Dec 2007 16:17:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

The rt6_info structure are no longer a global static variable but a dynamically allocated structure.

In order to facilitate future multiple instantiations of rt6_info structures when multiple network namespaces will be supported, a global static variable is still present as template for rt6_info structure initialization.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

Signed-off-by: Benjamin Thery <benjamin.thery@bull.net>

net/ipv6/route.c | 67 ++++++++++++++++++++++++++++++++++++++-----
1 file changed, 47 insertions(+), 20 deletions(-)

Index: linux-2.6-netns/net/ipv6/route.c

=====

--- linux-2.6-netns.orig/net/ipv6/route.c

+++ linux-2.6-netns/net/ipv6/route.c

@@ -132,7 +132,7 @@ static struct dst_ops ip6_dst_blackhole_
.entry_size = sizeof(struct rt6_info),
};

-static struct rt6_info __ip6_null_entry = {

+static struct rt6_info ip6_null_entry_template = {

.u = {

.dst = {

.__refcnt = ATOMIC_INIT(1),

@@ -143,7 +143,6 @@ static struct rt6_info __ip6_null_entry

.input = ip6_pkt_discard,

.output = ip6_pkt_discard_out,

.ops = &ip6_dst_ops,

- .path = (struct dst_entry*)&__ip6_null_entry,

}

},

.rt6i_flags = (RTF_REJECT | RTF_NONEXTHOP),

@@ -151,35 +150,34 @@ static struct rt6_info __ip6_null_entry

.rt6i_ref = ATOMIC_INIT(1),

};

-struct rt6_info *ip6_null_entry = &__ip6_null_entry;

+struct rt6_info *ip6_null_entry;

#ifdef CONFIG_IPV6_MULTIPLE_TABLES

static int ip6_pkt_prohibit(struct sk_buff *skb);

```
static int ip6_pkt_prohibit_out(struct sk_buff *skb);
```

```
-struct rt6_info __ip6_prohibit_entry = {
+struct rt6_info ip6_prohibit_entry_template = {
    .u = {
        .dst = {
            - .__refcnt = ATOMIC_INIT(1),
            - .__use = 1,
            - .obsolete = -1,
            - .error = -EACCES,
            - .metrics = { [RTAX_HOPLIMIT - 1] = 255, },
            - .input = ip6_pkt_prohibit,
            - .output = ip6_pkt_prohibit_out,
            - .ops = &ip6_dst_ops,
            - .path = (struct dst_entry*)&__ip6_prohibit_entry,
+        .__refcnt = ATOMIC_INIT(1),
+        .__use = 1,
+        .obsolete = -1,
+        .error = -EACCES,
+        .metrics = { [RTAX_HOPLIMIT - 1] = 255, },
+        .input = ip6_pkt_prohibit,
+        .output = ip6_pkt_prohibit_out,
+        .ops = &ip6_dst_ops,
        }
    },
    - .rt6i_flags = (RTF_REJECT | RTF_NONEXTHOP),
    - .rt6i_metric = ~(u32) 0,
    - .rt6i_ref = ATOMIC_INIT(1),
+    .rt6i_flags = (RTF_REJECT | RTF_NONEXTHOP),
+    .rt6i_metric = ~(u32) 0,
+    .rt6i_ref = ATOMIC_INIT(1),
};
```

```
-struct rt6_info *ip6_prohibit_entry = &__ip6_prohibit_entry;
+struct rt6_info *ip6_prohibit_entry;
```

```
-static struct rt6_info __ip6_blk_hole_entry = {
+static struct rt6_info ip6_blk_hole_entry_template = {
    .u = {
        .dst = {
            .__refcnt = ATOMIC_INIT(1),
@@ -190,7 +188,6 @@ static struct rt6_info __ip6_blk_hole_en
        .input = dst_discard,
        .output = dst_discard,
        .ops = &ip6_dst_ops,
    - .path = (struct dst_entry*)&__ip6_blk_hole_entry,
    }
},
```

```

    .rt6i_flags = (RTF_REJECT | RTF_NONEXTHOP),
@@ -198,7 +195,7 @@ static struct rt6_info __ip6_blk_hole_en
    .rt6i_ref = ATOMIC_INIT(1),
};

-struct rt6_info *ip6_blk_hole_entry = &__ip6_blk_hole_entry;
+struct rt6_info *ip6_blk_hole_entry;

#endif

@@ -2534,6 +2531,32 @@ static struct pernet_operations ip6_rout

void __init ip6_route_init(void)
{
+ ip6_null_entry = kzalloc(sizeof(*ip6_null_entry), GFP_KERNEL);
+ if (!ip6_null_entry)
+ panic("IPV6: cannot allocate ip6_null_entry\n");
+
+ memcpy(ip6_null_entry, &ip6_null_entry_template,
+        sizeof(*ip6_null_entry));
+ ip6_null_entry->u.dst.path = (struct dst_entry*)ip6_null_entry;
+
+ #ifdef CONFIG_IPV6_MULTIPLE_TABLES
+ ip6_prohibit_entry = kzalloc(sizeof(*ip6_prohibit_entry), GFP_KERNEL);
+ if (!ip6_prohibit_entry)
+ panic("IPV6: cannot allocate ip6_prohibit_entry\n");
+
+ memcpy(ip6_prohibit_entry, &ip6_prohibit_entry_template,
+        sizeof(*ip6_prohibit_entry));
+ ip6_prohibit_entry->u.dst.path = (struct dst_entry*)ip6_prohibit_entry;
+
+ ip6_blk_hole_entry = kzalloc(sizeof(*ip6_blk_hole_entry), GFP_KERNEL);
+ if (!ip6_blk_hole_entry)
+ panic("IPV6: panic cannot allocate ip6_blk_hole_entry\n");
+
+ memcpy(ip6_blk_hole_entry, &ip6_blk_hole_entry_template,
+        sizeof(*ip6_blk_hole_entry));
+ ip6_blk_hole_entry->u.dst.path = (struct dst_entry*)ip6_blk_hole_entry;
+ #endif
+
    ip6_dst_ops.kmem_cachep =
        kmem_cache_create("ip6_dst_cache", sizeof(struct rt6_info), 0,
            SLAB_HWCACHE_ALIGN|SLAB_PANIC, NULL);
@@ -2566,4 +2589,8 @@ void ip6_route_cleanup(void)
    rt6_ifdown(NULL);
    fib6_gc_cleanup();
    kmem_cache_destroy(ip6_dst_ops.kmem_cachep);
+

```

```
+ kfree(ip6_null_entry);  
+ kfree(ip6_prohibit_entry);  
+ kfree(ip6_blk_hole_entry);  
}
```

--

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
