
Subject: [patch 35/38][IPV6] addrconf - Add a network namespace parameter to
addrconf_forward_change

Posted by [Daniel Lezcano](#) on Mon, 03 Dec 2007 16:17:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

Add a network namespace parameter to addrconf_forward_change to
remove reference to init_net and make it more generic.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

Signed-off-by: Benjamin Thery <benjamin.thery@bull.net>

net/ipv6/addrconf.c | 8 ++++----

1 file changed, 4 insertions(+), 4 deletions(-)

Index: linux-2.6-netns/net/ipv6/addrconf.c

=====

--- linux-2.6-netns.orig/net/ipv6/addrconf.c

+++ linux-2.6-netns/net/ipv6/addrconf.c

@ @ -451,13 +451,13 @ @ static void dev_forward_change(struct in
{

-static void addrconf_forward_change(void)

+static void addrconf_forward_change(struct net *net)

{
 struct net_device *dev;
 struct inet6_dev *idev;

 read_lock(&dev_base_lock);

- for_each_netdev(&init_net, dev) {

+ for_each_netdev(net, dev) {

 rcu_read_lock();

 idev = __in6_dev_get(dev);

 if (idev) {

@ @ -3808,7 +3808,7 @ @ int addrconf_sysctl_forward(ctl_table *c
 }

 } else {

 ipv6_devconf_dflt.forwarding = ipv6_devconf.forwarding;

- addrconf_forward_change();

+ addrconf_forward_change(&init_net);

 }

 if (*valp)

 rt6_purge_dflt_routers(&init_net);

@ @ -3860,7 +3860,7 @ @ static int addrconf_sysctl_forward_strat
 dev_forward_change(idev);

 } else {

 *valp = new;

- addrconf_forward_change();

```
+ addrconf_forward_change(&init_net);  
}  
  
if (*valp)
```

```
--
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
