
Subject: perl LOCALE issue- and solution

Posted by [Michael Klatsky](#) on Fri, 07 Dec 2007 18:15:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello all-

I ran into a puzzling issue and found a solution- but I am wondering what the root cause really was, and whether others have run into this:

After create a VE using the repo provided centos-4-i386-default template, I entered the VE via ssh. When running perl (any perl script), I got the message:

```
perl: warning: Setting locale failed.  
perl: warning: Please check that your locale settings:  
    LANGUAGE = "en_US:en",  
    LC_ALL = (unset),  
    LANG = "en_US"  
are supported and installed on your system.  
perl: warning: Falling back to the standard locale ("C")
```

After doing a bit of hunting on methods to set this, including these pages:

<http://www.in-ulm.de/~mascheck/locale/#short>

<http://perldoc.perl.org/perllocale.html#Permanently-fixing-your-system's-locale-configuration>

I started looking closely at glibc-common, as when I did "locale -a" I got the message that locale directories could not be found.

I checked, and indeed- rpm -q glibc-common reported that the package was installed. However, after checking some of the files included that should have existed, I found that the local dirs were not there (example: /usr/lib/locale/en_US/LC_TIME). So, I grabbed the glibc-common rpm and did a rpm -ivh --force, and voila- all was properly installed.

The purpose of my post is to document this for others who may have run into this, and to solicit any theories as to why that package was "phantomly" installed. Significantly, other than the locale issue- the system was operating properly.

Thanks- and so far quite impressed

--

Sincerely,

Michael

Subject: Re: perl LOCALE issue- and solution
Posted by [dev](#) on Mon, 10 Dec 2007 11:55:07 GMT
[View Forum Message](#) <> [Reply to Message](#)

was it -minimal template?

Some of templates AFAIK have removed locales,
since locales take really much space (~20Mb) while not needed in most cases
(except for the default C one).

Thanks,
Kirill

Michael Klatsky wrote:

> Hello all-

>
> I ran into a puzzling issue and found a solution- but I am wondering
> what the root cause really was, and whether others have run into this:
>
> After create a VE using the repo provided centos-4-i386-default
> template, I entered the VE via ssh. When running perl (any perl
> script), I got the message:
>
> perl: warning: Setting locale failed.
> perl: warning: Please check that your locale settings:
> LANGUAGE = "en_US:en",
> LC_ALL = (unset),
> LANG = "en_US"
> are supported and installed on your system.
> perl: warning: Falling back to the standard locale ("C")
>
> After doing a bit of hunting on methods to set this, including these pages:
> <http://www.in-ulm.de/~mascheck/locale/#short>
> <http://perldoc.perl.org/perllocale.html#Permanently-fixing-your-system's-locale-configuration>
>
> I started looking closely at glibc-common, as when I did "locale -a" I
> got the message that locale directories could not be found.
>
> I checked, and indeed- rpm -q glibc-common reported that the package
> was installed. However, after checking some of the files included that
> should have existed, I found that the local dirs were not there
> (example: /usr/lib/locale/en_US/LC_TIME). So, I grabbed the
> glibc-common rpm and did a rpm -ivh --force, and voila- all was
> properly installed.
>

> The purpose of my post is to document this for others who may have run
> into this, and to solicit any theories as to why that package was
> "phantomly" installed. Significantly, other than the locale issue- the
> system was operating properly.
>
> Thanks- and so far quite impressed
>
>

Subject: Re: perl LOCALE issue- and solution
Posted by [Thorsten Schifferdeck](#) on Mon, 10 Dec 2007 12:30:27 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

or Disable overriding LC_* variables in /etc/ssh/sshd_config:

```
# Allow client to pass locale environment variables
AcceptEnv LANG LC_*
```

```
to
#AcceptEnv LANG LC_*
```

so default LC is used.

Regards,
Thorsten

Am Mo, 10.12.2007, 12:55, schrieb Kirill Korotaev:

> was it -minimal template?
> Some of templates AFAIK have removed locales,
> since locales take really much space (~20Mb) while not needed in most
> cases
> (except for the default C one).

>
> Thanks,
> Kirill

>
> Michael Klatsky wrote:
>> Hello all-

>>
>> I ran into a puzzling issue and found a solution- but I am wondering
>> what the root cause really was, and whether others have run into this:
>>

>> After create a VE using the repo provided centos-4-i386-default
>> template, I entered the VE via ssh. When running perl (any perl

>> script), I got the message:
>>
>> perl: warning: Setting locale failed.
>> perl: warning: Please check that your locale settings:
>> LANGUAGE = "en_US:en",
>> LC_ALL = (unset),
>> LANG = "en_US"
>> are supported and installed on your system.
>> perl: warning: Falling back to the standard locale ("C")
>>
>> After doing a bit of hunting on methods to set this, including these
>> pages:
>> <http://www.in-ulm.de/~mascheck/locale/#short>
>> <http://perldoc.perl.org/perllocale.html#Permanently-fixing-your-system's-locale-configuration>
>>
>> I started looking closely at glibc-common, as when I did "locale -a" I
>> got the message that locale directories could not be found.
>>
>> I checked, and indeed- rpm -q glibc-common reported that the package
>> was installed. However, after checking some of the files included that
>> should have existed, I found that the local dirs were not there
>> (example: /usr/lib/locale/en_US/LC_TIME). So, I grabbed the
>> glibc-common rpm and did a rpm -ivh --force, and voila- all was
>> properly installed.
>>
>> The purpose of my post is to document this for others who may have run
>> into this, and to solicit any theories as to why that package was
>> "phantomly" installed. Significantly, other than the locale issue- the
>> system was operating properly.
>>
>> Thanks- and so far quite impressed
>>
>>
>
--
Thorsten Schifferdecker
email ts@sysys.org
phone +49 (0) 911 50 63 69 82

Subject: Re: perl LOCALE issue- and solution
Posted by [dev](#) on Mon, 10 Dec 2007 17:43:22 GMT
[View Forum Message](#) <> [Reply to Message](#)

Added: http://wiki.openvz.org/Locales_inside_VE
Thorsten, thanks for this info - never knew about ssh overrides.

Thanks,

Kirill

Thorsten Schifferdecker wrote:

```
> Hi,
>
> or Disable overrideing LC_* variables in /etc/ssh/sshd_config:
>
> # Allow client to pass locale environment variables
> AcceptEnv LANG LC_*
>
> to
> #AcceptEnv LANG LC_*
>
> so default LC ist used.
>
> Regards,
> Thorsten
>
> Am Mo, 10.12.2007, 12:55, schrieb Kirill Korotaev:
>
>>was it -minimal template?
>>Some of templates AFAIK have removed locales,
>>since locales take really much space (~20Mb) while not needed in most
>>cases
>>(except for the default C one).
>>
>>Thanks,
>>Kirill
>>
>>
>>Michael Klatsky wrote:
>>
>>>Hello all-
>>>
>>>I ran into a puzzling issue and found a solution- but I am wondering
>>>what the root cause really was, and whether others have run into this:
>>>
>>>After create a VE using the repo provided centos-4-i386-default
>>>template, I entered the VE via ssh. When running perl (any perl
>>>script), I got the message:
>>>
>>>perl: warning: Setting locale failed.
>>>perl: warning: Please check that your locale settings:
>>>    LANGUAGE = "en_US:en",
>>>    LC_ALL = (unset),
>>>    LANG = "en_US"
>>> are supported and installed on your system.
>>>perl: warning: Falling back to the standard locale ("C")
```

>>>
>>>After doing a bit of hunting on methods to set this, including these
>>>pages:
>>><http://www.in-ulm.de/~mascheck/locale/#short>
>>><http://perldoc.perl.org/perllocale.html#Permanently-fixing-your-system's-locale-configuration>
>>>
>>>I started looking closely at glibc-common, as when I did "locale -a" I
>>>got the message that locale directories could not be found.
>>>
>>>I checked, and indeed- rpm -q glibc-common reported that the package
>>>was installed. However, after checking some of the files included that
>>>should have existed, I found that the local dirs were not there
>>>(example: /usr/lib/locale/en_US/LC_TIME). So, I grabbed the
>>>glibc-common rpm and did a rpm -ivh --force, and voila- all was
>>>properly installed.
>>>
>>>The purpose of my post is to document this for others who may have run
>>>into this, and to solicit any theories as to why that package was
>>>"phantomly" installed. Significantly, other than the locale issue- the
>>>system was operating properly.
>>>
>>>Thanks- and so far quite impressed
>>>
>>>
>>
