
Subject: multiple NICs on Different Networks with different default gateways

Posted by [zerodni](#) on Wed, 19 Apr 2006 14:29:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

I have a Openvz host box that has 3 NICs in it on three different networks. I'm trying to setup vps's to connect to different default gateways depending on what ip address i have given them. For example one vps is setup with a ip address of 192.168.1.25 with the default gateway of that network being 192.168.1.1 and another vps is setup with the ip address 192.168.2.25 with the default gateway of that network being 192.168.2.1. When i setup the vps now i can connect to them from the out side world no problem. But inside the vps i cant ping out if the the vps network is different than the network where i setup my default gateway on the host. For example my default gateway on the host is setup with 192.168.1.1 and the vps on 192.168.1.25 can get out but the vps on 192.168.2.25 can't ping out but i can ping in to both of them from the out side network

Thanks for any Help that you can give me

Subject: Re: multiple NICs on Different Networks with different default gateways

Posted by [dev](#) on Thu, 20 Apr 2006 08:10:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

I suppose you need SRC routing:

http://forum.openvz.org/index.php?t=msg&goto=1631&&a mp;a mp;srch=src+routing#msg_1631

does it help?

Subject: Re: multiple NICs on Different Networks with different default gateways

Posted by [zerodni](#) on Thu, 20 Apr 2006 15:53:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

that would work for one ip but im really looking for a way to have all vps with the ip of 192.168.2 as their network go to the gateway of 192.168.2.1 with out having to setup a route on the host for every ip address used on the gateway that solution would work if it was just one vps that need to have a different default gateway but there will be lots of vps being created and destroyed on the three different networks and keeping up with the ip src routes by hand would not be feasible the main thing im looking for is all vps on this subnet of 192.168.2.0 will go to the gateway of 192.168.2.1 and the same for the 192.168.1.0 going to the gateway of 192.168.1.1 i tried something like this

<http://www.debian-administration.org/articles/377>

but it messed up something in openvz

Thanks

Subject: Re: multiple NICs on Different Networks with different default gateways

Posted by [dev](#) on Fri, 21 Apr 2006 08:38:46 GMT

[View Forum Message](#) <> [Reply to Message](#)

what prevents you from netmask?
just specify not a single IP, but IP/netmask
Or did I get something wrong?

Subject: Re: multiple NICs on Different Networks with different default gateways
Posted by [zerodni](#) on Fri, 21 Apr 2006 15:29:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

the main reason is that i have have three backbones that the server is connected to and i want to have vps on each backbone and having no connection to the others for example i want to make a vps on the the 192.168.1.1 network because that will be a box on the trusted network on its own backbone for example a T1 line then make another vps on the 192.168.2.1 network that is the oc-48 line and another vps on the 192.168.3.1 network that is a T-3 line and if the T1 dies i don't want the servers setup on the oc-48 line to stop working just because i have the t-1 line set as my default gateway. and i want to make allot of these vps on the different networks as needed

Thanks for all your help

Subject: Re: multiple NICs on Different Networks with different default gateways
Posted by [dev](#) on Sat, 22 Apr 2006 08:16:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

do you want VPS using T1 to switch to oc-48/T3 if T1 dies?
if not, this is exactly what I suggested.

you setup a rules, so that:

1. all IPs 192.168.1.0/24 go through 192.168.1.1 (T1)
2. all IPs 192.168.2.0/24 go through 192.168.2.1 (oc-48)
2. all IPs 192.168.3.0/24 go through 192.168.3.1 (T3)

and that's it.

The only changes to the proposed scheme I gave you are required if you want T1 users to be able to switch to backup line, e.g. oc-48 or T3 in case of failure.

Subject: Re: multiple NICs on Different Networks with different default gateways
Posted by [zerodni](#) on Mon, 24 Apr 2006 18:20:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

not so much as im looking for vps that are on the t1 network to work by them selves and the the

oc line vps to work by themselves because for some reason when the t1 is unplugged the vps on the oc line stop working because of the host system being set to have the t1 as the default gateway basically im trying to build 2 separate networks inside of the vps host system.

Thanks for all you help

Subject: Re: multiple NICs on Different Networks with different default gateways
Posted by [Antarion](#) on Mon, 24 Apr 2006 20:06:43 GMT

[View Forum Message](#) <> [Reply to Message](#)

I've been working on a similar setup for quite a while now, heres what i've got - it already comes pretty close to what i want. Just remember, these are my first steps with iproute2 and routing in general

My hostnode does have two NIC's, eth0 which does have a vlan covering the 62.75.xxx.yyy/24 range, eth1 which does have a vlan covering the 217.172.xxx.yyy/24 range.

Heres my CURRENT setup:

```
# flush everything
ip route flush cache

# set default routes for table 1 & 2
ip route add default via 62.75.xxx.1 dev eth0 tab 1
ip route add default via 217.172.xxx.1 dev eth1 tab 2

# add IP's within 62.75.xxx.0/24 to be used by VE's
ip rule add from 62.75.xxx.0/24 tab 1 priority 500

# Routing to VE's in the other "vlan"
# otherwise loop between hostnode
# and our default gateway (!?!?)
ip rule add from 62.75.xxx.0/24 iif venet0 lookup main

# add IPs within 217.172.xxx.0/24 to be used by VE's
ip rule add from 217.172.xxx.0/24 tab 2 priority 600

# Routing to VE's in the other "vlan"
# otherwise loop between hostnode
# and our default gateway (!?!?)
ip rule add from 217.172.xxx.0/24 iif venet0 lookup main

# ---- not sure if this is needed ----
ip route del default
ip route del default
ip route add default via 217.172.xxx.1 dev eth1
```

Maybe that helps, if you've got any suggestions let me know please!

-Torsten

Subject: Re: multiple NICs on Different Networks with different default gateways
Posted by [zerodni](#) on Tue, 06 Jun 2006 14:07:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

i was just wondering what the output is from the route command with this configuration

Thanks
Jacob

Subject: Re: multiple NICs on Different Networks with different default gateways
Posted by [kir](#) on Thu, 20 Jul 2006 17:44:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

This thread is summarised on wiki:Source based routing.
