

---

Subject: Network configuration

Posted by [Yoann Moulin](#) on Wed, 12 Dec 2007 17:01:04 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi all,

I'm currently working on a xen to openvz migration and some I have problem to setup the network configuration.

I'm using the latest kernel patch build to support nfsroot for the openvz host under ubuntu dapper 6.06 LTS

I will have at least 12 vlan on the OVZ host, and 2 or 3 vlan in each VE

for example, NETIF for the VEID 101

```
NETIF="ifname=eth1.10,mac=00:16:3E:00:00:1E,host_ifname=veth101.10,host_mac=00:E0:81:4B:2F:DB;ifname=eth1.19,mac=00:16:3E:00:00:1E,host_ifname=veth101&.19,host_mac=00:E0:81:4B:2F:DB"
```

and I want an EXTERNAL\_SCRIPT that check if the bridge exist, and if not create and add the interface

my first idea was adding a new variable that indicate all the vlan we have to configure :

```
VETH_BRIDGE="brvlan10 brvlan19"
```

with this script :

```
---- BEGIN SCRIPT ----
```

```
#!/bin/bash
```

```
# /usr/sbin/vznetaddroute
```

```
# a script to bring up virtual network interfaces (veth's) in a VE
```

```
CONFIGFILE=/etc/vz/conf/$VEID.conf
```

```
. $CONFIGFILE
```

```
VZHOSTIF=`echo $NETIF |sed 's/^.*host_ifname=\\(.*)\\.\\.\\. *.*$/1/g`
```

```
for BRIDGE in ${VETH_BRIDGE} ; do
```

```
    VLAN=`echo ${BRIDGE} | sed 's/brvlan//`
```

```
    if [ ! -n "${VZHOSTIF}.${VLAN}" ]; then
```

```
        echo "According to $CONFIGFILE VE$VEID has no veth interface configured."
```

```
        exit 1
```

```
    fi
```

```
    if [ ! -n "${BRIDGE}" ]; then
```

```
        echo "According to $CONFIGFILE VE$VEID has no veth bridge configured."
```

```

    exit 1
fi

echo "Adding interface ${VZHOSTIF}.${VLAN} to bridge ${BRIDGE} on VE0"

if [ -z "`/usr/sbin/brctl show | /bin/grep ${BRIDGE}`" ]; then
    /usr/sbin/brctl addbr ${BRIDGE}
    /usr/sbin/brctl addif ${BRIDGE} eth1.${VLAN}
    /sbin/ip link set ${BRIDGE} up
fi

    /usr/sbin/brctl addif ${BRIDGE} ${VZHOSTIF}.${VLAN}
    /sbin/ip link set ${VZHOSTIF}.${VLAN} up
done

exit 0
---- END SCRIPT ----

```

When I start my VE, I have :

```

# vzctl start 101
Starting VE ...
VE is mounted
Setting CPU limit: 241132
Setting CPU units: 55555
Configure meminfo: 502650
Set hostname: adviseo03
Configure veth devices: veth101.10 veth101.19
Adding interface veth101.10 to bridge brvlan10 on VE0
Adding interface veth101.19 to bridge brvlan19 on VE0
interface veth101.19 does not exist!
SIOCGIFFLAGS: No such device
Adding interface veth101.10 to bridge brvlan10 on VE0
device veth101.10 is already a member of a bridge; can't enslave it to bridge brvlan10.
Adding interface veth101.19 to bridge brvlan19 on VE0
VE start in progress...

```

so at start vzctl already know we will have 2 net device : "Configure veth devices: veth101.10 veth101.19"

so the EXTERNAL\_SCRIPT is execute 2 times, one time for each veth, so I shouldn't need to setup VETH\_BRIDGE if in the EXTERNAL\_SCRIPT, I'm able to know with veth is currently configured

It's not easy to explain until it is still quite complicated for me

so the question is :

is it possible to know in the EXTERNAL\_SCRIPT, for which interface, the script is execute ?

thanks for your help

Yoann

ps : already sent this message at 5:30pm GMT+1 but not arrived yet a 6:00 GMT+1

---

Subject: Re: Network configuration

Posted by [Yoann Moulin](#) on Wed, 12 Dec 2007 17:57:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

> is it possible to know in the EXTERNAL\_SCRIPT, for which interface, the  
> script is execute ?

Well, I gave a look to the source code and got my answer (\$3)... it's working perfectly.

NETIF still the same :

```
NETIF="ifname=eth1.10,mac=00:16:3E:00:00:1E,host_ifname=veth10.10,host_mac=00:E0:81:4B:2F:DB;ifname=eth1.19,mac=00:16:3E:00:00:1E,host_ifname=veth10.19,host_mac=00:E0:81:4B:2F:DB"
```

and the script begin :

```
---- BEGIN SCRIPT ----
```

```
#!/bin/bash
```

```
# /usr/sbin/vznetaddroute
```

```
# a script to bring up virtual network interfaces (veth's) in a VE
```

```
CONFIGFILE=/etc/vz/conf/$VEID.conf
```

```
. $CONFIGFILE
```

```
VETH=$3
```

```
VZHOSTIF=`echo ${VETH} | cut -f1 -d"."`
```

```
VLAN=`echo ${VETH} | cut -f2 -d"."`
```

```
VETH_BRIDGE=brvlan${VLAN}
```

```
if [ ! -n "${VZHOSTIF}.${VLAN}" ]; then
```

```
    echo "According to $CONFIGFILE VE$VEID has no veth interface configured."
```

```
    exit 1
```

```
fi
```

```
if [ ! -n "${VETH_BRIDGE}" ]; then
```

```
    echo "According to $CONFIGFILE VE$VEID has no veth VETH_BRIDGE configured."
```

```
    exit 1
```

```
fi
```

```
echo "Adding interface ${VZHOSTIF}.${VLAN} to VETH_BRIDGE ${VETH_BRIDGE} on VE0"
```

```
if [ -z "`/usr/sbin/brctl show | /bin/grep ${VETH_BRIDGE}`" ]; then
  /usr/sbin/brctl addbr ${VETH_BRIDGE}
  /usr/sbin/brctl addif ${VETH_BRIDGE} eth1.${VLAN}
  /sbin/ip link set ${VETH_BRIDGE} up
fi
```

```
/usr/sbin/brctl addif ${VETH_BRIDGE} ${VZHOSTIF}.${VLAN}
/sbin/ip link set ${VZHOSTIF}.${VLAN} up
exit 0
---- END SCRIPT ----
```

sorry for the noise

Yoann

---