
Subject: Network configuration

Posted by [Yoann Moulin](#) on Wed, 12 Dec 2007 16:30:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi all,

I'm currently working on a xen to openvz migration and some I have problem to setup the network configuration.

I'm using the latest kernel patch build to support nfsroot for the openvz host under ubuntu dapper 6.06 LTS

I will have at least 12 vlan on the OVZ host, and 2 or 3 vlan in each VE

for example, NETIF for the VEID 101

```
NETIF="ifname=eth1.10,mac=00:16:3E:00:00:1E,host_ifname=veth101.10,host_mac=00:E0:81:4B:2F:DB;ifname=eth1.19,mac=00:16:3E:00:00:1E,host_ifname=veth101&.19,host_mac=00:E0:81:4B:2F:DB"
```

and I want an EXTERNAL_SCRIPT that check if the bridge exist, and if not create and add the interface

my first idea was adding a new variable that indicate all the vlan we have to configure :

```
VETH_BRIDGE="brvlan10 brvlan19"
```

with this script :

```
---- BEGIN SCRIPT ----
```

```
#!/bin/bash
```

```
# /usr/sbin/vznetaddroute
```

```
# a script to bring up virtual network interfaces (veth's) in a VE
```

```
CONFIGFILE=/etc/vz/conf/$VEID.conf
```

```
. $CONFIGFILE
```

```
VZHOSTIF=`echo $NETIF |sed 's/^.*host_ifname=\\(.*)\\.\\.\\. *.*$/1/g`
```

```
for BRIDGE in ${VETH_BRIDGE} ; do
```

```
    VLAN=`echo ${BRIDGE} | sed 's/brvlan/'`
```

```
    if [ ! -n "${VZHOSTIF}.${VLAN}" ]; then
```

```
        echo "According to $CONFIGFILE VE$VEID has no veth interface configured."
```

```
        exit 1
```

```
    fi
```

```
    if [ ! -n "${BRIDGE}" ]; then
```

```
        echo "According to $CONFIGFILE VE$VEID has no veth bridge configured."
```

```

    exit 1
fi

echo "Adding interface ${VZHOSTIF}.${VLAN} to bridge ${BRIDGE} on VE0"

if [ -z "`/usr/sbin/brctl show | /bin/grep ${BRIDGE}`" ]; then
    /usr/sbin/brctl addbr ${BRIDGE}
    /usr/sbin/brctl addif ${BRIDGE} eth1.${VLAN}
    /sbin/ip link set ${BRIDGE} up
fi

/usr/sbin/brctl addif ${BRIDGE} ${VZHOSTIF}.${VLAN}
/sbin/ip link set ${VZHOSTIF}.${VLAN} up
done

exit 0
---- END SCRIPT ----

```

When I start my VE, I have :

```

# vzctl start 101
Starting VE ...
VE is mounted
Setting CPU limit: 241132
Setting CPU units: 55555
Configure meminfo: 502650
Set hostname: adviseo03
Configure veth devices: veth101.10 veth101.19
Adding interface veth101.10 to bridge brvlan10 on VE0
Adding interface veth101.19 to bridge brvlan19 on VE0
interface veth101.19 does not exist!
SIOCGIFFLAGS: No such device
Adding interface veth101.10 to bridge brvlan10 on VE0
device veth101.10 is already a member of a bridge; can't enslave it to bridge brvlan10.
Adding interface veth101.19 to bridge brvlan19 on VE0
VE start in progress...

```

so at start vzctl already know we will have 2 net device : "Configure veth devices: veth101.10 veth101.19"

so the EXTERNAL_SCRIPT is execute 2 times, one time for each veth, so I shouldn't need to setup VETH_BRIDGE if in the EXTERNAL_SCRIPT, I'm able to know with veth is currently configured

It's not easy to explain until it is still quite complicated for me

so the question is :

is it possible to know in the EXTERNAL_SCRIPT, for which interface, the script is execute ?

thanks for your help

Yoann

Subject: Re: Network configuration
Posted by [b52_](#) on Wed, 13 Feb 2008 17:15:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

>so the question is :
>
>is it possible to know in the EXTERNAL_SCRIPT, for which interface, the
>script is execute ?

Hi,

your script will be executed with parameters.

I tried this to find them out:

```
mrwhite:/# cat /etc/vz/vznet.conf  
EXTERNAL_SCRIPT="/opt/sbin/vznetaddnet"
```

```
mrwhite:/# cat /opt/sbin/vznetaddnet  
#!/bin/bash  
echo $@
```

and while startup this prints:
init veth veth101.10
init veth veth101.20

bye,b52
