
Subject: [PATCH 2.6.25] compilation fix for drivers/net/wireless/libertas/debugfs.c
Posted by [den](#) on Thu, 27 Dec 2007 10:23:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

Compilation fix. MAC_FMT is required for
drivers/net/wireless/libertas/debugfs.c

The problem has been introduced by the
commit 4b326fa2167d4ee2d722bff4e241fae299e32442
Author: Michael Chan <mchan@broadcom.com>
Date: Mon Dec 24 21:28:09 2007 -0800

```
diff --git a/include/linux/if_ether.h b/include/linux/if_ether.h
index 7a1e011..2928586 100644
--- a/include/linux/if_ether.h
+++ b/include/linux/if_ether.h
@@ -129,6 +129,7 @@ extern ssize_t sysfs_format_mac(char *buf, const unsigned char *addr,
int len);
/*
 * Display a 6 byte device address (MAC) in a readable format.
 */
+#define MAC_FMT "%02x:%02x:%02x:%02x:%02x:%02x"
extern char *print_mac(char *buf, const unsigned char *addr);
#define MAC_BUF_SIZE 18
#define DECLARE_MAC_BUF(var) char var[MAC_BUF_SIZE] __maybe_unused
```

Subject: Re: [PATCH 2.6.25] compilation fix for
drivers/net/wireless/libertas/debugfs.c
Posted by [davem](#) on Fri, 28 Dec 2007 00:45:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: "Denis V. Lunev" <den@openvz.org>
Date: Thu, 27 Dec 2007 13:24:54 +0300

> Compilation fix. MAC_FMT is required for
> drivers/net/wireless/libertas/debugfs.c

Putting this public macro back into a header file just
for one driver's debug handling is just ridiculous.

I've checked in the following fix instead, thanks.

commit f7b4d3b86615b95b104ca0a95902ca86373a6548
Author: David S. Miller <davem@davemloft.net>
Date: Thu Dec 27 16:43:38 2007 -0800

[LIBERTAS]: Remove last stray user of MAC_FMT.

Reported by Denis V. Lunev

Signed-off-by: David S. Miller <davem@davemloft.net>

```
diff --git a/drivers/net/wireless/libertas/debugfs.c b/drivers/net/wireless/libertas/debugfs.c
index 0bda0b5..95dd4ed 100644
--- a/drivers/net/wireless/libertas/debugfs.c
+++ b/drivers/net/wireless/libertas/debugfs.c
@@ -243,7 +243,8 @@ static void libertas_parse_bssid(char *buf, size_t count,
    if (!hold)
        return;
    hold += 6;
- sscanf(hold, MAC_FMT, mac, mac+1, mac+2, mac+3, mac+4, mac+5);
+ sscanf(hold, "%02x:%02x:%02x:%02x:%02x:%02x",
+        mac, mac+1, mac+2, mac+3, mac+4, mac+5);
    memcpy(scan_cfg->bssid, mac, ETH_ALEN);
}
```
