Subject: dhcpd problem
Posted by m.tinnemeier@squild.de on Thu, 17 Jan 2008 11:25:22 GMT
View Forum Message <> Reply to Message

Hi folks,

we have some strange problems with a dhcpd inside a vps.

We configured our VPS to bridge veth with hosts eth0. The actual problem is that some of our clients don't get ip addresses from the dhcpd with client-side error message that the ip adress this client asked for is actually used by ehternet id xx.xx... - the given ethernet id is the id of the host-side veth-device of the dhcp vps.

can anyone help?

regars,
matthias

our config in detail:

DHCPd-Log auf VPS

[...]
VPS dhcpd: DHCPDISCOVER from 00:1c:b3:bd:ac:d4 via eth0
VPS dhcpd: DHCPOFFER on 192.168.55.200 to 00:1c:b3:bd:ac:d4 via eth0
VPS dhcpd: DHCPREQUEST for 192.168.55.200 (192.168.55.11) from 00:1c:b3:bd:ac:d4 via eth0
VPS dhcpd: DHCPACK on 192.168.55.200 to 00:1c:b3:bd:ac:d4 via eth0
VPS dhcpd: DHCPREQUEST for 192.168.55.200 (192.168.55.11) from 00:1c:b3:bd:ac:d4 via eth0
VPS dhcpd: DHCPACK on 192.168.55.200 to 00:1c:b3:bd:ac:d4 via eth0
VPS dhcpd: Abandoning IP address 192.168.55.200: declined.
VPS dhcpd: DHCPDECLINE of 192.168.55.200 from 00:1c:b3:bd:ac:d4 via eth0: not found
[...]

Netzwerk-Setup VE0:

```
# The loopback network interface
auto lo
iface lo inet loopback
```

```
# OPENVZ anonymous bridge
#
# (anonymous bridge = a bridge without
# an assigned IP)
auto br0
iface br0 inet manual
 bridge_ports eth0
 bridge_maxwait 0


# The primary network interface
auto eth0
iface eth0 inet static
 address 192.168.55.5
 network 192.168.55.0
 netmask 255.255.255.0
 broadcast 192.168.55.255
 gateway 192.168.55.254
```

Routingtabelle DHCPd-VPS

```
# ip route show
192.168.55.11 dev br0  scope link
192.168.55.5 dev br0  scope link
192.168.55.0/24 dev eth0  proto kernel  scope link  src 192.168.55.5
default via 192.168.55.254 dev eth0
```

Netzwerk-Interfaces VE0

```
# ifconfig -a
br0       Protokoll:Ethernet  Hardware Adresse 00:0C:29:0C:7A:1A
          inet6 Adresse: fe80::218:f3ff:fe0d:2edd/64 GÃ¼ltigkeitsbereich:Verbindung
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:24758 errors:0 dropped:0 overruns:0 frame:0
          TX packets:2917 errors:0 dropped:0 overruns:0 carrier:0
          Kollisionen:0 SendewarteschlangenlÃ¤nge:0
          RX bytes:3819612 (3.6 MiB)  TX bytes:236898 (231.3 KiB)

eth0      Protokoll:Ethernet  Hardware Adresse 00:18:F3:0D:2E:DD
          inet Adresse:192.168.55.5  Bcast:192.168.55.255  Maske:255.255.255.0
          inet6 Adresse: fe80::218:f3ff:fe0d:2edd/64 GÃ¼ltigkeitsbereich:Verbindung
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:42497 errors:0 dropped:0 overruns:0 frame:0
          TX packets:30174 errors:0 dropped:0 overruns:0 carrier:0
          Kollisionen:0 SendewarteschlangenlÃ¤nge:1000
```

```
          RX bytes:6101271 (5.8 MiB)  TX bytes:6908267 (6.5 MiB)
          Interrupt:193

lo        Protokoll:Lokale Schleife
          inet Adresse:127.0.0.1  Maske:255.0.0.0
          inet6 Adresse: ::1/128 GÃ¼ltigkeitsbereich:Maschine
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:106 errors:0 dropped:0 overruns:0 frame:0
          TX packets:106 errors:0 dropped:0 overruns:0 carrier:0
          Kollisionen:0 SendewarteschlangenlÃ¤nge:0
          RX bytes:10878 (10.6 KiB)  TX bytes:10878 (10.6 KiB)

sit0      Protokoll:IPv6-nach-IPv4
          NOARP  MTU:1480  Metric:1
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0
          TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
          Kollisionen:0 SendewarteschlangenlÃ¤nge:0
          RX bytes:0 (0.0 b)  TX bytes:0 (0.0 b)

veth100.0 Protokoll:Ethernet  Hardware Adresse 00:0C:29:0C:7A:3A
          inet6 Adresse: fe80::20c:29ff:fe0c:7a3a/64 GÃ¼ltigkeitsbereich:Verbindung
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:3822 errors:0 dropped:0 overruns:0 frame:0
          TX packets:12067 errors:0 dropped:0 overruns:0 carrier:0
          Kollisionen:0 SendewarteschlangenlÃ¤nge:0
          RX bytes:2919192 (2.7 MiB)  TX bytes:1260384 (1.2 MiB)


-------------------------------------
Bridge VE0

# brctl show
bridge name bridge id  STP enabled interfaces
br0  8000.000c290c7a1a no  eth0
     veth100.0




-------------------------------------
Relevanter Auszug aus der VPS-Config
Rest Standard:


# cat /etc/vz/conf/100.conf

[...]
```

```
# Don't create a venet device!
#IP_ADDRESS=""

CONFIG_CUSTOMIZED="yes"

# Bridged networking
VZHOSTBR="br0"
VETH_IP_ADDRESS="192.168.55.11"
NETIF="ifname=eth0,mac=00:0C:29:0C:7A:2B,host_ifname=veth100.0,host_mac=00:0C:29:0C:7
A:3A"
```

Netzwerk-Setup DHCPd-VPS

```
# Auto generated interfaces
auto lo
iface lo inet loopback

auto eth0
iface eth0 inet static
 address 192.168.55.11
 netmask 255.255.255.0
 broadcast 192.168.55.255
 network 192.168.55.0
 gateway 192.168.55.254
 dns-nameserver 192.168.55.11
```

Routingtabelle DHCPd-VPS

```
# ip route show
192.168.55.0/24 dev eth0  proto kernel  scope link  src 192.168.55.11
default via 192.168.55.254 dev eth0
```