Subject: [PATCH 2/4] Pidns: fix badly converted mqueues pid handling
Posted by Pavel Emelianov on Mon, 28 Jan 2008 15:10:19 GMT

When sending the pid namespaces patches I wrongly converted
the tsk->tgid into task_pid_vnr(tsk) in mqueue-s (the git id
of this patch is b488893a390edfe027bae7a46e9af8083e740668).

The proper behavior is to get the task_tgid_vnr(tsk).

This seem to be the only mistake of that kind.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
 ipc/mqueue.c |   2 +-
 1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/ipc/mqueue.c b/ipc/mqueue.c
index eb3f489..b83e983 100644
--- a/ipc/mqueue.c
+++ b/ipc/mqueue.c
@@ -509,7 +509,7 @@ static void __do_notify(struct mqueue_inode_info *info)
   sig_i.si_errno = 0;
   sig_i.si_code = SI_MESGQ;
   sig_i.si_value = info->notify.sigev_value;
-  sig_i.si_pid = task_pid_vnr(current);
+   sig_i.si_pid = task_tgid_vnr(current);
   sig_i.si_uid = current->uid;

   kill_pid_info(info->notify.sigev_signo,
--
1.5.3.4
```