

---

Subject: Discovering VE0 from within a VE  
Posted by [jmelyn](#) on Tue, 05 Feb 2008 13:23:01 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hi there,

My question is: Is it possible to know the name of the host OS (VE0) directly from a VE?

Thanx in advance,

JMElyn.

---

---

Subject: Re: Discovering VE0 from within a VE  
Posted by [kir](#) on Tue, 05 Feb 2008 13:25:00 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

What do you mean by name?

---

---

Subject: Re: Discovering VE0 from within a VE  
Posted by [jmelyn](#) on Tue, 05 Feb 2008 13:39:09 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

I would like to know \${HOSTNAME} of VE0. This is not so static as a VE can migrate from a HN to another one.

---

---

Subject: Re: Discovering VE0 from within a VE  
Posted by [kir](#) on Tue, 05 Feb 2008 13:44:30 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

You can't know the hostname. You can know host system IP though if you run traceroute/tracepath to some remote IP, as every packet goes through host system.

---

---

Subject: [SOLVED] Re: Discovering VE0 from within a VE  
Posted by [jmelyn](#) on Tue, 05 Feb 2008 14:00:31 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

So the command:

```
traceroute aComputer | awk '/^ 1 / {print $2}'
```

will give me the name of the host! That's finally rather simple  
Thank you Kir!

---