
Subject: [PATCH] [IPV4]: Remove warning in node_set_parent.

Posted by [den](#) on Mon, 11 Feb 2008 08:47:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

net/ipv4/fib_trie.c: In function 'node_set_parent':
net/ipv4/fib_trie.c:184: warning: assignment makes integer from pointer
without a cast

Signed-off-by: Denis V. Lunev <den@openvz.org>

net/ipv4/fib_trie.c | 7 ++++---

1 files changed, 4 insertions(+), 3 deletions(-)

diff --git a/net/ipv4/fib_trie.c b/net/ipv4/fib_trie.c

index f5fba3f..1753cd4 100644

--- a/net/ipv4/fib_trie.c

+++ b/net/ipv4/fib_trie.c

```
@@ -177,10 +177,11 @@ static inline struct tnode *node_parent_rcu(struct node *node)
    return rcu_dereference(ret);
}
```

```
-static inline void node_set_parent(struct node *node, struct tnode *ptr)
+static inline void node_set_parent(struct node *node, struct tnode *__ptr)
{
- rcu_assign_pointer(node->parent,
-    (unsigned long)ptr | NODE_TYPE(node));
+ struct node *ptr;
+ ptr = (struct node *)((unsigned long)__ptr | NODE_TYPE(node));
+ rcu_assign_pointer(node->parent, ptr);
}
```

```
static inline struct node *tnode_get_child(struct tnode *tn, unsigned int i)
```

--

1.5.3.rc5

Subject: Re: [PATCH] [IPV4]: Remove warning in node_set_parent.

Posted by [Stephen Hemminger](#) on Mon, 11 Feb 2008 19:48:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Mon, 11 Feb 2008 11:47:17 +0300

"Denis V. Lunev" <den@openvz.org> wrote:

> net/ipv4/fib_trie.c: In function 'node_set_parent':

> net/ipv4/fib_trie.c:184: warning: assignment makes integer from pointer

> without a cast

>

> Signed-off-by: Denis V. Lunev <den@openvz.org>

```

> ---
> net/ipv4/fib_trie.c | 7 ++++---
> 1 files changed, 4 insertions(+), 3 deletions(-)
>
> diff --git a/net/ipv4/fib_trie.c b/net/ipv4/fib_trie.c
> index f5fba3f..1753cd4 100644
> --- a/net/ipv4/fib_trie.c
> +++ b/net/ipv4/fib_trie.c
> @@ -177,10 +177,11 @@ static inline struct tnode *node_parent_rcu(struct node *node)
>  return rcu_dereference(ret);
> }
>
> -static inline void node_set_parent(struct node *node, struct tnode *ptr)
> +static inline void node_set_parent(struct node *node, struct tnode *__ptr)
> {
> - rcu_assign_pointer(node->parent,
> - (unsigned long)ptr | NODE_TYPE(node));
> + struct node *ptr;
> + ptr = (struct node *)((unsigned long)__ptr | NODE_TYPE(node));
> + rcu_assign_pointer(node->parent, ptr);
> }
>
> static inline struct node *tnode_get_child(struct tnode *tn, unsigned int i)

```

No, this causes new warning from assigning pointer (ptr) to integer node->parent.

Why not just change rcupdate.h to do the right thing.

```

>From a00f7cbf1c2f2282eced236e1e8b99b0fec213a Mon Sep 17 00:00:00 2001
From: Stephen Hemminger <stephen.hemminger@vyatta.com>
Date: Mon, 11 Feb 2008 11:28:13 -0800
Subject: [PATCH] eliminate warnings when rcu_assign_pointer is used with unsigned long

```

It is reasonable to use RCU with non-pointer values, and describe the optimization.

Signed-off-by: Stephen Hemminger <shemminger@vyatta.com>

```

include/linux/rcupdate.h | 13 ++++++-----
1 files changed, 7 insertions(+), 6 deletions(-)

```

```

diff --git a/include/linux/rcupdate.h b/include/linux/rcupdate.h
index 37a642c..c44ac87 100644
--- a/include/linux/rcupdate.h
+++ b/include/linux/rcupdate.h
@@ -172,14 +172,15 @@ struct rcu_head {
 * structure after the pointer assignment. More importantly, this
 * call documents which pointers will be dereferenced by RCU read-side

```

```

* code.
+ *
+ * If value is the NULL (constant 0), then no barrier is needed.
*/

```

```

-#define rcu_assign_pointer(p, v) \
- ({ \
-  if (!__builtin_constant_p(v) || \
-      (v) != NULL)) \
-    smp_wmb(); \
-  (p) = (v); \
+#define rcu_assign_pointer(p, v) \
+ ({ \
+  if (!__builtin_constant_p(v) && v)) \
+    smp_wmb(); \
+  (p) = (v); \
+ })

```

```

/**

```

```

--

```

1.5.3.8

```

--

```

Stephen Hemminger <stephen.hemminger@vyatta.com>

Subject: Re: [PATCH] [IPV4]: Remove warning in node_set_parent.

Posted by [den](#) on Tue, 12 Feb 2008 08:11:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

ugly :), but

Acked-by: Denis V. Lunev <den@openvz.org>

On Mon, 2008-02-11 at 11:48 -0800, Stephen Hemminger wrote:

> On Mon, 11 Feb 2008 11:47:17 +0300

> "Denis V. Lunev" <den@openvz.org> wrote:

>

> > net/ipv4/fib_trie.c: In function 'node_set_parent':

> > net/ipv4/fib_trie.c:184: warning: assignment makes integer from pointer

> > without a cast

> >

> > Signed-off-by: Denis V. Lunev <den@openvz.org>

> > ---

> > net/ipv4/fib_trie.c | 7 ++++---

```

> > 1 files changed, 4 insertions(+), 3 deletions(-)
> >
> > diff --git a/net/ipv4/fib_trie.c b/net/ipv4/fib_trie.c
> > index f5fba3f..1753cd4 100644
> > --- a/net/ipv4/fib_trie.c
> > +++ b/net/ipv4/fib_trie.c
> > @@ -177,10 +177,11 @@ static inline struct tnode *node_parent_rcu(struct node *node)
> >     return rcu_dereference(ret);
> > }
> >
> > -static inline void node_set_parent(struct node *node, struct tnode *ptr)
> > +static inline void node_set_parent(struct node *node, struct tnode *__ptr)
> > {
> > - rcu_assign_pointer(node->parent,
> > -     (unsigned long)ptr | NODE_TYPE(node));
> > + struct node *ptr;
> > + ptr = (struct node *)((unsigned long)__ptr | NODE_TYPE(node));
> > + rcu_assign_pointer(node->parent, ptr);
> > }
> >
> > static inline struct node *tnode_get_child(struct tnode *tn, unsigned int i)
>
> No, this causes new warning from assigning pointer (ptr) to integer node->parent.
>
> Why not just change rcupdate.h to do the right thing.
>
> >From a00f7cbf1c2f2282eced236e1e8b99b0fec213a Mon Sep 17 00:00:00 2001
> From: Stephen Hemminger <stephen.hemminger@vyatta.com>
> Date: Mon, 11 Feb 2008 11:28:13 -0800
> Subject: [PATCH] eliminate warnings when rcu_assign_pointer is used with unsigned long
>
> It is reasonable to use RCU with non-pointer values, and describe
> the optimization.
>
> Signed-off-by: Stephen Hemminger <shemminger@vyatta.com>
> ---
> include/linux/rcupdate.h | 13 ++++++-----
> 1 files changed, 7 insertions(+), 6 deletions(-)
>
> diff --git a/include/linux/rcupdate.h b/include/linux/rcupdate.h
> index 37a642c..c44ac87 100644
> --- a/include/linux/rcupdate.h
> +++ b/include/linux/rcupdate.h
> @@ -172,14 +172,15 @@ struct rcu_head {
>  * structure after the pointer assignment. More importantly, this
>  * call documents which pointers will be dereferenced by RCU read-side
>  * code.
> + *

```

```
> + * If value is the NULL (constant 0), then no barrier is needed.
> */
>
> -#define rcu_assign_pointer(p, v) \
> - ({ \
> -   if (!__builtin_constant_p(v) || \
> -       ((v) != NULL)) \
> -     smp_wmb(); \
> -   (p) = (v); \
> +#define rcu_assign_pointer(p, v) \
> + ({ \
> +   if (!__builtin_constant_p(v) && v) \
> +     smp_wmb(); \
> +   (p) = (v); \
> })
>
> /**
> --
> 1.5.3.8
>
>
>
>
```
