
Subject: NFS-client patch

Posted by [Groening](#) on Fri, 05 May 2006 05:04:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

We have a patch by dev to make NFS-client work in VPS:

```
diff -r -u linux-2.6.16-ovz/arch/i386/kernel/process.c  
linux-2.6.16-ovz_with_nfs/arch/i386/kernel/process.c  
--- linux-2.6.16-ovz/arch/i386/kernel/process.c 2006-04-14 12:53:49.000000000 +0000
```

```
+++ linux-2.6.16-ovz_with_nfs/arch/i386/kernel/process.c      2006-04-14 13:01:23.000000000  
+0000  
@@ -341,13 +341,6 @@
```

```
{
```

```
    struct pt_regs regs;
```

```
-     /* Don't allow kernel_thread() inside VE */  
  
-     if (!ve_is_super(get_exec_env())) {  
  
-         printk("kernel_thread call inside VE\n");  
  
-         dump_stack();  
  
-         return -EPERM;  
  
-     }
```

```
-
```

```
    memset(&regs, 0, sizeof(regs));
```

```
    regs.ebx = (unsigned long) fn;
```

```
diff -r -u linux-2.6.16-ovz/fs/nfs/inode.c linux-2.6.16-ovz_with_nfs/fs/nfs/inode.c
```

```
--- linux-2.6.16-ovz/fs/nfs/inode.c   2006-04-14 12:53:17.000000000 +0000
```

```
+++ linux-2.6.16-ovz_with_nfs/fs/nfs/inode.c 2006-04-14 12:58:40.000000000 +0000
```

```
@@ -1721,7 +1721,7 @@
```

```
    .name      = "nfs",
```

```
.get_sb      = nfs_get_sb,
.kill_sb     = nfs_kill_super,
- .fs_flags    = FS_ODD_RENAME|FS_REVAL_DOT|FS_BINARY_MOUNTDATA,
+ .fs_flags    =
FS_ODD_RENAME|FS_REVAL_DOT|FS_BINARY_MOUNTDATA|FS_VIRTUALIZED,
};

#endif CONFIG_NFS_V4
```

```
diff -r -u linux-2.6.16-ovz/kernel/exit.c linux-2.6.16-ovz_with_nfs/kernel/exit.c
```

```
--- linux-2.6.16-ovz/kernel/exit.c 2006-04-14 12:53:49.000000000 +0000
```

```
+++ linux-2.6.16-ovz_with_nfs/kernel/exit.c 2006-04-14 13:00:32.000000000 +0000
```

```
@@ -276,9 +276,6 @@
```

```
{
```

```
    struct task_struct *curr = current->group_leader;
```

```
-    WARN_ON(is_virtual_pid(pgrp));
```

```
-    WARN_ON(is_virtual_pid(session));
```

```
-
```

```
    if (curr->signal->session != session) {
```

```
        detach_pid(curr, PIDTYPE_SID);
```

```
        curr->signal->session = session;
```

```
diff -r -u linux-2.6.16-ovz/net/sunrpc/rpc_pipe.c linux-2.6.16-ovz_with_nfs/net/sunrpc/rpc_pipe.c
```

```
--- linux-2.6.16-ovz/net/sunrpc/rpc_pipe.c 2006-04-14 12:53:20.000000000 +0000
```

```
+++ linux-2.6.16-ovz_with_nfs/net/sunrpc/rpc_pipe.c 2006-04-14 12:59:46.000000000 +0000
```

```
@@ -824,6 +824,7 @@
```

```
.name      = "rpc_pipefs",
.get_sb    = rpc_get_sb,
.kill_sb   = kill_litter_super,
+.fs_flags = FS_VIRTUALIZED,
};
```

```
static void
```

```
and this work, but if we apply patch where will be removed piece:
```

```
diff -r -u linux-2.6.16-ovz/arch/i386/kernel/process.c
linux-2.6.16-ovz_with_nfs/arch/i386/kernel/process.c
--- linux-2.6.16-ovz/arch/i386/kernel/process.c 2006-04-14 12:53:49.000000000 +0000
```

```
+++ linux-2.6.16-ovz_with_nfs/arch/i386/kernel/process.c      2006-04-14 13:01:23.000000000
+0000
@@ -341,13 +341,6 @@
```

```
{
```

```
    struct pt_regs regs;
```

```
-    /* Don't allow kernel_thread() inside VE */
-
-    if (!ve_is_super(get_exec_env())) {
-
-        printk("kernel_thread call inside VE\n");
-
-        dump_stack();
-
-        return -EPERM;
-
-    }
```

```
    memset(&regs, 0, sizeof(regs));
```

regs.ebx = (unsigned long) fn;
this patch also will be works.

Attention! Questions:

- 1) If this patch work, why it don't included in distributive?
 - 2) Why if we removed piece, which turn on kernel threads in VPS, this patch is also works?
 - 3) And why in openvz turned off kernel threads? (more technical details please)
-
-

Subject: Re: NFS-client patch

Posted by [Vasily Tarasov](#) on Fri, 05 May 2006 06:11:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

> 2) Why if we removed piece, which turn on kernel threads in VPS, this patch is also works?

This patch was ported from 2.4 kernel, and there it's necessary for nfs to run kernel threads.

> 3) And why in openvz turned off kernel threads? (more technical details please)

AFAIK, for security reasons.
